

100%



PRODUCED  
RAN & OWNED

# Oracle Data Model

*for use with Invantive SQL*

23.0



# Copyright

(C) Copyright 2004-2023 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

## Important Safety and Usage Information

**Intended Use and Limitations:** This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting and sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weapon control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

**User Responsibility:** Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.

**Disclaimer of Liability:** Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

---

# Contents

<b>1</b>	<b>Provider OracleManaged: Oracle .NET driver-based provider.</b>	<b>1</b>
<b>2</b>	<b>Catalog: Database</b>	<b>2</b>
<b>2.1</b>	<b>Schemas .....</b>	<b>2</b>
2.1.1	Schema: Invantive .....	2
2.1.2	Schema: Native .....	2
	<b>Index</b>	<b>3</b>

## 1 Provider OracleManaged: Oracle .NET driver-based provider.

Oracle .NET driver-based provider.

Code for use in settings.xml: OracleManaged

Alias: oracle

Status: Production

Available in Editions: Paid

Additional Driver to install: <https://support.invantive.com/download-driver-oracle>

### Provider Attributes

The following provider attributes are available for OracleManaged:

Code	Description	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Provider's File
command-timeout-sec	Number of seconds after which a command times out.		✓	✓	✓
connection-string-self-tuning-add	Should the 'Self Tuning' be added automatically to the connection string?	True	✓	✓	✓
connection-string-self-tuning-value	Value of self tuning to be added to the connection string	True	✓	✓	✓
connection-string-statement-cache-size-add	Should the 'Statement Cache Size' be added automatically to the connection string?	True	✓	✓	✓
connection-string-statement-cache-size-value	Size of the statement cache size to be added to the connection string	250	✓	✓	✓
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	False	✓	✓	✓
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and Mixed.		✓	✓	✓
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	True	✓	✓	✓
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	False	✓	✓	✓
invantive-use-cache	Whether to cache the results of a query.	True	✓	✓	✓
maximum-length-identifiers	Non-default maximum length in characters of identifier names.		✓	✓	✓
maximum-number-of-pooled-connections	Maximum number of concurrent pooled connections.		✓	✓	✓
maximum-sleep-acquire-pooled-connection-ms	Maximum time in ms to wait for acquiring a free connection from a pool of connections.	30000	✓	✓	✓
maximum-sleep-acquire-unpooled-connection-ms	Maximum time in ms to wait for acquire a free connection when there is no connection pooling.	60000	✓	✓	✓

Code	Description	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Provider's File
preferred-number-of-pooled-connections	Preferred number of concurrent pooled connections.		✓	✓	✓
prefix-bind-variable-in-list	Prefix for bind variables used in an IN-list	i	✓	✓	✓
prefix-bind-variable-normal	Prefix for bind variables used in all cases except in an IN-list	w	✓	✓	✓
prefix-renamed-columns	Prefix appended to columns whose names occur multiple times in the column list of a query	column	✓	✓	✓
pre-request-delay-ms	Pre-request delay in milliseconds per request.	0	✓	✓	✓
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	32	✓	✓	✓
return-null-on-ora-22288	Return a null value instead of an exception when Oracle returns ORA-22288 when querying a bfile column	False	✓	✓	✓
slot-based-rate-limit-length-ms	Length in ms of a slot-based rate limit.	60000	✓		✓
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit		✓		✓
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	True	✓	✓	✓
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	True	✓	✓	✓
trace-native-calls	Trace native calls to data container backend.	False	✓	✓	✓

## 2 Catalog: Database

### 2.1 Schemas

#### 2.1.1 Schema: Invantive

##### 2.1.1.1 Tables

###### **PooledConnections: Pooled Connections**

Catalog: Database

Schema: Invantive

Label: Pooled Connections

#### 2.1.2 Schema: Native

##### 2.1.2.1 Tables

###### **NativePlatformScalarRequests: Native Platform Scalar Requests**

Catalog: Database

Schema: Native

Label: Native Platform Scalar Requests

# Index

## - C -

command-timeout-sec 1  
 connection-string-self-tuning-add 1  
 connection-string-self-tuning-value 1  
 connection-string-statement-cache-size-add 1  
 connection-string-statement-cache-size-value 1

## - F -

force-case-sensitive-identifiers 1  
 forced-casing-identifiers 1

## - I -

invantive-sql-forward-filters-to-data-containers 1  
 invantive-sql-shuffle-fetch-results-data-containers 1  
 invantive-use-cache 1

## - M -

maximum-length-identifiers 1  
 maximum-number-of-pooled-connections 1  
 maximum-sleep-acquire-pooled-connection-ms 1  
 maximum-sleep-acquire-unpooled-connection-ms 1

## - N -

Native Platform Scalar Requests 2  
 NativePlatformScalarRequests 2

## - O -

oracle 1  
 OracleManaged 1, 2

## - P -

Pooled Connections 2  
 PooledConnections 2  
 preferred-number-of-pooled-connections 1  
 prefix-bind-variable-in-list 1  
 prefix-bind-variable-normal 1  
 prefix-renamed-columns 1

pre-request-delay-ms 1

## - R -

requests-parallel-max 1  
 return-null-on-ora-22288 1

## - S -

slot-based-rate-limit-length-ms 1  
 slot-based-rate-limit-slots 1  
 standardize-identifiers 1  
 standardize-identifiers-casing 1

## - T -

trace-native-calls 1



# *invantive* the **SQL** company

Invantive B.V.  
Biesteweg 11  
3849 RD Hierden  
the Netherlands

Tel: +31 88 00 26 500  
Fax: +31 84 22 58 178  
info@invantive.com  
invantive.com

IBAN NL25 BUNQ 2098 2586 07  
Chamber of Industry and Commerce  
13031406  
VAT NL812602377B01  
RSIN 8122602377  
Managing Director: Guido Leenders  
Registered office: Roermond