



Atlassian Confluence Data Model

for use with Invantive SQL

Copyright

(C) Copyright 2004-2023 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

Important Safety and Usage Information

Intended Use and Limitations: This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting and sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weaponry control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

User Responsibility: Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.

Disclaimer of Liability: Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

Contents

1	SQL Driver for Atlassian Confluence API	1
2	SQL Driver Attributes for Atlassian Confluence API	2
3	Schema: Confluence	15
3.1	Tables	15
3.1.1	AnonymousUser: Atlassian Confluence Anonymous User	15
3.1.2	AuditLogs: Atlassian Confluence Audit Logs	16
3.1.3	AuditRetentionSettings: Atlassian Confluence Audit Retention Settings	18
3.1.4	BlueprintTemplates: Atlassian Confluence Blueprint Templates	18
3.1.5	ContentBlogsBySpaceKey: Atlassian Confluence Content Blogs by Space Key	19
3.1.6	ContentBlogsMetadataBySpaceKey	26
3.1.7	ContentPagesBySpaceKey: Atlassian Confluence Content Pages by Space Key	32
3.1.8	ContentPagesMetadataBySpaceKey	39
3.1.9	CurrentUser: Atlassian Confluence Current User	46
3.1.10	GroupMembersByGroupName: Atlassian Confluence Members by Group Name	55
3.1.11	Groups: Atlassian Confluence Groups	65
3.1.12	LongTasks: Atlassian Confluence Long Tasks	66
3.1.13	LookAndFeelSettings: Atlassian Confluence Look-and-feel Settings	66
3.1.14	SearchCql: Atlassian Confluence User by Account ID	70
3.1.15	SpaceByKey: Atlassian Confluence Space by Key	77
3.1.16	Spaces: Atlassian Confluence Spaces	86
3.1.17	SystemInformation: Atlassian Confluence System Information	95
3.1.18	UserByAccountId: Atlassian Confluence User by Account ID	96
4	Schema: Native	106
4.1	Tables	106
4.1.1	NATIVEPLATFORMSCALARREQUESTS: Atlassian Confluence Native Platform Scalar Requests	106
5	Schema: Views	108
5.1	Views	108
5.1.1	ContentBlogs	108
5.1.2	ContentBlogsMetadata	121
5.1.3	ContentPages	135
5.1.4	ContentPagesMetadata	149
5.1.5	GroupMembers	163
	Index	173

1 SQL Driver for Atlassian Confluence API

Invantive SQL is the fastest, easiest and most reliable way to exchange data with the Atlassian Confluence API.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the [user community](#). Other users or Invantive Support will try to help you to our best.

JIRA is cloud software for managing business processes and sharing knowledge. Confluence is online collaboration software for sharing knowledge.

The Atlassian Confluence driver covers 24 tables and 2556 columns.

Atlassian Confluence API Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigm). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

The [Atlassian Confluence Power BI connector](#) is based on the Invantive SQL driver for Atlassian Confluence, completed by a high-performance OData connector which works straight on Power BI without any add-on. The OData protocol is always version 4, independent whether the backing platform uses OData, SOAP or another protocol.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from the Atlassian Confluence API into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using [Invantive Data Replicator](#). Invantive Data Replicator automatically creates and maintains Atlassian Confluence datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an Atlassian Confluence ADO.net provider.

Finally, online web apps can be build for Atlassian Confluence using App Online of [Invantive Cloud](#).

Monitor API Calls

When a query or DML-statement has been executed on Invantive SQL a developer can evaluate the actual calls made to the Atlassian Confluence API using a query on sessionios@DataDictionary. As an alternative, extensive request and response logging can be enabled by setting log-native-calls-to-disk to true. In the %USERPROFILE%\Invantive\NativeLog folder Invantive SQL will create log files per API request and response.

Specifications

The SQL driver for Atlassian Confluence does not support partitioning. Define one data container in a database for each company in Atlassian Confluence to enable parallel access for data from multiple companies.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the [Invantive SQL grammar](#).

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the [driver attributes](#).

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On Atlassian Confluence the comparison of two texts is case sensitive by default.

Changes and bug fixes on the Atlassian Confluence SQL driver can be found in the [release notes](#). There is currently no specific section on the [Invantive forums](#) for Atlassian Confluence. Please reach out to other users of Atlassian Confluence by leaving a question or contact request.

Driver code for use in settings.xml: Confluence

Alias: confluence

Recommended alias: cf1

Status: Non-production

More technical documentation as provided by the supplier of the Atlassian Confluence API on the native API connection used can be found at <https://developer.atlassian.com/jiradev/jira-apis/jira-rest-apis>.

General documentation on Atlassian Confluence is available at <https://jira-apps.com>

Authentication can be done using one of the following two alternatives:
1. Using the user log on code, token and server name from the JIRA URL (basic authentication).
2. Using OAuth code grant flow. Authentication using user log on code and token is recommended for on-premise use. The basic authentication token can be defined on <https://id.atlassian.com/manage/api-tokens>. The OAuth code grant flow is recommended for online use; register a client at <https://developer.atlassian.com/apps>.

Updated: 15-06-2022 21:49 using Invantive SQL version 22.0.232-PROD+3445.

2 SQL Driver Attributes for Atlassian Confluence API

The SQL driver for Atlassian Confluence has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of Atlassian Confluence or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The Atlassian Confluence driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).

- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for Atlassian Confluence can be found in the `settings*.xml` file used for the database. `Settings*.xml` files are typically located in the `%USERPROFILE%\invantive` folder in most deployment scenarios. The reference manuals contain instructions how to relocate the `settings*.xml` files. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The Atlassian Confluence driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
add-odata-mandatory-filters	Whether to automatically add OData filters deemed necessary by the platform.	OData	False	✓	✓	✓	
analysis-enforce-row-uniqueness	Use for analysis only! Enforce rows to be unique.	Shared	False	✓	✓	✓	
api-access-token	Access Token is a security token for multiple OAuth2 Flows. With an Access Token you can access protected resources. An Access Token must be stored securely since once compromised allows access to your protected resources.	OData		✓		✓	✓
api-client-id	The client ID is a unique identifier of your application. It is generated by registering an application.	OData		✓		✓	✓
api-client-secret	The client secret is to be kept confidential. Such as a password for a logon code, the client secret is the confidential part of an app identified by a client ID. It is needed during the OAuth2 Code Grant Flow together with the refresh token to get access.	OData		✓		✓	✓
api-password-authentication	Use username/token basic authentication when true. OAuth otherwise.			✓		✓	
api-pre-expiry-refresh-sec	The number of seconds before the token expires to acquire a new	OData		✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from SQL-Statement	Set from Drivers File	Set from Log On
	token.						
api-redirect-url	The redirect URI is the website a browser session is redirected to after the OAuth2 authentication process has been completed.	OData		✓		✓	✓
api-refresh-token	Refresh Token is a security token for the OAuth2 Code Grant Flow . With a Refresh Token and client secret you can retrieve a renewed access token to access protected resources. A Refresh Token and client secret must be stored securely since once compromised allows access to your protected resources.	OData		✓		✓	✓
api-scope	The scope to request an OAuth token for.	OData		✓		✓	
api-token-url	The token URI is the OAuth2 endpoint to exchange tokens.	OData		✓		✓	
api-url	URL to access the API.	OData		✓		✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting	Shared	250	✓	✓	✓	
download-error-400-bad-request-max-tries	Maximum number of tries when OData server reports bad format during retrieval of data.		3	✓	✓	✓	
download-error-400-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		500	✓	✓	✓	
download-error-400-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		5000	✓	✓	✓	
download-error-400-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
download-error-408-request-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 408.		10	✓	✓	✓	
download-error-408-request-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 408.		10000	✓	✓	✓	
download-error-408-request-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 408.		300000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
dow nload-error-408-request-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 408.		2	✓	✓	✓	
dow nload-error-422-bad-request-max-tries	Maximum number of tries when OData server reports unprocessable entity during retrieval of data.		30	✓	✓	✓	
dow nload-error-422-bad-request-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		10000	✓	✓	✓	
dow nload-error-422-bad-request-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports unprocessable entity during retrieval of data.		300000	✓	✓	✓	
dow nload-error-422-bad-request-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports unprocessable entity during retrieval of data.		2	✓	✓	✓	
dow nload-error-429-too-many-requests-max-tries	Maximum number of tries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		10000	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		300000	✓	✓	✓	
dow nload-error-429-too-many-requests-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports that too many requests have been made during a timeslot of one minute or one day.		2	✓	✓	✓	
dow nload-error-502-server-unavailable-max-tries	Maximum number of tries when OData server reports a bad gateway during retrieval of data.		30	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports a bad gateway during retrieval of data.		10000	✓	✓	✓	
dow nload-error-502-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that a bad gateway during retrieval of data.		300000	✓	✓	✓	
dow nload-error-502-server-	Multiplication factor for sleep between retries OData server		2	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
unavailable-sleep-multiplicator	reports a bad gateway during retrieval of data.						
dow nload-error-503-server-unavailable-max-tries	Maximum number of tries when OData server reports that the API server is unavailable during retrieval of data.		30	✓	✓	✓	
dow nload-error-503-server-unavailable-sleep-initial-ms	Initial sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		10000	✓	✓	✓	
dow nload-error-503-server-unavailable-sleep-max-ms	Maximum sleep in milliseconds between retries when OData server reports that the API server is unavailable during retrieval of data.		300000	✓	✓	✓	
dow nload-error-503-server-unavailable-sleep-multiplicator	Multiplication factor for sleep between retries OData server reports that the API server is unavailable during retrieval of data.		2	✓	✓	✓	
dow nload-error-504-gateway-timeout-max-tries	Maximum number of tries when the website reports a gateway timeout.		10	✓	✓	✓	
dow nload-error-504-gateway-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a gateway timeout.		10000	✓	✓	✓	
dow nload-error-504-gateway-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a gateway timeout.		300000	✓	✓	✓	
dow nload-error-504-gateway-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a gateway timeout.		2	✓	✓	✓	
dow nload-error-590-network-connect-timeout-max-tries	Maximum number of tries when the website reports a HTTP status 590.		10	✓	✓	✓	
dow nload-error-590-network-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 590.		10000	✓	✓	✓	
dow nload-error-590-network-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 590.		300000	✓	✓	✓	
dow nload-error-590-network-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 590.		2	✓	✓	✓	
dow nload-error-599-network-connect-timeout	Maximum number of tries when the website reports a HTTP status 599.		10	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
connect-timeout-max-tries							
dow nload-error-599-netw ork-connect-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the website reports a HTTP status 599.		10000	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the website reports a HTTP status 599.		300000	✓	✓	✓	
dow nload-error-599-netw ork-connect-timeout-sleep-multiplicator	Multiplication factor for sleep between retries when the website reports a HTTP status 599.		2	✓	✓	✓	
dow nload-error-argument-exception-max-tries	Maximum number of tries when an argument exception is returned when downloading a blob.		10	✓	✓	✓	
dow nload-error-argument-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		10000	✓	✓	✓	
dow nload-error-argument-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an argument exception is returned when downloading a blob.		300000	✓	✓	✓	
dow nload-error-argument-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an argument exception is returned when downloading a blob.		2	✓	✓	✓	
dow nload-error-internet-dow n-max-tries	Maximum number of tries when the Internet connection seems down during retrieval of data.		10	✓	✓	✓	
dow nload-error-internet-dow n-sleep-initial-ms	Initial sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		10000	✓	✓	✓	
dow nload-error-internet-dow n-sleep-max-ms	Maximum sleep in milliseconds between retries when the Internet connection seems down during retrieval of data.		300000	✓	✓	✓	
dow nload-error-internet-dow n-sleep-multiplicator	Multiplication factor for sleep between retries when the Internet connection seems down during retrieval of data.		2	✓	✓	✓	
dow nload-error-io-exception-max-tries	Maximum number of tries when a network I/O connection failure occurs during retrieval of data.		10	✓	✓	✓	
dow nload-error-io-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		10000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from SQL-Statement	Set from Drivers File	Set from Log On
dow nload-error-io-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a network I/O connection failure occurs during retrieval of data.		300000	✓	✓	✓	
dow nload-error-io-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a network I/O connection failure occurs during retrieval of data.		2	✓	✓	✓	
dow nload-error-json-exception-max-tries	Maximum number of tries when an invalid JSON body is returned.		3	✓	✓	✓	
dow nload-error-json-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an invalid JSON body is returned.		1000	✓	✓	✓	
dow nload-error-json-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an invalid JSON body is returned.		10000	✓	✓	✓	
dow nload-error-json-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an invalid JSON body is returned.		2	✓	✓	✓	
dow nload-error-other-exception-max-tries	Maximum number of tries when an unqualified error occurs during retrieval of data.		3	✓	✓	✓	
dow nload-error-other-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when an unqualified error occurs during retrieval of data.		10000	✓	✓	✓	
dow nload-error-other-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when an unqualified error occurs during retrieval of data.		300000	✓	✓	✓	
dow nload-error-other-exception-sleep-multiplicator	Multiplication factor for sleep between retries when an unqualified error occurs during retrieval of data.		2	✓	✓	✓	
dow nload-error-socket-exception-max-tries	Maximum number of tries when the network connection is forcibly dropped during retrieval of data.		10	✓	✓	✓	
dow nload-error-socket-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when the network connection is forcibly dropped during retrieval of data.		10000	✓	✓	✓	
dow nload-error-socket-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when the network connection is forcibly dropped during retrieval of data.		300000	✓	✓	✓	
dow nload-error-socket-exception-sleep-multiplicator	Multiplication factor for sleep between retries when the network connection is forcibly dropped during retrieval of data.		2	✓	✓	✓	
dow nload-error-web-exception-max-tries	Maximum number of tries when a web connection failure occurs during retrieval of data.		10	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
dow nload-error-web-exception-sleep-initial-ms	Initial sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		10000	✓	✓	✓	
dow nload-error-web-exception-sleep-max-ms	Maximum sleep in milliseconds between retries when a web connection failure occurs during retrieval of data.		300000	✓	✓	✓	
dow nload-error-web-exception-sleep-multiplicator	Multiplication factor for sleep between retries when a web connection failure occurs during retrieval of data.		2	✓	✓	✓	
dow nload-error-web-not-implemented-max-tries	Maximum number of tries when the connection reports not implemented.		1	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports not implemented.		10000	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports not implemented.		300000	✓	✓	✓	
dow nload-error-web-not-implemented-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports not implemented.		2	✓	✓	✓	
dow nload-error-web-timeout-max-tries	Maximum number of tries when the connection reports a timeout.		10	✓	✓	✓	
dow nload-error-web-timeout-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports a timeout.		1000	✓	✓	✓	
dow nload-error-web-timeout-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports a timeout.		30000	✓	✓	✓	
dow nload-error-web-authorized-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports a timeout.		2	✓	✓	✓	
dow nload-error-web-unauthorized-max-tries	Maximum number of tries when the connection reports an unauthorized error.		1	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between retries when the connection reports an unauthorized error.		10000	✓	✓	✓	
dow nload-error-web-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between retries when the connection reports an unauthorized error.		300000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
dow nload-error-w eb-unauthorized-sleep-multiplicator	Multiplication factor for sleep between retries when the connection reports an unauthorized error.		2	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and Mixed.	Shared		✓	✓	✓	
http-disk-cache-compression-level	Compression level for the HTTP disk cache, ranging from 1 (little) to 9 (intense). Default is 5.	Shared	5	✓	✓	✓	
http-disk-cache-directory	Directory where HTTP cache is stored.	Shared	C:\Users\gle3.WS212\Invantive\Cache\http\gle3\shared	✓	✓	✓	
http-disk-cache-ignore-write-errors	Whether to ignore write errors to disk cache.	Shared	False	✓	✓	✓	
http-disk-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP disk cache.	Shared	2592000	✓	✓	✓	
http-get-timeout-max-ms	HTTP GET maximum timeout on retry (ms).		300000	✓	✓	✓	
http-get-timeout-ms	HTTP GET timeout (ms).		60000	✓	✓	✓	
http-memory-cache-compression-level	Compression level for the HTTP memory cache, ranging from 1 (little) to 9 (intense). Default is 5.	OData	5	✓	✓	✓	
http-memory-cache-max-age-sec	Maximum acceptable age in seconds for use of data in the HTTP memory cache.	OData	14400	✓	✓	✓	
http-post-timeout-max-ms	HTTP POST maximum timeout on retry (ms).		300000	✓	✓	✓	
http-post-timeout-ms	HTTP POST timeout (ms).		300000	✓	✓	✓	
ignore-http-400-errors	Ignore HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-401-errors	Ignore HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-402-errors	Ignore HTTP 402 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-403-errors	Ignore HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-404-errors	Ignore HTTP 404 errors when exchanging results with the OData		False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	endpoint.						
ignore-http-422-errors	Ignore HTTP 422 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-429-errors	Ignore HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-500-errors	Ignore HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-502-errors	Ignore HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
ignore-http-503-errors	Ignore HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
invalid-json-on-get-max-tries	Maximum number of tries when the JSON received on GET is invalid.		10	✓	✓	✓	
invalid-json-on-get-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on GET is invalid.		10000	✓	✓	✓	
invalid-json-on-get-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on GET is invalid.		300000	✓	✓	✓	
invalid-json-on-get-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on GET is invalid.		2	✓	✓	✓	
invalid-json-on-post-max-tries	Maximum number of tries when the JSON received on POST is invalid.		1	✓	✓	✓	
invalid-json-on-post-sleep-initial-ms	Initial sleep in milliseconds between retries when the JSON received on POST is invalid.		10000	✓	✓	✓	
invalid-json-on-post-sleep-max-ms	Maximum sleep in milliseconds between retries when the JSON received on POST is invalid.		300000	✓	✓	✓	
invalid-json-on-post-sleep-multiplicator	Multiplication factor for sleep between retries when the JSON received on POST is invalid.		2	✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
join-set-points-per-request	Maximum number of values in a request when executing a join set.	OData	60	✓	✓	✓	
limit-partition-calls-left	Minimum number of remaining API calls on a partition towards a hard limit. When below , an error is raised.	OData	500	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files when an error occurred.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files when successful.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
max-odata-filters	The maximum number of OData filter elements.	OData	100	✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
metadata-cache-max-age-sec	Maximum acceptable age in seconds for re-use of metadata.	OData		✓	✓	✓	
oauth-unauthorized-max-tries	Maximum number of tries when an OAuth exception occurs.	OData	2	✓	✓	✓	
oauth-unauthorized-sleep-initial-ms	Initial sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	10000	✓	✓	✓	
oauth-unauthorized-sleep-max-ms	Maximum sleep in milliseconds between OAuth reauthentication tries when the OAuth authentication fails.	OData	1000	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
oauth-unauthorized-sleep-multiplicator	Multiplication factor for sleep between OAuth reauthentication tries when the OAuth authentication fails.	OData	2	✓	✓	✓	
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
server	Server name (basic authentication only).			✓		✓	✓
simulate-http-400-errors	Simulate HTTP 400 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-400-errors-percentage	Percentage of simulated HTTP 400 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-401-errors	Simulate HTTP 401 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-401-errors-percentage	Percentage of simulated HTTP 401 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-403-errors	Simulate HTTP 403 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-403-errors-percentage	Percentage of simulated HTTP 403 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-408-errors	Simulate HTTP 408 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-408-errors-percentage	Percentage of simulated HTTP 408 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-429-errors	Simulate HTTP 429 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-429-errors-percentage	Percentage of simulated HTTP 429 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from SQL-Statement	Set from Drivers File	Set from Log On
simulate-http-500-errors	Simulate HTTP 500 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-500-errors-percentage	Percentage of simulated HTTP 500 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-502-errors	Simulate HTTP 502 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-502-errors-percentage	Percentage of simulated HTTP 502 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-503-errors	Simulate HTTP 503 errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-503-errors-percentage	Percentage of simulated HTTP 503 errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-protocol-errors	Simulate HTTP protocol errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-protocol-errors-percentage	Percentage of simulated HTTP protocol errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
simulate-http-timeout-errors	Simulate HTTP timeout errors when exchanging results with the OData endpoint.		False	✓	✓	✓	
simulate-http-timeout-errors-percentage	Percentage of simulated HTTP timeout errors when exchanging results with the OData endpoint.		0	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
use-batch-insert	Whether to use batch insert.	OData	True	✓	✓	✓	
use-http-disk-cache-read	Whether to use HTTP responses from previous queries stored on disk to answer the current query.	Shared	False	✓	✓	✓	
use-http-disk-cache-write	Whether to memorize HTTP responses on disk.	Shared	False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
use-http-memory-cache-read	Whether to use HTTP responses from previous queries stored in memory that can answer the current query.	OData	True	✓	✓	✓	
use-http-memory-cache-write	Whether to memorize HTTP responses from previous queries for use by future queries.	OData	True	✓	✓	✓	

3 Schema: Confluence

3.1 Tables

3.1.1 AnonymousUser: Atlassian Confluence Anonymous User

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Anonymous User

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: `/user/anonymous`

Insert Atlassian Confluence API URL: `/user/anonymous`

Update Atlassian Confluence API URL: `/user/anonymous`

Delete Atlassian Confluence API URL: `/user/anonymous`

Field Selection Method: NotRequired

Table Function Columns

The columns of the table function `AnonymousUser` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
displayName	string		<input type="checkbox"/>	
profilePicture_height	int32		<input type="checkbox"/>	
profilePicture_isDefault	boolean		<input type="checkbox"/>	
profilePicture_path	string		<input type="checkbox"/>	
profilePicture_width	int32		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	

3.1.2 AuditLogs: Atlassian Confluence Audit Logs

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Audit Logs

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /audit

Insert Atlassian Confluence API URL: /audit

Update Atlassian Confluence API URL: /audit

Delete Atlassian Confluence API URL: /audit

Field Selection Method: NotRequired

Base Path: results [*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function AuditLogs. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
endDate	int64	<input type="checkbox"/>		End time as UNIX timestamp.
searchString	string	<input type="checkbox"/>		Filters the results to records that have string property values matching the searchString.
startDate	int64	<input type="checkbox"/>		Start time as UNIX timestamp.

Table Function Columns

The columns of the table function AuditLogs are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
associatedObjects	string		<input type="checkbox"/>	Associated objects.
author_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
author_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
author_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
author_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
author_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
author_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
author_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
author_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
author_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
category	string		<input type="checkbox"/>	Category.
changedValues	string		<input type="checkbox"/>	Changed values.
creationDate	datetime		<input type="checkbox"/>	Creation date.
description	string		<input type="checkbox"/>	Description.
remoteAddress	string		<input type="checkbox"/>	Remote address.
source_name	string		<input type="checkbox"/>	Name.
source_objectType	string		<input type="checkbox"/>	Object type.

Name	Data Type	Label	Required	Documentation
summary	string		<input type="checkbox"/>	Summary.
sysAdmin	boolean		<input type="checkbox"/>	Whether user was system administrator.

3.1.3 AuditRetentionSettings: Atlassian Confluence Audit Retention Settings

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Audit Retention Settings

This is a read-only table. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /audit/retention

Insert Atlassian Confluence API URL: /audit/retention

Update Atlassian Confluence API URL: /audit/retention

Delete Atlassian Confluence API URL: /audit/retention

Field Selection Method: NotRequired

Table Columns

The columns of the table AuditRetentionSettings are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
number	int32		<input type="checkbox"/>	The number of units for the retention period.
units	string		<input type="checkbox"/>	The unit of time that the retention period is measured in. Valid values: NANOS, MICROS, MILLIS, SECONDS, MINUTES, HOURS, HALF_DAYS, DAYS, WEEKS, MONTHS, YEARS, DECADES, CENTURIES, MILLENNIA, ERAS, FOREVER.

3.1.4 BlueprintTemplates: Atlassian Confluence Blueprint Templates

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Blueprint Templates

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: `/template/blueprint?expand=body`

Insert Atlassian Confluence API URL: `/template/blueprint?expand=body`

Update Atlassian Confluence API URL: `/template/blueprint?expand=body`

Delete Atlassian Confluence API URL: `/template/blueprint?expand=body`

Field Selection Method: `NotRequired`

Base Path: `results [*]`

Table Function Columns

The columns of the table function `BlueprintTemplates` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_body_contexts	string		<input type="checkbox"/>	
body_body_keys	string		<input type="checkbox"/>	
body_body_superbatch	string		<input type="checkbox"/>	
body_body_tags	string		<input type="checkbox"/>	
body_body_uris	string		<input type="checkbox"/>	
body_representation	string		<input type="checkbox"/>	Valid values: <code>view</code> , <code>export_view</code> , <code>styled_view</code> , <code>storage</code> , <code>editor2</code> , <code>anonymous_export_view</code> .
body_value	string		<input type="checkbox"/>	
description	string		<input type="checkbox"/>	
name	string		<input type="checkbox"/>	
referencingBlueprint	string		<input type="checkbox"/>	
templateId	string		<input type="checkbox"/>	
templateType	string		<input type="checkbox"/>	

3.1.5 ContentBlogsBySpaceKey: Atlassian Confluence Content Blogs by Space Key

Catalog: JIRA

Schema: Confluence

Primary Keys: `id`

Label: Content Blogs by Space Key

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=body.export_view,version

Insert Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=body.export_view,version

Update Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=body.export_view,version

Delete Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=body.export_view,version

Field Selection Method: NotRequired

Base Path: results [*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContentBlogsBySpaceKey. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
depth	string	<input type="checkbox"/>		Filter the results to content at the root level of the space or all content. Default: all. Valid values: all, root.
spaceKey	string	<input type="checkbox"/>		The key of the space to be returned.

Table Function Columns

The columns of the table function ContentBlogsBySpaceKey are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

3.1.6 ContentBlogsMetadataBySpaceKey

Catalog: JIRA

Schema: Confluence

Primary Keys: id

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=version

Insert Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=version

Update Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=version

Delete Atlassian Confluence API URL: /space/{spaceKey}/content/blog?
expand=version

Field Selection Method: NotRequired

Base Path: results[*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContentBlogsMetadataBySpaceKey. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four

parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
depth	string	<input type="checkbox"/>		Filter the results to content at the root level of the space or all content. Default: all. Valid values: all, root.
spaceKey	string	<input type="checkbox"/>		The key of the space to be returned.

Table Function Columns

The columns of the table function `ContentBlogsMetadataBySpaceKey` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is

Name	Data Type	Label	Required	Documentation
				missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account,

Name	Data Type	Label	Required	Documentation
				app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian

Name	Data Type	Label	Required	Documentation
				regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account,

Name	Data Type	Label	Required	Documentation
				app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is

Name	Data Type	Label	Required	Documentation
				missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

3.1.7 ContentPagesBySpaceKey: Atlassian Confluence Content Pages by Space Key

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Content Pages by Space Key

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=body.export_view,version

Insert Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=body.export_view,version

Update Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=body.export_view,version

Delete Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=body.export_view,version

Field Selection Method: NotRequired

Base Path: results[*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContentPagesBySpaceKey. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
depth	string	<input type="checkbox"/>		Filter the results to content at the root level of the space or all content. Default: all. Valid values: all, root.
spaceKey	string	<input type="checkbox"/>		The key of the space to be returned.

Table Function Columns

The columns of the table function ContentPagesBySpaceKey are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdByAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdByActive	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdByDisplayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdByEmail	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

3.1.8 ContentPagesMetadataBySpaceKey

Catalog: JIRA

Schema: Confluence

Primary Keys: id

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=version

Insert Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=version

Update Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=version

Delete Atlassian Confluence API URL: /space/{spaceKey}/content/page?
expand=version

Field Selection Method: NotRequired

Base Path: results[*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function ContentPagesMetadataBySpaceKey. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
depth	string	<input type="checkbox"/>		Filter the results to content at the root level of the space or all content. Default: all. Valid values: all, root.
spaceKey	string	<input type="checkbox"/>		The key of the space to be returned.

Table Function Columns

The columns of the table function ContentPagesMetadataBySpaceKey are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_contributors	string		<input type="checkbox"/>	
history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is

Name	Data Type	Label	Required	Documentation
				missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown

Name	Data Type	Label	Required	Documentation
				is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is

Name	Data Type	Label	Required	Documentation
				missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

3.1.9 CurrentUser: Atlassian Confluence Current User

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Current User

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /user/current?expand=personalSpace

Insert Atlassian Confluence API URL: /user/current?expand=personalSpace

Update Atlassian Confluence API URL: /user/current?expand=personalSpace

Delete Atlassian Confluence API URL: /user/current?expand=personalSpace

Field Selection Method: NotRequired

Table Function Columns

The columns of the table function CurrentUser are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may be the same as publicName.
email	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
personalSpace_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_history_contributors	string		<input type="checkbox"/>	
personalSpace_homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian

Name	Data Type	Label	Required	Documentation
				regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdDate	datetime		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_latest	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is

Name	Data Type	Label	Required	Documentation
				missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_previousVersion_by_emailAddresses	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_id	int64		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_key	string		<input type="checkbox"/>	
personalSpace_homepage_status	string		<input type="checkbox"/>	
personalSpace_homepage_title	string		<input type="checkbox"/>	
personalSpace_homepage_type	string		<input type="checkbox"/>	
personalSpace_homepage_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_version_friendlyWhen	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_version_links	string		<input type="checkbox"/>	
personalSpace_homepage_version_message	string		<input type="checkbox"/>	
personalSpace_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_version_number	int32		<input type="checkbox"/>	
personalSpace_homepage_version_when	string		<input type="checkbox"/>	
personalSpace_icon_height	int32		<input type="checkbox"/>	
personalSpace_icon_isDefault	boolean		<input type="checkbox"/>	
personalSpace_icon_path	string		<input type="checkbox"/>	
personalSpace_icon_width	int32		<input type="checkbox"/>	
personalSpace_id	int64		<input type="checkbox"/>	ID.
personalSpace_key	string		<input type="checkbox"/>	Key.
personalSpace_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_headings	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_links	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_name	string		<input type="checkbox"/>	Name.

Name	Data Type	Label	Required	Documentation
personalSpace_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
personalSpace_status	string		<input type="checkbox"/>	Status.
personalSpace_type	string		<input type="checkbox"/>	Type.
profilePicture_height	int32		<input type="checkbox"/>	
profilePicture_isDefault	boolean		<input type="checkbox"/>	
profilePicture_path	string		<input type="checkbox"/>	
profilePicture_width	int32		<input type="checkbox"/>	
publicName	string		<input type="checkbox"/>	The public name or nickname of the user. Will always contain a value.
type	string		<input type="checkbox"/>	Valid values: known, unknown, anonymous, user.

3.1.10 GroupMembersByGroupName: Atlassian Confluence Members by Group Name

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Members by Group Name

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /group/{groupName}/member

Insert Atlassian Confluence API URL: /group/{groupName}/member

Update Atlassian Confluence API URL: /group/{groupName}/member

Delete Atlassian Confluence API URL: /group/{groupName}/member

Field Selection Method: NotRequired

Base Path: results[*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function GroupMembersByGroupName. A value must be provided at all times for required

parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
groupName	string	<input checked="" type="checkbox"/>		The name of the group to be queried for its members.

Table Function Columns

The columns of the table function `GroupMembersByGroupName` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may be the same as <code>publicName</code> .
email	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_body_anonymous_export_view_represe	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
ntation				
personalSpace_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_history_contributors	string		<input type="checkbox"/>	
personalSpace_homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems,

Name	Data Type	Label	Required	Documentation
				customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdDate	datetime		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may return an alternative value.
personalSpace_homepage_history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_latest	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth

Name	Data Type	Label	Required	Documentation
				to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you

Name	Data Type	Label	Required	Documentation
				need to access more information about the user.
personalSpace_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_previousVersion_by_emailAddresses	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_id	int64		<input type="checkbox"/>	
personalSpace_homepage_key	string		<input type="checkbox"/>	
personalSpace_homepage_status	string		<input type="checkbox"/>	
personalSpace_homepage_title	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_type	string		<input type="checkbox"/>	
personalSpace_homepage_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_version_links	string		<input type="checkbox"/>	
personalSpace_homepage_version_message	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_version_number	int32		<input type="checkbox"/>	
personalSpace_homepage_version_when	string		<input type="checkbox"/>	
personalSpace_icon_height	int32		<input type="checkbox"/>	
personalSpace_icon_isDefault	boolean		<input type="checkbox"/>	
personalSpace_icon_path	string		<input type="checkbox"/>	
personalSpace_icon_width	int32		<input type="checkbox"/>	
personalSpace_id	int64		<input type="checkbox"/>	ID.
personalSpace_key	string		<input type="checkbox"/>	Key.
personalSpace_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_headings	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_links	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_focus	string		<input type="checkbox"/>	
personalSpace_name	string		<input type="checkbox"/>	Name.
personalSpace_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property

Name	Data Type	Label	Required	Documentation
				is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
personalSpace_status	string		<input type="checkbox"/>	Status.
personalSpace_type	string		<input type="checkbox"/>	Type.
profilePicture_height	int32		<input type="checkbox"/>	
profilePicture_isDefault	boolean		<input type="checkbox"/>	
profilePicture_path	string		<input type="checkbox"/>	
profilePicture_width	int32		<input type="checkbox"/>	
publicName	string		<input type="checkbox"/>	The public name or nickname of the user. Will always contain a value.
type	string		<input type="checkbox"/>	Valid values: known, unknown, anonymous, user.

3.1.11 Groups: Atlassian Confluence Groups

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Groups

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /group

Insert Atlassian Confluence API URL: /group

Update Atlassian Confluence API URL: /group

Delete Atlassian Confluence API URL: /group

Field Selection Method: NotRequired

Base Path: results [*]

Table Function Columns

The columns of the table function Groups are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
name	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
type	string		<input type="checkbox"/>	

3.1.12 LongTasks: Atlassian Confluence Long Tasks

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Long Tasks

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: `/longtask`

Insert Atlassian Confluence API URL: `/longtask`

Update Atlassian Confluence API URL: `/longtask`

Delete Atlassian Confluence API URL: `/longtask`

Field Selection Method: NotRequired

Base Path: `results [*]`

Table Function Columns

The columns of the table function `LongTasks` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
elapsedTime	int64		<input type="checkbox"/>	
id	string		<input type="checkbox"/>	
messages_args	string		<input type="checkbox"/>	
messages_key	string		<input type="checkbox"/>	
name_args	string		<input type="checkbox"/>	
name_key	string		<input type="checkbox"/>	
percentageComplete	int32		<input type="checkbox"/>	
successful	boolean		<input type="checkbox"/>	

3.1.13 LookAndFeelSettings: Atlassian Confluence Look-and-feel Settings

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Look-and-feel Settings

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: `/settings/lookandfeel`

Insert Atlassian Confluence API URL: `/settings/lookandfeel`

Update Atlassian Confluence API URL: `/settings/lookandfeel`

Delete Atlassian Confluence API URL: `/settings/lookandfeel`

Field Selection Method: NotRequired

Table Function Columns

The columns of the table function `LookAndFeelSettings` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
custom_bordersAndDividers	string		<input type="checkbox"/>	
custom_content_body_background	string		<input type="checkbox"/>	
custom_content_body_backgroundColor	string		<input type="checkbox"/>	
custom_content_body_backgroundImage	string		<input type="checkbox"/>	
custom_content_body_backgroundSize	string		<input type="checkbox"/>	
custom_content_body_borderRadius	string		<input type="checkbox"/>	
custom_content_body_padding	string		<input type="checkbox"/>	
custom_content_container_background	string		<input type="checkbox"/>	
custom_content_container_backgroundColor	string		<input type="checkbox"/>	
custom_content_container_backgroundImage	string		<input type="checkbox"/>	
custom_content_container_backgroundSize	string		<input type="checkbox"/>	
custom_content_container_borderRadius	string		<input type="checkbox"/>	
custom_content_container_padding	string		<input type="checkbox"/>	
custom_content_header_background	string		<input type="checkbox"/>	
custom_content_header_backgroundColor	string		<input type="checkbox"/>	
custom_content_header_backgroundImage	string		<input type="checkbox"/>	
custom_content_header_backgroundSize	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
custom_content_header_borderRadius	string		<input type="checkbox"/>	
custom_content_header_padding	string		<input type="checkbox"/>	
custom_content_screen_background	string		<input type="checkbox"/>	
custom_content_screen_backgroundColor	string		<input type="checkbox"/>	
custom_content_screen_backgroundImage	string		<input type="checkbox"/>	
custom_content_screen_backgroundSize	string		<input type="checkbox"/>	
custom_content_screen_gutterBottom	string		<input type="checkbox"/>	
custom_content_screen_gutterLeft	string		<input type="checkbox"/>	
custom_content_screen_gutterRight	string		<input type="checkbox"/>	
custom_content_screen_gutterTop	string		<input type="checkbox"/>	
custom_header_backgroundColor	string		<input type="checkbox"/>	
custom_header_button_backgroundColor	string		<input type="checkbox"/>	
custom_header_button_color	string		<input type="checkbox"/>	
custom_header_primaryNavigation_color	string		<input type="checkbox"/>	
custom_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
custom_header_search_backgroundColor	string		<input type="checkbox"/>	
custom_header_search_color	string		<input type="checkbox"/>	
custom_header_secondaryNavigation_color	string		<input type="checkbox"/>	
custom_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
custom_headings	string		<input type="checkbox"/>	
custom_links	string		<input type="checkbox"/>	
custom_menus_color	string		<input type="checkbox"/>	
custom_menus_hoverOrFocus	string		<input type="checkbox"/>	
global_bordersAndDividers	string		<input type="checkbox"/>	
global_content_body_background	string		<input type="checkbox"/>	
global_content_body_backgroundColor	string		<input type="checkbox"/>	
global_content_body_backgroundImage	string		<input type="checkbox"/>	
global_content_body_backgroundSize	string		<input type="checkbox"/>	
global_content_body_borderRadius	string		<input type="checkbox"/>	
global_content_body_padding	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
global_content_container_background	string		<input type="checkbox"/>	
global_content_container_backgroundColor	string		<input type="checkbox"/>	
global_content_container_backgroundImage	string		<input type="checkbox"/>	
global_content_container_backgroundSize	string		<input type="checkbox"/>	
global_content_container_borderRadius	string		<input type="checkbox"/>	
global_content_container_padding	string		<input type="checkbox"/>	
global_content_header_background	string		<input type="checkbox"/>	
global_content_header_backgroundColor	string		<input type="checkbox"/>	
global_content_header_backgroundImage	string		<input type="checkbox"/>	
global_content_header_backgroundSize	string		<input type="checkbox"/>	
global_content_header_borderRadius	string		<input type="checkbox"/>	
global_content_header_padding	string		<input type="checkbox"/>	
global_content_screen_background	string		<input type="checkbox"/>	
global_content_screen_backgroundColor	string		<input type="checkbox"/>	
global_content_screen_backgroundImage	string		<input type="checkbox"/>	
global_content_screen_backgroundSize	string		<input type="checkbox"/>	
global_content_screen_gutterBottom	string		<input type="checkbox"/>	
global_content_screen_gutterLeft	string		<input type="checkbox"/>	
global_content_screen_gutterRight	string		<input type="checkbox"/>	
global_content_screen_gutterTop	string		<input type="checkbox"/>	
global_header_backgroundColor	string		<input type="checkbox"/>	
global_header_button_backgroundColor	string		<input type="checkbox"/>	
global_header_button_color	string		<input type="checkbox"/>	
global_header_primaryNavigation_color	string		<input type="checkbox"/>	
global_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
global_header_search_backgroundColor	string		<input type="checkbox"/>	
global_header_search_color	string		<input type="checkbox"/>	
global_header_secondaryNavigation_color	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
global_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
global_headings	string		<input type="checkbox"/>	
global_links	string		<input type="checkbox"/>	
global_menus_color	string		<input type="checkbox"/>	
global_menus_hoverOrFocus	string		<input type="checkbox"/>	

3.1.14 SearchCql: Atlassian Confluence User by Account ID

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: User by Account ID

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /search?expand=personalSpace

Insert Atlassian Confluence API URL: /search?expand=personalSpace

Update Atlassian Confluence API URL: /search?expand=personalSpace

Delete Atlassian Confluence API URL: /search?expand=personalSpace

Field Selection Method: NotRequired

Base Path: results [*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SearchCql. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
cql	string	<input checked="" type="checkbox"/>		The CQL query to be used for the search.

Name	Data Type	Required	Default Value	Documentation
cqlcontext	string	<input type="checkbox"/>		The space, content, and content status to execute the search against.spaceKey: Key of the space to search against.Optional.contentId: ID of the content to search against.Optional.Must be in the space specified by spaceKey.contentStatuses: Content statuses to search against.Optional.
includeArchivedSpaces	boolean	<input type="checkbox"/>		Include content from archived spaces in the results. Default: false.

Table Function Columns

The columns of the table function `SearchCql` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
content_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
content_body_anonymous_export_value	string		<input type="checkbox"/>	
content_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
content_body_atlas_doc_format_value	string		<input type="checkbox"/>	
content_body_editor_representation	string		<input type="checkbox"/>	
content_body_editor_value	string		<input type="checkbox"/>	
content_body_editor2_representation	string		<input type="checkbox"/>	
content_body_editor2_value	string		<input type="checkbox"/>	
content_body_export_view_representation	string		<input type="checkbox"/>	
content_body_export_view_value	string		<input type="checkbox"/>	
content_body_storage_representation	string		<input type="checkbox"/>	
content_body_storage_value	string		<input type="checkbox"/>	
content_body_styled_view_representation	string		<input type="checkbox"/>	
content_body_styled_view_value	string		<input type="checkbox"/>	
content_body_view_representation	string		<input type="checkbox"/>	
content_body_view_value	string		<input type="checkbox"/>	
content_history_contributors	string		<input type="checkbox"/>	
content_history_createdBy_account	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the

Name	Data Type	Label	Required	Documentation
				user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
content_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
content_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
content_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
content_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
content_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
content_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
content_history_createdDate	datetime		<input type="checkbox"/>	
content_history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you

Name	Data Type	Label	Required	Documentation
				need to access more information about the user.
content_history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
content_history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
content_history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
content_history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
content_history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
content_history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
content_history_lastUpdated_collaborators	string		<input type="checkbox"/>	
content_history_lastUpdated_friendWhen	string		<input type="checkbox"/>	
content_history_lastUpdated_links	string		<input type="checkbox"/>	
content_history_lastUpdated_message	string		<input type="checkbox"/>	
content_history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
content_history_lastUpdated_number	int32		<input type="checkbox"/>	
content_history_lastUpdated_when	string		<input type="checkbox"/>	
content_history_latest	boolean		<input type="checkbox"/>	
content_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5.

Name	Data Type	Label	Required	Documentation
				Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
content_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
content_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
content_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
content_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
content_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
content_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
content_history_nextVersion_collaborators	string		<input type="checkbox"/>	
content_history_nextVersion_friendWhen	string		<input type="checkbox"/>	
content_history_nextVersion_links	string		<input type="checkbox"/>	
content_history_nextVersion_message	string		<input type="checkbox"/>	
content_history_nextVersion_minEdit	boolean		<input type="checkbox"/>	
content_history_nextVersion_number	int32		<input type="checkbox"/>	
content_history_nextVersion_when	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
content_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
content_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
content_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
content_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
content_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
content_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
content_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
content_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
content_history_previousVersion_collaborators	string		<input type="checkbox"/>	
content_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
content_history_previousVersion_links	string		<input type="checkbox"/>	
content_history_previousVersion_message	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
content_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
content_history_previousVersion_number	int32		<input type="checkbox"/>	
content_history_previousVersion_when	string		<input type="checkbox"/>	
content_id	int64		<input type="checkbox"/>	
content_key	string		<input type="checkbox"/>	
content_status	string		<input type="checkbox"/>	
content_title	string		<input type="checkbox"/>	
content_type	string		<input type="checkbox"/>	
content_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
content_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
content_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
content_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
content_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
content_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
content_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
content_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.

Name	Data Type	Label	Required	Documentation
content_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
content_version_collaborators	string		<input type="checkbox"/>	
content_version_friendlyWhen	string		<input type="checkbox"/>	
content_version_links	string		<input type="checkbox"/>	
content_version_message	string		<input type="checkbox"/>	
content_version_minorEdit	boolean		<input type="checkbox"/>	
content_version_number	int32		<input type="checkbox"/>	
content_version_when	string		<input type="checkbox"/>	
entityType	string		<input type="checkbox"/>	
excerpt	string		<input type="checkbox"/>	
friendlyLastModified	string		<input type="checkbox"/>	
iconCssClass	string		<input type="checkbox"/>	
lastModified	string		<input type="checkbox"/>	
resultGlobalContainer_displayUrl	string		<input type="checkbox"/>	
resultGlobalContainer_title	string		<input type="checkbox"/>	
resultParentContainer_displayUrl	string		<input type="checkbox"/>	
resultParentContainer_title	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
url	string		<input type="checkbox"/>	

3.1.15 SpaceByKey: Atlassian Confluence Space by Key

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Space by Key

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /space/{spaceKey}?
 expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage

Insert Atlassian Confluence API URL: /space/{spaceKey}?
 expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage

Update Atlassian Confluence API URL: /space/{spaceKey}?
 expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage

Delete Atlassian Confluence API URL: /space/{spaceKey}?expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage

Field Selection Method: NotRequired

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function SpaceByKey. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
spaceKey	string	<input type="checkbox"/>		The key of the space to be returned.

Table Function Columns

The columns of the table function SpaceByKey are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
homepage_body_editor_representation	string		<input type="checkbox"/>	
homepage_body_editor_value	string		<input type="checkbox"/>	
homepage_body_editor2_representation	string		<input type="checkbox"/>	
homepage_body_editor2_value	string		<input type="checkbox"/>	
homepage_body_export_view_representation	string		<input type="checkbox"/>	
homepage_body_export_view_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
homepage_body_storage_representation	string		<input type="checkbox"/>	
homepage_body_storage_value	string		<input type="checkbox"/>	
homepage_body_styled_view_representation	string		<input type="checkbox"/>	
homepage_body_styled_view_value	string		<input type="checkbox"/>	
homepage_body_view_representation	string		<input type="checkbox"/>	
homepage_body_view_value	string		<input type="checkbox"/>	
homepage_history_contributors	string		<input type="checkbox"/>	
homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.

Name	Data Type	Label	Required	Documentation
homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_createdDate	datetime		<input type="checkbox"/>	
homepage_history_lastUpdated_byAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_lastUpdated_byAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_lastUpdated_byActive	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_lastUpdated_byDisplayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_history_lastUpdated_byEmailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_lastUpdated_byKey	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_history_lastUpdated_byLocale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_lastUpdated_byName	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_lastUpdated_byTimeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_lastUpdated_byCollaborators	string		<input type="checkbox"/>	
homepage_history_lastUpdated_friendWhen	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
homepage_history_lastUpdated_linx	string		<input type="checkbox"/>	
homepage_history_lastUpdated_message	string		<input type="checkbox"/>	
homepage_history_lastUpdated_menorEdit	boolean		<input type="checkbox"/>	
homepage_history_lastUpdated_number	int32		<input type="checkbox"/>	
homepage_history_lastUpdated_when	string		<input type="checkbox"/>	
homepage_history_latest	boolean		<input type="checkbox"/>	
homepage_history_nextVersion_b_y_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_nextVersion_b_y_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_nextVersion_b_y_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_nextVersion_b_y_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_history_nextVersion_b_y_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_nextVersion_b_y_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_history_nextVersion_b_y_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_nextVersion_b_y_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_nextVersion_b_y_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the

Name	Data Type	Label	Required	Documentation
				user's privacy setting, this may be returned as null.
homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
homepage_history_nextVersion_friendWhen	string		<input type="checkbox"/>	
homepage_history_nextVersion_links	string		<input type="checkbox"/>	
homepage_history_nextVersion_message	string		<input type="checkbox"/>	
homepage_history_nextVersion_moderEdit	boolean		<input type="checkbox"/>	
homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
homepage_history_nextVersion_when	string		<input type="checkbox"/>	
homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
homepage_history_previousVersion_links	string		<input type="checkbox"/>	
homepage_history_previousVersion_message	string		<input type="checkbox"/>	
homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
homepage_history_previousVersion_when	string		<input type="checkbox"/>	
homepage_id	int64		<input type="checkbox"/>	
homepage_key	string		<input type="checkbox"/>	
homepage_status	string		<input type="checkbox"/>	
homepage_title	string		<input type="checkbox"/>	
homepage_type	string		<input type="checkbox"/>	
homepage_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b2cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may return an alternative value.
homepage_version_by_emailAddresses	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_version_collaborators	string		<input type="checkbox"/>	
homepage_version_friendlyWhen	string		<input type="checkbox"/>	
homepage_version_links	string		<input type="checkbox"/>	
homepage_version_message	string		<input type="checkbox"/>	
homepage_version_minorEdit	boolean		<input type="checkbox"/>	
homepage_version_number	int32		<input type="checkbox"/>	
homepage_version_when	string		<input type="checkbox"/>	
icon_height	int32		<input type="checkbox"/>	
icon_isDefault	boolean		<input type="checkbox"/>	
icon_path	string		<input type="checkbox"/>	
icon_width	int32		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	ID.
key	string		<input type="checkbox"/>	Key.
lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
lookAndFeel_content_body_background	string		<input type="checkbox"/>	
lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
lookAndFeel_content_container_background	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
lookAndFeel_content_header_background	string		<input type="checkbox"/>	
lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_header_button_color	string		<input type="checkbox"/>	
lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
lookAndFeel_header_search_color	string		<input type="checkbox"/>	
lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
lookAndFeel_headings	string		<input type="checkbox"/>	
lookAndFeel_links	string		<input type="checkbox"/>	
lookAndFeel_menus_color	string		<input type="checkbox"/>	
lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
name	string		<input type="checkbox"/>	Name.
settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
status	string		<input type="checkbox"/>	Status.
type	string		<input type="checkbox"/>	Type.

3.1.16 Spaces: Atlassian Confluence Spaces

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: Spaces

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: /space?

```
expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage
```

Insert Atlassian Confluence API URL: /space?

```
expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage
```

Update Atlassian Confluence API URL: /space?

```
expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage
```

Delete Atlassian Confluence API URL: /space?

expand=settings,lookAndFeel,icon,description.plain,description.view,theme,homepage

Field Selection Method: NotRequired

Base Path: results [*]

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function Spaces. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
favourite	boolean	<input type="checkbox"/>		Filter the results to the favourite spaces of the user specified by favouriteUserKey. Note, 'favourite' spaces are also known as 'saved for later' spaces.
favouriteUserKey	string	<input type="checkbox"/>		The userKey of the user, whose favourite spaces are used to filter the results when using the favourite parameter.
status	string	<input type="checkbox"/>		Filter the results to spaces based on their status. Valid values: current, archived.
type	string	<input type="checkbox"/>		Filter the results to spaces based on their type. Valid values: global, personal.

Table Function Columns

The columns of the table function Spaces are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
homepage_body_anonymous_exp ort_view_representation	string		<input type="checkbox"/>	
homepage_body_anonymous_exp ort_view_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
homepage_body_editor_representation	string		<input type="checkbox"/>	
homepage_body_editor_value	string		<input type="checkbox"/>	
homepage_body_editor2_representation	string		<input type="checkbox"/>	
homepage_body_editor2_value	string		<input type="checkbox"/>	
homepage_body_export_view_representation	string		<input type="checkbox"/>	
homepage_body_export_view_value	string		<input type="checkbox"/>	
homepage_body_storage_representation	string		<input type="checkbox"/>	
homepage_body_storage_value	string		<input type="checkbox"/>	
homepage_body_styled_view_representation	string		<input type="checkbox"/>	
homepage_body_styled_view_value	string		<input type="checkbox"/>	
homepage_body_view_representation	string		<input type="checkbox"/>	
homepage_body_view_value	string		<input type="checkbox"/>	
homepage_history_contributors	string		<input type="checkbox"/>	
homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may return an alternative value.
homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_createdDate	datetime		<input type="checkbox"/>	
homepage_history_lastUpdated_byAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_lastUpdated_byAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_lastUpdated_byActive	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_lastUpdated_byDisplayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_history_lastUpdated_byEmailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_lastUpdated_byKey	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon

Name	Data Type	Label	Required	Documentation
homepage_history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_lastUpdated_by_llaborators	string		<input type="checkbox"/>	
homepage_history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
homepage_history_lastUpdated_lanks	string		<input type="checkbox"/>	
homepage_history_lastUpdated_message	string		<input type="checkbox"/>	
homepage_history_lastUpdated_menorEdit	boolean		<input type="checkbox"/>	
homepage_history_lastUpdated_number	int32		<input type="checkbox"/>	
homepage_history_lastUpdated_when	string		<input type="checkbox"/>	
homepage_history_latest	boolean		<input type="checkbox"/>	
homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.

Name	Data Type	Label	Required	Documentation
homepage_history_nextVersion_b y_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_nextVersion_b y_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_history_nextVersion_b y_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_nextVersion_b y_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_nextVersion_b y_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_nextVersion_c ollaborators	string		<input type="checkbox"/>	
homepage_history_nextVersion_fri endlyWhen	string		<input type="checkbox"/>	
homepage_history_nextVersion_lin ks	string		<input type="checkbox"/>	
homepage_history_nextVersion_m essage	string		<input type="checkbox"/>	
homepage_history_nextVersion_mi norEdit	boolean		<input type="checkbox"/>	
homepage_history_nextVersion_n umber	int32		<input type="checkbox"/>	
homepage_history_nextVersion_w hen	string		<input type="checkbox"/>	
homepage_history_previousVersio n_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
homepage_history_previousVersio n_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
homepage_history_previousVersion_links	string		<input type="checkbox"/>	
homepage_history_previousVersion_message	string		<input type="checkbox"/>	
homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
homepage_history_previousVersion_when	string		<input type="checkbox"/>	
homepage_id	int64		<input type="checkbox"/>	
homepage_key	string		<input type="checkbox"/>	
homepage_status	string		<input type="checkbox"/>	
homepage_title	string		<input type="checkbox"/>	
homepage_type	string		<input type="checkbox"/>	
homepage_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users.

Name	Data Type	Label	Required	Documentation
				We recommend you treat this value as an error case if you need to access more information about the user.
homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
homepage_version_by_emailAddresses	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
homepage_version_collaborators	string		<input type="checkbox"/>	
homepage_version_friendlyWhen	string		<input type="checkbox"/>	
homepage_version_links	string		<input type="checkbox"/>	
homepage_version_message	string		<input type="checkbox"/>	
homepage_version_minorEdit	boolean		<input type="checkbox"/>	
homepage_version_number	int32		<input type="checkbox"/>	
homepage_version_when	string		<input type="checkbox"/>	
icon_height	int32		<input type="checkbox"/>	
icon_isDefault	boolean		<input type="checkbox"/>	
icon_path	string		<input type="checkbox"/>	
icon_width	int32		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	ID.
key	string		<input type="checkbox"/>	Key.
lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
lookAndFeel_content_body_background	string		<input type="checkbox"/>	
lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
lookAndFeel_content_container_background	string		<input type="checkbox"/>	
lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
lookAndFeel_content_header_background	string		<input type="checkbox"/>	
lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_header_button_backgrounColor	string		<input type="checkbox"/>	
lookAndFeel_header_button_color	string		<input type="checkbox"/>	
lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
lookAndFeel_header_search_color	string		<input type="checkbox"/>	
lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
lookAndFeel_headings	string		<input type="checkbox"/>	
lookAndFeel_links	string		<input type="checkbox"/>	
lookAndFeel_menus_color	string		<input type="checkbox"/>	
lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
name	string		<input type="checkbox"/>	Name.
settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
status	string		<input type="checkbox"/>	Status.
type	string		<input type="checkbox"/>	Type.

3.1.17 SystemInformation: Atlassian Confluence System Information

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: System Information

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter

case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: `/settings/systemInfo`

Insert Atlassian Confluence API URL: `/settings/systemInfo`

Update Atlassian Confluence API URL: `/settings/systemInfo`

Delete Atlassian Confluence API URL: `/settings/systemInfo`

Field Selection Method: NotRequired

Table Function Columns

The columns of the table function `SystemInformation` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
cloudId	string		<input type="checkbox"/>	
commitHash	string		<input type="checkbox"/>	

3.1.18 UserByAccountId: Atlassian Confluence User by Account ID

Catalog: JIRA

Schema: Confluence

Primary Keys: id

Label: User by Account ID

This is a read-only table function. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table `NativePlatformScalarRequests` to upload data to the Atlassian Confluence API.

Select Atlassian Confluence API URL: `/user?accountId={accountId}&expand=personalSpace`

Insert Atlassian Confluence API URL: `/user?accountId={accountId}&expand=personalSpace`

Update Atlassian Confluence API URL: `/user?accountId={accountId}&expand=personalSpace`

Delete Atlassian Confluence API URL: `/user?accountId={accountId}&expand=personalSpace`

Field Selection Method: NotRequired

Parameters of Table Function

The following parameters can be used to control the behaviour of the table function `UserByAccountId`. A value must be provided at all times for required parameters, but optional parameters in general do not need to have a value and the execution will default to a pre-defined behaviour. Values can be specified by position and by name. In both cases, all parameters not specified will be treated using their default values.

Value specification by position is done by listing all values from the first to the last needed value. For example with `select * from table(value1, value2, value3)` on a table with four parameters will use the default value for the fourth parameter and the specified values for the first three.

Value specification by name is done by listing all values that require a value. For example with `select * from table(name1 => value1, name3 => value3)` on the same table will use the default values for the second and fourth parameters and the specified values for the first and third.

Name	Data Type	Required	Default Value	Documentation
accountId	string	<input checked="" type="checkbox"/>		Account ID.

Table Function Columns

The columns of the table function `UserByAccountId` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may be the same as <code>publicName</code> .
email	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_history_contributors	string		<input type="checkbox"/>	
personalSpace_homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdDate	datetime		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_latest	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b2cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account,

Name	Data Type	Label	Required	Documentation
				app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_id	int64		<input type="checkbox"/>	
personalSpace_homepage_key	string		<input type="checkbox"/>	
personalSpace_homepage_status	string		<input type="checkbox"/>	
personalSpace_homepage_title	string		<input type="checkbox"/>	
personalSpace_homepage_type	string		<input type="checkbox"/>	
personalSpace_homepage_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian

Name	Data Type	Label	Required	Documentation
				products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_version_links	string		<input type="checkbox"/>	
personalSpace_homepage_version_message	string		<input type="checkbox"/>	
personalSpace_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_version_number	int32		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_version	string		<input type="checkbox"/>	
personalSpace_icon_height	int32		<input type="checkbox"/>	
personalSpace_icon_isDefault	boolean		<input type="checkbox"/>	
personalSpace_icon_path	string		<input type="checkbox"/>	
personalSpace_icon_width	int32		<input type="checkbox"/>	
personalSpace_id	int64		<input type="checkbox"/>	ID.
personalSpace_key	string		<input type="checkbox"/>	Key.
personalSpace_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_headings	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_links	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_name	string		<input type="checkbox"/>	Name.
personalSpace_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to

Name	Data Type	Label	Required	Documentation
				provide content-only theming without overriding the space home.
personalSpace_status	string		<input type="checkbox"/>	Status.
personalSpace_type	string		<input type="checkbox"/>	Type.
profilePicture_height	int32		<input type="checkbox"/>	
profilePicture_isDefault	boolean		<input type="checkbox"/>	
profilePicture_path	string		<input type="checkbox"/>	
profilePicture_width	int32		<input type="checkbox"/>	
publicName	string		<input type="checkbox"/>	The public name or nickname of the user. Will always contain a value.
type	string		<input type="checkbox"/>	Valid values: known, unknown, anonymous, user.

4 Schema: Native

4.1 Tables

4.1.1 NATIVEPLATFORMSCALARREQUESTS: Atlassian Confluence Native Platform Scalar Requests

Direct access to native API.

Catalog: JIRA

Schema: Native

Alias: npt

Label: Native Platform Scalar Requests

Documentation:

The NativePlatformScalarRequests table provides direct access to the native API protocol over an established connection to the Atlassian Confluence API server. It will contain a new row for every row inserted with a native API request in PAYLOAD_TEXT with the results of unaltered forwarding of the payload to the Atlassian Confluence API server.

Retrieve: true

Insert: true

Update: false

Delete: false

View Columns

The columns of the view NATIVEPLATFORMSCALARREQUESTS are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

Name	Data Type	Label	Required	Documentation
BLOB_PREFERRED	boolean	BLOB Preferred	<input checked="" type="checkbox"/>	Indicator whether a BLOB result is preferred over text.

Name	Data Type	Label	Required	Documentation
BOL_RESPONSE_CACHE_MAX_AGE_SEC	int32	Response Cache Maximum Age (sec)	<input type="checkbox"/>	Maximum age in seconds of Bridge Online response cache entries to be used.
CONTENT_TYPE	string(240)	Content Type	<input type="checkbox"/>	
DATE_ENDED	datetime	End Date	<input checked="" type="checkbox"/>	
DATE_STARTED	datetime	Start Date	<input checked="" type="checkbox"/>	
DRY_RUN	boolean	Run without Actions	<input checked="" type="checkbox"/>	
DURATION_MS	int32	Duration (ms)	<input checked="" type="checkbox"/>	
ERROR_MESSAGE_CODE	string(30)	Error Message Code	<input type="checkbox"/>	
ERROR_MESSAGE_TEXT	string(32000)	Error Message Text	<input type="checkbox"/>	
FAIL_ON_ERROR	boolean	Fail on Error	<input checked="" type="checkbox"/>	Whether to raise an exception when processing the native request triggered an error from the provider.
HTTP_DISK_CACHE_MAX_AGE_SEC	int32	HTTP Disk Cache Maximum Age (sec)	<input type="checkbox"/>	Maximum age in seconds of HTTP disk cache entries to be used.
HTTP_DISK_CACHE_SAVE	boolean	Save HTTP Disk Cache	<input type="checkbox"/>	Whether results can be stored in HTTP disk cache.
HTTP_DISK_CACHE_USE	boolean	Use HTTP Disk Cache	<input type="checkbox"/>	Whether results can be fetched from HTTP disk cache.
HTTP_MEMORY_CACHE_MAX_AGE_SEC	int32	HTTP Memory Cache Maximum Age (sec)	<input type="checkbox"/>	Maximum age in seconds of HTTP memory cache entries to be used.
HTTP_MEMORY_CACHE_SAVE	boolean	Save HTTP Memory Cache	<input type="checkbox"/>	Whether results can be stored in HTTP memory cache.
HTTP_MEMORY_CACHE_USE	boolean	Use HTTP Memory Cache	<input type="checkbox"/>	Whether results can be fetched from HTTP memory cache.
HTTP_METHOD	string(30)	HTTP Method	<input type="checkbox"/>	
HTTP_STATUS_CODE	int16	HTTP Status Code	<input type="checkbox"/>	
ORIG_SYSTEM_GROUP	string(4000)	Original System Group	<input type="checkbox"/>	
ORIG_SYSTEM_REFERENCE	string(4000)	Original System Reference	<input type="checkbox"/>	
PAYOUT_TEXT	string	Payout	<input type="checkbox"/>	
RESULT_BLOB	byte[]	Result BLOB	<input type="checkbox"/>	
RESULT_DATE_TIME_UTC	datetime		<input type="checkbox"/>	
RESULT_NUMBER	decimal		<input type="checkbox"/>	
RESULT_TEXT	string	Result Text	<input type="checkbox"/>	
SUCCESSFUL	boolean	Successful	<input checked="" type="checkbox"/>	
TIMEOUT_SEC	int32	Timeout (sec)	<input type="checkbox"/>	Timeout in seconds.
TRANSACTION_ID	int32	Transaction ID	<input checked="" type="checkbox"/>	Incrementing ID of the transaction.
URL	string(4000)	URL	<input type="checkbox"/>	

5 Schema: Views

5.1 Views

5.1.1 ContentBlogs

Catalog: JIRA

Schema: Views

This is a read-only view. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

View Columns

The columns of the view ContentBlogs are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.

Name	Data Type	Label	Required	Documentation
history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
sce_homepage_body_editor_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor_value	string		<input type="checkbox"/>	
sce_homepage_body_editor2_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor2_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_homepage_body_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_storage_representation	string		<input type="checkbox"/>	
sce_homepage_body_storage_value	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_value	string		<input type="checkbox"/>	
sce_homepage_body_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_view_value	string		<input type="checkbox"/>	
sce_homepage_history_contributors	string		<input type="checkbox"/>	
sce_homepage_history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_createdByAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_createdByActive	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_createdByDisplayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_createdByEmailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdByKey	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_createdByLocale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
sce_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdDate	datetime		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_lastUpdate_d_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_lastUpdate_d_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_lastUpdate_d_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_lastUpdate_d_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_lastUpdate_d_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_lastUpdate_d_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the

Name	Data Type	Label	Required	Documentation
				user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_links	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_message	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_number	int32		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_when	string		<input type="checkbox"/>	
sce_homepage_history_latest	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
sce_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
sce_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
sce_homepage_id	int64		<input type="checkbox"/>	
sce_homepage_key	string		<input type="checkbox"/>	
sce_homepage_status	string		<input type="checkbox"/>	
sce_homepage_title	string		<input type="checkbox"/>	
sce_homepage_type	string		<input type="checkbox"/>	
sce_homepage_version_by_account	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk

Name	Data Type	Label	Required	Documentation
				account representing an external service desk
sce_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_collaborators	string		<input type="checkbox"/>	
sce_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_version_links	string		<input type="checkbox"/>	
sce_homepage_version_message	string		<input type="checkbox"/>	
sce_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_version_number	int32		<input type="checkbox"/>	
sce_homepage_version_when	string		<input type="checkbox"/>	
sce_icon_height	int32		<input type="checkbox"/>	
sce_icon_isDefault	boolean		<input type="checkbox"/>	
sce_icon_path	string		<input type="checkbox"/>	
sce_icon_width	int32		<input type="checkbox"/>	
sce_id	int64		<input type="checkbox"/>	ID.
sce_key	string		<input type="checkbox"/>	Key.
sce_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_orderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
sce_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_headings	string		<input type="checkbox"/>	
sce_lookAndFeel_links	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_color	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
sce_name	string		<input type="checkbox"/>	Name.
sce_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
sce_status	string		<input type="checkbox"/>	Status.
sce_type	string		<input type="checkbox"/>	Type.
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.

Name	Data Type	Label	Required	Documentation
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

5.1.2 ContentBlogsMetadata

Catalog: JIRA

Schema: Views

This is a read-only view. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

View Columns

The columns of the view ContentBlogsMetadata are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.

Name	Data Type	Label	Required	Documentation
history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy

Name	Data Type	Label	Required	Documentation
				setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon

Name	Data Type	Label	Required	Documentation
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon

Name	Data Type	Label	Required	Documentation
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
sce_homepage_body_editor_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor_value	string		<input type="checkbox"/>	
sce_homepage_body_editor2_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor2_value	string		<input type="checkbox"/>	
sce_homepage_body_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_storage_representation	string		<input type="checkbox"/>	
sce_homepage_body_storage_value	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_value	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_homepage_body_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_view_value	string		<input type="checkbox"/>	
sce_homepage_history_contributors	string		<input type="checkbox"/>	
sce_homepage_history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_createdByAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_createdByActive	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_createdByDisplayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_createdByEmailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdByKey	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_createdByLocale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdByName	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_createdByTimeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdDate	datetime		<input type="checkbox"/>	
sce_homepage_history_lastUpdateD_byAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the

Name	Data Type	Label	Required	Documentation
				user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_lastUpdate_d_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_lastUpdate_d_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_lastUpdate_d_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_lastUpdate_d_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_lastUpdate_d_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_lastUpdate_d_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_links	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_message	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_minorEdit	boolean		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_homepage_history_lastUpdate_d_number	int32		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_when	string		<input type="checkbox"/>	
sce_homepage_history_latest	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the

Name	Data Type	Label	Required	Documentation
				user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
sce_homepage_id	int64		<input type="checkbox"/>	
sce_homepage_key	string		<input type="checkbox"/>	
sce_homepage_status	string		<input type="checkbox"/>	
sce_homepage_title	string		<input type="checkbox"/>	
sce_homepage_type	string		<input type="checkbox"/>	
sce_homepage_version_by_account	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
sce_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_collaborators	string		<input type="checkbox"/>	
sce_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_version_links	string		<input type="checkbox"/>	
sce_homepage_version_message	string		<input type="checkbox"/>	
sce_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_version_number	int32		<input type="checkbox"/>	
sce_homepage_version_when	string		<input type="checkbox"/>	
sce_icon_height	int32		<input type="checkbox"/>	
sce_icon_isDefault	boolean		<input type="checkbox"/>	
sce_icon_path	string		<input type="checkbox"/>	
sce_icon_width	int32		<input type="checkbox"/>	
sce_id	int64		<input type="checkbox"/>	ID.
sce_key	string		<input type="checkbox"/>	Key.
sce_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
sce_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondNavigation_color	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_headings	string		<input type="checkbox"/>	
sce_lookAndFeel_links	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_color	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
sce_name	string		<input type="checkbox"/>	Name.
sce_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
sce_status	string		<input type="checkbox"/>	Status.
sce_type	string		<input type="checkbox"/>	Type.
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.

Name	Data Type	Label	Required	Documentation
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

5.1.3 ContentPages

Catalog: JIRA

Schema: Views

This is a read-only view. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

View Columns

The columns of the view ContentPages are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
sce_homepage_body_editor_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor_value	string		<input type="checkbox"/>	
sce_homepage_body_editor2_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor2_value	string		<input type="checkbox"/>	
sce_homepage_body_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_storage_representation	string		<input type="checkbox"/>	
sce_homepage_body_storage_value	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_value	string		<input type="checkbox"/>	
sce_homepage_body_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_view_value	string		<input type="checkbox"/>	
sce_homepage_history_contributors	string		<input type="checkbox"/>	
sce_homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is

Name	Data Type	Label	Required	Documentation
				missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdDate	datetime		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_lastUpdate_d_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian

Name	Data Type	Label	Required	Documentation
				regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_lastUpdate_d_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_lastUpdate_d_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_lastUpdate_d_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_lastUpdate_d_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_lastUpdate_d_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_links	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_message	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_number	int32		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_when	string		<input type="checkbox"/>	
sce_homepage_history_latest	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which

Name	Data Type	Label	Required	Documentation
				only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian

Name	Data Type	Label	Required	Documentation
				products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_homepage_history_previousVersionWhen	string		<input type="checkbox"/>	
sce_homepage_id	int64		<input type="checkbox"/>	
sce_homepage_key	string		<input type="checkbox"/>	
sce_homepage_status	string		<input type="checkbox"/>	
sce_homepage_title	string		<input type="checkbox"/>	
sce_homepage_type	string		<input type="checkbox"/>	
sce_homepage_version_by_account	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
sce_homepage_version_collaborators	string		<input type="checkbox"/>	
sce_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_version_links	string		<input type="checkbox"/>	
sce_homepage_version_message	string		<input type="checkbox"/>	
sce_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_version_number	int32		<input type="checkbox"/>	
sce_homepage_version_when	string		<input type="checkbox"/>	
sce_icon_height	int32		<input type="checkbox"/>	
sce_icon_isDefault	boolean		<input type="checkbox"/>	
sce_icon_path	string		<input type="checkbox"/>	
sce_icon_width	int32		<input type="checkbox"/>	
sce_id	int64		<input type="checkbox"/>	ID.
sce_key	string		<input type="checkbox"/>	Key.
sce_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
sce_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_headings	string		<input type="checkbox"/>	
sce_lookAndFeel_links	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_color	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
sce_name	string		<input type="checkbox"/>	Name.
sce_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a

Name	Data Type	Label	Required	Documentation
				space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
sce_status	string		<input type="checkbox"/>	Status.
sce_type	string		<input type="checkbox"/>	Type.
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

5.1.4 ContentPagesMetadata

Catalog: JIRA

Schema: Views

This is a read-only view. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

View Columns

The columns of the view ContentPagesMetadata are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
body_anonymous_export_view_representation	string		<input type="checkbox"/>	
body_anonymous_export_view_value	string		<input type="checkbox"/>	
body_atlas_doc_format_representation	string		<input type="checkbox"/>	
body_atlas_doc_format_value	string		<input type="checkbox"/>	
body_editor_representation	string		<input type="checkbox"/>	
body_editor_value	string		<input type="checkbox"/>	
body_editor2_representation	string		<input type="checkbox"/>	
body_editor2_value	string		<input type="checkbox"/>	
body_export_view_representation	string		<input type="checkbox"/>	
body_export_view_value	string		<input type="checkbox"/>	
body_storage_representation	string		<input type="checkbox"/>	
body_storage_value	string		<input type="checkbox"/>	
body_styled_view_representation	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
body_styled_view_value	string		<input type="checkbox"/>	
body_view_representation	string		<input type="checkbox"/>	
body_view_value	string		<input type="checkbox"/>	
history_contributors	string		<input type="checkbox"/>	
history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_createdByAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_createdByActive	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_createdByDisplayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_createdByEmailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdByKey	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_createdByLocale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_createdByName	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_createdByTimeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_createdDate	datetime		<input type="checkbox"/>	
history_lastUpdatedByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example,

Name	Data Type	Label	Required	Documentation
				5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_lastUpdated_collaborators	string		<input type="checkbox"/>	
history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
history_lastUpdated_links	string		<input type="checkbox"/>	
history_lastUpdated_message	string		<input type="checkbox"/>	
history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
history_lastUpdated_number	int32		<input type="checkbox"/>	
history_lastUpdated_when	string		<input type="checkbox"/>	
history_latest	boolean		<input type="checkbox"/>	
history_nextVersion_byAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian

Name	Data Type	Label	Required	Documentation
				products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_nextVersion_collaborators	string		<input type="checkbox"/>	
history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
history_nextVersion_links	string		<input type="checkbox"/>	
history_nextVersion_message	string		<input type="checkbox"/>	
history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
history_nextVersion_number	int32		<input type="checkbox"/>	
history_nextVersion_when	string		<input type="checkbox"/>	
history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example,

Name	Data Type	Label	Required	Documentation
				5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
history_previousVersion_collaborators	string		<input type="checkbox"/>	
history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
history_previousVersion_links	string		<input type="checkbox"/>	
history_previousVersion_message	string		<input type="checkbox"/>	
history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
history_previousVersion_number	int32		<input type="checkbox"/>	
history_previousVersion_when	string		<input type="checkbox"/>	
id	int64		<input type="checkbox"/>	
key	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	
sce_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
sce_homepage_body_editor_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor_value	string		<input type="checkbox"/>	
sce_homepage_body_editor2_representation	string		<input type="checkbox"/>	
sce_homepage_body_editor2_value	string		<input type="checkbox"/>	
sce_homepage_body_export_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_export_view_value	string		<input type="checkbox"/>	
sce_homepage_body_storage_representation	string		<input type="checkbox"/>	
sce_homepage_body_storage_value	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_styled_view_value	string		<input type="checkbox"/>	
sce_homepage_body_view_representation	string		<input type="checkbox"/>	
sce_homepage_body_view_value	string		<input type="checkbox"/>	
sce_homepage_history_contributors	string		<input type="checkbox"/>	
sce_homepage_history_createdByAccountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_createdByAccountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk

Name	Data Type	Label	Required	Documentation
				account representing an external service desk
sce_homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_createdDate	datetime		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_lastUpdate_d_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_lastUpdate_d_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_lastUpdate_d_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.

Name	Data Type	Label	Required	Documentation
sce_homepage_history_lastUpdate_d_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_lastUpdate_d_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_lastUpdate_d_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_lastUpdate_d_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_links	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_message	string		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_number	int32		<input type="checkbox"/>	
sce_homepage_history_lastUpdate_d_when	string		<input type="checkbox"/>	
sce_homepage_history_latest	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk

Name	Data Type	Label	Required	Documentation
sce_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b2cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account,

Name	Data Type	Label	Required	Documentation
				app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
sce_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
sce_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
sce_homepage_id	int64		<input type="checkbox"/>	
sce_homepage_key	string		<input type="checkbox"/>	
sce_homepage_status	string		<input type="checkbox"/>	
sce_homepage_title	string		<input type="checkbox"/>	
sce_homepage_type	string		<input type="checkbox"/>	
sce_homepage_version_by_account	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian

Name	Data Type	Label	Required	Documentation
				products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
sce_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
sce_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
sce_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
sce_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
sce_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
sce_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
sce_homepage_version_collaborators	string		<input type="checkbox"/>	
sce_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
sce_homepage_version_links	string		<input type="checkbox"/>	
sce_homepage_version_message	string		<input type="checkbox"/>	
sce_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
sce_homepage_version_number	int32		<input type="checkbox"/>	
sce_homepage_version_when	string		<input type="checkbox"/>	
sce_icon_height	int32		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_icon_isDefault	boolean		<input type="checkbox"/>	
sce_icon_path	string		<input type="checkbox"/>	
sce_icon_width	int32		<input type="checkbox"/>	
sce_id	int64		<input type="checkbox"/>	ID.
sce_key	string		<input type="checkbox"/>	Key.
sce_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
sce_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
sce_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
sce_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
sce_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
sce_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
sce_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
sce_lookAndFeel_headings	string		<input type="checkbox"/>	
sce_lookAndFeel_links	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_color	string		<input type="checkbox"/>	
sce_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
sce_name	string		<input type="checkbox"/>	Name.
sce_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming without overriding the space home.
sce_status	string		<input type="checkbox"/>	Status.
sce_type	string		<input type="checkbox"/>	Type.
status	string		<input type="checkbox"/>	
title	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
type	string		<input type="checkbox"/>	
version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
version_collaborators	string		<input type="checkbox"/>	
version_friendlyWhen	string		<input type="checkbox"/>	
version_links	string		<input type="checkbox"/>	
version_message	string		<input type="checkbox"/>	
version_minorEdit	boolean		<input type="checkbox"/>	
version_number	int32		<input type="checkbox"/>	
version_when	string		<input type="checkbox"/>	

5.1.5 GroupMembers

Catalog: JIRA

Schema: Views

This is a read-only view. The Atlassian Confluence API may not support changing the data or the Invantive SQL driver for Atlassian Confluence does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the Atlassian Confluence API.

View Columns

The columns of the view GroupMembers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may be the same as publicName.
email	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
grp_name	string		<input type="checkbox"/>	
grp_type	string		<input type="checkbox"/>	
personalSpace_homepage_body_anonymous_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_anonymous_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_atlas_doc_format_representation	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_body_atlas_doc_format_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_editor2_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_export_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_storage_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_styled_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_representation	string		<input type="checkbox"/>	
personalSpace_homepage_body_view_value	string		<input type="checkbox"/>	
personalSpace_homepage_history_contributors	string		<input type="checkbox"/>	
personalSpace_homepage_history_createdBy_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_createdBy_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_createdBy_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_createdBy_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_createdBy_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_createdBy_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdBy_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_createdBy_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_createdDate	datetime		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_lastUpdated_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_lastUpdated_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_lastUpdated_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_lastUpdated_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_lastUpdated_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_lastUpdated_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_lastUpdated_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_lastUpdated_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_lastUpdated_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_latest	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_nextVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_nextVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.

Name	Data Type	Label	Required	Documentation
personalSpace_homepage_history_nextVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_nextVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_nextVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_nextVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_nextVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_nextVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_history_previousVersion_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems,

Name	Data Type	Label	Required	Documentation
				customer Jira Service Desk account representing an external service desk
personalSpace_homepage_history_previousVersion_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_history_previousVersion_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_history_previousVersion_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_history_previousVersion_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_history_previousVersion_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_history_previousVersion_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_links	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_message	string		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_number	int32		<input type="checkbox"/>	
personalSpace_homepage_history_previousVersion_when	string		<input type="checkbox"/>	
personalSpace_homepage_id	int64		<input type="checkbox"/>	
personalSpace_homepage_key	string		<input type="checkbox"/>	
personalSpace_homepage_status	string		<input type="checkbox"/>	
personalSpace_homepage_title	string		<input type="checkbox"/>	
personalSpace_homepage_type	string		<input type="checkbox"/>	
personalSpace_homepage_version_by_accountId	string		<input type="checkbox"/>	The account ID of the user, which uniquely identifies the user across all Atlassian products. For example, 5b10ac8d82e05b22cc7d4ef5. Required in requests. An

Name	Data Type	Label	Required	Documentation
				account ID with value unknown is returned when there is missing data for a user, which only happens for deleted users. We recommend you treat this value as an error case if you need to access more information about the user.
personalSpace_homepage_version_by_accountType	string		<input type="checkbox"/>	The user account type. Can take the following values: atlassian regular Atlassian user account, app system account used for Connect applications and OAuth to represent external systems, customer Jira Service Desk account representing an external service desk
personalSpace_homepage_version_by_active	boolean		<input type="checkbox"/>	Indicates whether the user is active.
personalSpace_homepage_version_by_displayName	string		<input type="checkbox"/>	The display name of the user. Depending on the user's privacy setting, this may return an alternative value.
personalSpace_homepage_version_by_emailAddress	string		<input type="checkbox"/>	The email address of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_key	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon
personalSpace_homepage_version_by_locale	string		<input type="checkbox"/>	The locale of the user. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_by_name	string		<input type="checkbox"/>	This property is no longer available and will be removed from the documentation soon.
personalSpace_homepage_version_by_timeZone	string		<input type="checkbox"/>	The time zone specified in the user's profile. Depending on the user's privacy setting, this may be returned as null.
personalSpace_homepage_version_collaborators	string		<input type="checkbox"/>	
personalSpace_homepage_version_friendlyWhen	string		<input type="checkbox"/>	
personalSpace_homepage_version_links	string		<input type="checkbox"/>	
personalSpace_homepage_version_message	string		<input type="checkbox"/>	
personalSpace_homepage_version_minorEdit	boolean		<input type="checkbox"/>	
personalSpace_homepage_version_number	int32		<input type="checkbox"/>	
personalSpace_homepage_version_when	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_icon_height	int32		<input type="checkbox"/>	
personalSpace_icon_isDefault	boolean		<input type="checkbox"/>	
personalSpace_icon_path	string		<input type="checkbox"/>	
personalSpace_icon_width	int32		<input type="checkbox"/>	
personalSpace_id	int64		<input type="checkbox"/>	ID.
personalSpace_key	string		<input type="checkbox"/>	Key.
personalSpace_lookAndFeel_bordersAndDividers	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_body_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_container_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_borderRadius	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_header_padding	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_background	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundColor	string		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
personalSpace_lookAndFeel_content_screen_backgroundImage	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_backgroundSize	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterBottom	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterLeft	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterRight	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_content_screen_gutterTop	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_button_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_primaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_backgroundColor	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_search_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_header_secondaryNavigation_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_headings	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_links	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_color	string		<input type="checkbox"/>	
personalSpace_lookAndFeel_menus_hoverOrFocus	string		<input type="checkbox"/>	
personalSpace_name	string		<input type="checkbox"/>	Name.
personalSpace_settings_routeOverrideEnabled	boolean		<input type="checkbox"/>	Defines whether an override for the space home should be used. This is used in conjunction with a space theme provided by an app. For example, if this property is set to true, a theme can display a page other than the space homepage when users visit the root URL for a space. This property allows apps to provide content-only theming

Name	Data Type	Label	Required	Documentation
				without overriding the space home.
personalSpace_status	string		<input type="checkbox"/>	Status.
personalSpace_type	string		<input type="checkbox"/>	Type.
profilePicture_height	int32		<input type="checkbox"/>	
profilePicture_isDefault	boolean		<input type="checkbox"/>	
profilePicture_path	string		<input type="checkbox"/>	
profilePicture_width	int32		<input type="checkbox"/>	
publicName	string		<input type="checkbox"/>	The public name or nickname of the user. Will always contain a value.
type	string		<input type="checkbox"/>	Valid values: known, unknown, anonymous, user.

Index

- A -

accountId 46, 55, 96, 163
 accountType 46, 55, 96, 163
 add-odata-mandatory-filters 2
 analysis-enforce-row-uniqueness 2
 Anonymous User 15
 AnonymousUser 15
 api-access-token 2
 api-client-id 2
 api-client-secret 2
 api-password-authentication 2
 api-pre-expiry-refresh-sec 2
 api-redirect-url 2
 api-refresh-token 2
 api-scope 2
 api-token-url 2
 api-url 2
 associatedObjects 16
 Atlassian Confluence 1, 15, 16, 18, 19, 26, 32, 39, 46, 55, 65, 66, 70, 77, 86, 95, 96, 106, 108, 121, 135, 149, 163
 Audit Logs 16
 Audit Retention Settings 18
 AuditLogs 16
 AuditRetentionSettings 18
 author_accountId 16
 author_accountType 16
 author_active 16
 author_displayName 16
 author_emailAddress 16
 author_key 16
 author_locale 16
 author_name 16
 author_timeZone 16

- B -

BLOB Preferred 106
 BLOB_PREFERRED 106
 Blueprint Templates 18
 BlueprintTemplates 18
 body_anonymous_export_view_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_anonymous_export_view_value 19, 26, 32, 39, 70, 108, 121, 135, 149

body_atlas_doc_format_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_atlas_doc_format_value 19, 26, 32, 39, 108, 121, 135, 149
 body_body_contexts 18
 body_body_keys 18
 body_body_superbatch 18
 body_body_tags 18
 body_body_uris 18
 body_editor_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_editor_value 19, 26, 32, 39, 108, 121, 135, 149
 body_editor2_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_editor2_value 19, 26, 32, 39, 108, 121, 135, 149
 body_export_view_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_export_view_value 19, 26, 32, 39, 108, 121, 135, 149
 body_representation 18
 body_storage_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_storage_value 19, 26, 32, 39, 108, 121, 135, 149
 body_styled_view_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_styled_view_value 19, 26, 32, 39, 108, 121, 135, 149
 body_value 18
 body_view_representation 19, 26, 32, 39, 108, 121, 135, 149
 body_view_value 19, 26, 32, 39, 108, 121, 135, 149
 BOL_RESPONSE_CACHE_MAX_AGE_SEC 106
 bulk-delete-page-size-rows 2
 bulk-insert-page-size-bytes 2
 bulk-insert-page-size-rows 2

- C -

category 16
 changedValues 16
 cloudId 95
 commitHash 95
 Confluence 1
 Content Blogs by Space Key 19
 Content Pages by Space Key 32
 Content Type 106
 content_body_anonymous_export_view_representation 19, 26, 32, 39, 70
 content_body_anonymous_export_view_value 70
 content_body_atlas_doc_format_representation 70

content_body_atlas_doc_format_value 70
 content_body_editor_representation 70
 content_body_editor_value 70
 content_body_editor2_representation 70
 content_body_editor2_value 70
 content_body_export_view_representation 70
 content_body_export_view_value 70
 content_body_storage_representation 70
 content_body_storage_value 70
 content_body_styled_view_representation 70
 content_body_styled_view_value 70
 content_body_view_representation 70
 content_body_view_value 70
 content_history_contributors 70
 content_history_createdBy_accountId 70
 content_history_createdBy_accountType 70
 content_history_createdBy_active 70
 content_history_createdBy_displayName 70
 content_history_createdBy_emailAddress 70
 content_history_createdBy_key 70
 content_history_createdBy_locale 70
 content_history_createdBy_name 70
 content_history_createdBy_timeZone 70
 content_history_createdDate 70
 content_history_lastUpdated_by_accountId 70
 content_history_lastUpdated_by_accountType 70
 content_history_lastUpdated_by_active 70
 content_history_lastUpdated_by_displayName 70
 content_history_lastUpdated_by_emailAddress 70
 content_history_lastUpdated_by_key 70
 content_history_lastUpdated_by_locale 70
 content_history_lastUpdated_by_name 70
 content_history_lastUpdated_by_timeZone 70
 content_history_lastUpdated_collaborators 70
 content_history_lastUpdated_friendlyWhen 70
 content_history_lastUpdated_links 70
 content_history_lastUpdated_message 70
 content_history_lastUpdated_minorEdit 70
 content_history_lastUpdated_number 70
 content_history_lastUpdated_when 70
 content_history_latest 70
 content_history_nextVersion_by_accountId 70
 content_history_nextVersion_by_accountType 70
 content_history_nextVersion_by_active 70
 content_history_nextVersion_by_displayName 70
 content_history_nextVersion_by_emailAddress 70
 content_history_nextVersion_by_key 70
 content_history_nextVersion_by_locale 70
 content_history_nextVersion_by_name 70
 content_history_nextVersion_by_timeZone 70
 content_history_nextVersion_collaborators 70
 content_history_nextVersion_friendlyWhen 70
 content_history_nextVersion_links 70
 content_history_nextVersion_message 70
 content_history_nextVersion_minorEdit 70
 content_history_nextVersion_number 70
 content_history_nextVersion_when 70
 content_history_previousVersion_by_accountId 70
 content_history_previousVersion_by_accountType 70
 content_history_previousVersion_by_active 70
 content_history_previousVersion_by_displayName 70
 content_history_previousVersion_by_emailAddress 70
 content_history_previousVersion_by_key 70
 content_history_previousVersion_by_locale 70
 content_history_previousVersion_by_name 70
 content_history_previousVersion_by_timeZone 70
 content_history_previousVersion_collaborators 70
 content_history_previousVersion_friendlyWhen 70
 content_history_previousVersion_links 70
 content_history_previousVersion_message 70
 content_history_previousVersion_minorEdit 70
 content_history_previousVersion_number 70
 content_history_previousVersion_when 70
 content_id 70
 content_key 70
 content_status 70
 content_title 70
 CONTENT_TYPE 70, 106
 content_version_by_accountId 70
 content_version_by_accountType 70
 content_version_by_active 70
 content_version_by_displayName 70
 content_version_by_emailAddress 70
 content_version_by_key 70
 content_version_by_locale 70
 content_version_by_name 70
 content_version_by_timeZone 70
 content_version_collaborators 70
 content_version_friendlyWhen 70
 content_version_links 70
 content_version_message 70
 content_version_minorEdit 70
 content_version_number 70
 content_version_when 70
 ContentBlogs 108
 ContentBlogsBySpaceKey 19
 ContentBlogsMetadata 121
 ContentBlogsMetadataBySpaceKey 26
 ContentPages 135
 ContentPagesBySpaceKey 32

ContentPagesMetadata 149
 ContentPagesMetadataBySpaceKey 39
 cql 70
 cqcontext 70
 creationDate 16
 Current User 46
 CurrentUser 46
 custom_bordersAndDividers 66
 custom_content_body_background 66
 custom_content_body_backgroundColor 66
 custom_content_body_backgroundImage 66
 custom_content_body_backgroundSize 66
 custom_content_body_borderRadius 66
 custom_content_body_padding 66
 custom_content_container_background 66
 custom_content_container_backgroundColor 66
 custom_content_container_backgroundImage 66
 custom_content_container_backgroundSize 66
 custom_content_container_borderRadius 66
 custom_content_container_padding 66
 custom_content_header_background 66
 custom_content_header_backgroundColor 66
 custom_content_header_backgroundImage 66
 custom_content_header_backgroundSize 66
 custom_content_header_borderRadius 66
 custom_content_header_padding 66
 custom_content_screen_background 66
 custom_content_screen_backgroundColor 66
 custom_content_screen_backgroundImage 66
 custom_content_screen_backgroundSize 66
 custom_content_screen_gutterBottom 66
 custom_content_screen_gutterLeft 66
 custom_content_screen_gutterRight 66
 custom_content_screen_gutterTop 66
 custom_header_backgroundColor 66
 custom_header_button_backgroundColor 66
 custom_header_button_color 66
 custom_header_primaryNavigation_color 66
 custom_header_primaryNavigation_hoverOrFocus 66
 custom_header_search_backgroundColor 66
 custom_header_search_color 66
 custom_header_secondaryNavigation_color 66
 custom_header_secondaryNavigation_hoverOrFocus 66
 custom_headings 66
 custom_links 66
 custom_menus_color 66
 custom_menus_hoverOrFocus 66

- D -

DATE_ENDED 106
 DATE_STARTED 106
 depth 19, 26, 32, 39
 displayName 15, 46, 55, 96, 163
 download-error-400-bad-request-max-tries 2
 download-error-400-bad-request-sleep-initial-ms 2
 download-error-400-bad-request-sleep-max-ms 2
 download-error-400-bad-request-sleep-multiplicator 2
 download-error-408-request-timeout-max-tries 2
 download-error-408-request-timeout-sleep-initial-ms 2
 download-error-408-request-timeout-sleep-max-ms 2
 download-error-408-request-timeout-sleep-multiplicator 2
 download-error-422-bad-request-max-tries 2
 download-error-422-bad-request-sleep-initial-ms 2
 download-error-422-bad-request-sleep-max-ms 2
 download-error-422-bad-request-sleep-multiplicator 2
 download-error-429-too-many-requests-max-tries 2
 download-error-429-too-many-requests-sleep-initial-ms 2
 download-error-429-too-many-requests-sleep-max-ms 2
 download-error-429-too-many-requests-sleep-multiplicator 2
 download-error-502-server-unavailable-max-tries 2
 download-error-502-server-unavailable-sleep-initial-ms 2
 download-error-502-server-unavailable-sleep-max-ms 2
 download-error-502-server-unavailable-sleep-multiplicator 2
 download-error-503-server-unavailable-max-tries 2
 download-error-503-server-unavailable-sleep-initial-ms 2
 download-error-503-server-unavailable-sleep-max-ms 2
 download-error-503-server-unavailable-sleep-multiplicator 2
 download-error-504-gateway-timeout-max-tries 2
 download-error-504-gateway-timeout-sleep-initial-ms 2
 download-error-504-gateway-timeout-sleep-max-ms 2
 download-error-504-gateway-timeout-sleep-multiplicator 2
 download-error-590-network-connect-timeout-max-tries 2

download-error-590-network-connect-timeout-sleep-init
 al-ms 2 download-error-web-timeout-sleep-initial-ms 2
 download-error-590-network-connect-timeout-sleep-max-ms download-error-web-timeout-sleep-max-ms 2
 x-ms 2 download-error-web-timeout-sleep-multiplicator 2
 download-error-590-network-connect-timeout-sleep-mul
 tiplicator 2 download-error-web-unauthorized-max-tries 2
 download-error-599-network-connect-timeout-max-tries
 2 download-error-web-unauthorized-sleep-initial-ms 2
 download-error-599-network-connect-timeout-sleep-init
 al-ms 2 Driver 1
 download-error-599-network-connect-timeout-sleep-ma DRY_RUN 106
 x-ms 2 Duration (ms) 106
 download-error-599-network-connect-timeout-sleep-mul
 tiplicator 2 DURATION_MS 106

- E -

download-error-argument-exception-max-tries 2 elapsedTime 66
 download-error-argument-exception-sleep-initial-ms 2 email 46, 55, 96, 163
 download-error-argument-exception-sleep-max-ms 2 End Date 106
 download-error-argument-exception-sleep-multiplicator 2 endDate 16
 2 entityType 70
 download-error-internet-down-max-tries 2 Error Message Code 106
 download-error-internet-down-sleep-initial-ms 2 Error Message Text 106
 download-error-internet-down-sleep-max-ms 2 ERROR_MESSAGE_CODE 106
 download-error-internet-down-sleep-multiplicator 2 ERROR_MESSAGE_TEXT 106
 download-error-io-exception-max-tries 2 excerpt 70

- F -

download-error-io-exception-sleep-initial-ms 2 Fail on Error 106
 download-error-io-exception-sleep-max-ms 2 FAIL_ON_ERROR 106
 download-error-io-exception-sleep-multiplicator 2 favourite 86
 download-error-other-exception-max-tries 2 favouriteUserKey 86
 download-error-other-exception-sleep-initial-ms 2 force-case-sensitive-identifiers 2
 download-error-other-exception-sleep-max-ms 2 forced-casing-identifiers 2
 download-error-other-exception-sleep-multiplicator 2 friendlyLastModified 70

- G -

download-error-socket-exception-max-tries 2 global_bordersAndDividers 66
 download-error-socket-exception-sleep-initial-ms 2 global_content_body_background 66
 download-error-socket-exception-sleep-max-ms 2 global_content_body_backgroundColor 66
 download-error-socket-exception-sleep-multiplicator 2 global_content_body_backgroundImage 66
 download-error-socket-exception-sleep-initial-ms 2 global_content_body_backgroundSize 66
 download-error-socket-exception-sleep-max-ms 2 global_content_body_borderRadius 66
 download-error-socket-exception-sleep-multiplicator 2 global_content_body_padding 66
 download-error-web-exception-max-tries 2 global_content_container_background 66
 download-error-web-exception-sleep-initial-ms 2 global_content_container_backgroundColor 66
 download-error-web-exception-sleep-max-ms 2 global_content_container_backgroundImage 66
 download-error-web-exception-sleep-multiplicator 2 global_content_container_backgroundSize 66
 download-error-web-not-implemented-max-tries 2 global_content_container_borderRadius 66
 download-error-web-not-implemented-sleep-initial-ms
 2 or 2

download-error-web-timeout-max-tries 2

global_content_container_padding	66	history_createdBy_locale	19, 26, 32, 39, 108, 121, 135, 149
global_content_header_background	66	history_createdBy_name	19, 26, 32, 39, 108, 121, 135, 149
global_content_header_backgroundColor	66	history_createdBy_timeZone	19, 26, 32, 39, 108, 121, 135, 149
global_content_header_backgroundImage	66	history_createdDate	19, 26, 32, 39, 108, 121, 135, 149
global_content_header_backgroundSize	66	history_lastUpdated_by_accountId	19, 26, 32, 39, 108, 121, 135, 149
global_content_header_borderRadius	66	history_lastUpdated_by_accountType	19, 26, 32, 39, 108, 121, 135, 149
global_content_header_padding	66	history_lastUpdated_by_active	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_background	66	history_lastUpdated_by_displayName	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_backgroundColor	66	history_lastUpdated_by_emailAddress	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_backgroundImage	66	history_lastUpdated_by_key	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_backgroundSize	66	history_lastUpdated_by_locale	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_gutterBottom	66	history_lastUpdated_by_name	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_gutterLeft	66	history_lastUpdated_by_timeZone	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_gutterRight	66	history_lastUpdated_collaborators	19, 26, 32, 39, 108, 121, 135, 149
global_content_screen_gutterTop	66	history_lastUpdated_friendlyWhen	19, 26, 32, 39, 108, 121, 135, 149
global_header_backgroundColor	66	history_lastUpdated_links	19, 26, 32, 39, 108, 121, 135, 149
global_header_button_backgroundColor	66	history_lastUpdated_message	19, 26, 32, 39, 108, 121, 135, 149
global_header_button_color	66	history_lastUpdated_minorEdit	19, 26, 32, 39, 108, 121, 135, 149
global_header_primaryNavigation_color	66	history_lastUpdated_number	19, 26, 32, 39, 108, 121, 135, 149
global_header_primaryNavigation_hoverOrFocus		history_lastUpdated_when	19, 26, 32, 39, 108, 121, 135, 149
global_header_search_backgroundColor	66	history_latest	19, 26, 32, 39, 108, 121, 135, 149
global_header_search_color	66	history_nextVersion_by_accountId	19, 26, 32, 39, 108, 121, 135, 149
global_header_secondaryNavigation_color	66	history_nextVersion_by_accountType	19, 26, 32, 39, 108, 121, 135, 149
global_header_secondaryNavigation_hoverOrFocus	66	history_nextVersion_by_active	19, 26, 32, 39, 108, 121, 135, 149
global_headings	66	history_nextVersion_by_displayName	19, 26, 32, 39, 108, 121, 135, 149
global_links	66	history_nextVersion_by_emailAddress	19, 26, 32, 39, 108, 121, 135, 149
global_menus_color	66	history_nextVersion_by_key	19, 26, 32, 39, 108, 121, 135, 149
global_menus_hoverOrFocus	66	history_nextVersion_by_locale	19, 26, 32, 39, 108, 121, 135, 149
GroupMembers	163		
GroupMembersByGroupName	55		
groupName	55		
Groups	65		
grp_name	163		
grp_type	163		
- H -			
history_contributors	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_accountId	19, 26, 32, 39, 108, 121, 135, 149
history_createdBy_accountId	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_accountType	19, 26, 32, 39, 108, 121, 135, 149
history_createdBy_accountType	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_active	19, 26, 32, 39, 108, 121, 135, 149
history_createdBy_active	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_displayName	19, 26, 32, 39, 108, 121, 135, 149
history_createdBy_displayName	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_emailAddress	19, 26, 32, 39, 108, 121, 135, 149
history_createdBy_emailAddress	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_key	19, 26, 32, 39, 108, 121, 135, 149
history_createdBy_key	19, 26, 32, 39, 108, 121, 135, 149	history_nextVersion_by_locale	19, 26, 32, 39, 108, 121, 135, 149

history_nextVersion_by_name 19, 26, 32, 39, 108
 121, 135, 149
 homepage_body_atlas_doc_format_representation
 77, 86
 history_nextVersion_by_timeZone 19, 26, 32, 39, homepage_body_atlas_doc_format_value 77, 86
 108, 121, 135, 149
 homepage_body_editor_representation 77, 86
 history_nextVersion_collaborators 19, 26, 32, 39, homepage_body_editor_value 77, 86
 108, 121, 135, 149
 homepage_body_editor2_representation 77, 86
 history_nextVersion_friendlyWhen 19, 26, 32, 39, homepage_body_editor2_value 77, 86
 108, 121, 135, 149
 homepage_body_export_view_representation 77, 86
 history_nextVersion_links 19, 26, 32, 39, 108, 121
 135, 149
 homepage_body_export_view_value 77, 86
 homepage_body_storage_representation 77, 86
 homepage_body_storage_value 77, 86
 history_nextVersion_message 19, 26, 32, 39, 108
 121, 135, 149
 homepage_body_styled_view_representation 77, 86
 121, 135, 149
 homepage_body_styled_view_value 77, 86
 history_nextVersion_number 19, 26, 32, 39, 108, homepage_body_view_representation 77, 86
 121, 135, 149
 homepage_body_view_value 77, 86
 history_nextVersion_when 19, 26, 32, 39, 108, 121
 135, 149
 homepage_history_contributors 77, 86
 homepage_history_createdBy_accountId 77, 86
 history_previousVersion_by_accountId 19, 26, 32, homepage_history_createdBy_accountType 77, 86
 39, 108, 121, 135, 149
 homepage_history_createdBy_active 77, 86
 history_previousVersion_by_accountType 19, 26, 32, homepage_history_createdBy_displayName 77, 86
 32, 39, 108, 121, 135, 149
 homepage_history_createdBy_emailAddress 77, 86
 history_previousVersion_by_active 19, 26, 32, 39, homepage_history_createdBy_key 77, 86
 108, 121, 135, 149
 homepage_history_createdBy_locale 77, 86
 history_previousVersion_by_displayName 19, 26, 32, 39, homepage_history_createdBy_name 77, 86
 32, 39, 108, 121, 135, 149
 homepage_history_createdBy_timeZone 77, 86
 32, 39, 108, 121, 135, 149
 homepage_history_createdDate 77, 86
 history_previousVersion_by_key 19, 26, 32, 39, homepage_history_lastUpdated_by_accountId 77,
 108, 121, 135, 149
 86
 homepage_history_lastUpdated_by_accountType
 77, 86
 history_previousVersion_by_locale 19, 26, 32, 39, homepage_history_lastUpdated_by_active 77, 86
 108, 121, 135, 149
 homepage_history_lastUpdated_by_displayName
 77, 86
 history_previousVersion_by_timeZone 19, 26, 32, 39, homepage_history_lastUpdated_by_emailAddress
 77, 86
 39, 108, 121, 135, 149
 homepage_history_lastUpdated_by_key 77, 86
 39, 108, 121, 135, 149
 homepage_history_lastUpdated_by_locale 77, 86
 39, 108, 121, 135, 149
 homepage_history_lastUpdated_by_name 77, 86
 history_previousVersion_links 19, 26, 32, 39, 108
 homepage_history_lastUpdated_by_timeZone 77,
 121, 135, 149
 86
 homepage_history_lastUpdated_collaborators 77,
 108, 121, 135, 149
 86
 homepage_history_lastUpdated_friendlyWhen 77,
 108, 121, 135, 149
 86
 homepage_history_lastUpdated_links 77, 86
 108, 121, 135, 149
 homepage_history_lastUpdated_message 77, 86
 history_previousVersion_when 19, 26, 32, 39, 108
 homepage_history_lastUpdated_minorEdit 77, 86
 121, 135, 149
 homepage_history_lastUpdated_number 77, 86
 homepage_body_anonymous_export_view_representation
 77, 86
 homepage_history_lastUpdated_when 77, 86
 homepage_body_anonymous_export_view_value
 77, 86
 homepage_history_latest 77, 86
 homepage_history_nextVersion_by_accountId 77,
 86

homepage_history_nextVersion_by_accountType 77, 86
 homepage_history_nextVersion_by_active 77, 86
 homepage_history_nextVersion_by_displayName 77, 86
 homepage_history_nextVersion_by_emailAddress 77, 86
 homepage_history_nextVersion_by_key 77, 86
 homepage_history_nextVersion_by_locale 77, 86
 homepage_history_nextVersion_by_name 77, 86
 homepage_history_nextVersion_by_timeZone 77, 86
 homepage_history_nextVersion_collaborators 77, 86
 homepage_history_nextVersion_friendlyWhen 77, 86
 homepage_history_nextVersion_links 77, 86
 homepage_history_nextVersion_message 77, 86
 homepage_history_nextVersion_minorEdit 77, 86
 homepage_history_nextVersion_number 77, 86
 homepage_history_nextVersion_when 77, 86
 homepage_history_previousVersion_by_accountId 77, 86
 homepage_history_previousVersion_by_accountType 77, 86
 homepage_history_previousVersion_by_active 77, 86
 homepage_history_previousVersion_by_displayName 77, 86
 homepage_history_previousVersion_by_emailAddress 77, 86
 homepage_history_previousVersion_by_key 77, 86
 homepage_history_previousVersion_by_locale 77, 86
 homepage_history_previousVersion_by_name 77, 86
 homepage_history_previousVersion_by_timeZone 77, 86
 homepage_history_previousVersion_collaborators 77, 86
 homepage_history_previousVersion_friendlyWhen 77, 86
 homepage_history_previousVersion_links 77, 86
 homepage_history_previousVersion_message 77, 86
 homepage_history_previousVersion_minorEdit 77, 86
 homepage_history_previousVersion_number 77, 86
 homepage_history_previousVersion_when 77, 86
 homepage_id 77, 86
 homepage_key 77, 86
 homepage_status 77, 86
 homepage_title 77, 86
 homepage_type 77, 86
 homepage_version_by_accountId 77, 86
 homepage_version_by_accountType 77, 86
 homepage_version_by_active 77, 86
 homepage_version_by_displayName 77, 86
 homepage_version_by_emailAddress 77, 86
 homepage_version_by_key 77, 86
 homepage_version_by_locale 77, 86
 homepage_version_by_name 77, 86
 homepage_version_by_timeZone 77, 86
 homepage_version_collaborators 77, 86
 homepage_version_friendlyWhen 77, 86
 homepage_version_links 77, 86
 homepage_version_message 77, 86
 homepage_version_minorEdit 77, 86
 homepage_version_number 77, 86
 homepage_version_when 77, 86
 HTTP Disk Cache Maximum Age (sec) 106
 HTTP Memory Cache Maximum Age (sec) 106
 HTTP Method 106
 HTTP Status Code 106
 HTTP_DISK_CACHE_MAX_AGE_SEC 106
 HTTP_DISK_CACHE_SAVE 106
 HTTP_DISK_CACHE_USE 106
 HTTP_MEMORY_CACHE_MAX_AGE_SEC 106
 HTTP_MEMORY_CACHE_SAVE 106
 HTTP_MEMORY_CACHE_USE 106
 HTTP_METHOD 106
 HTTP_STATUS_CODE 106
 http-disk-cache-compression-level 2
 http-disk-cache-directory 2
 http-disk-cache-ignore-write-errors 2
 http-disk-cache-max-age-sec 2
 http-get-timeout-max-ms 2
 http-get-timeout-ms 2
 http-memory-cache-compression-level 2
 http-memory-cache-max-age-sec 2
 http-post-timeout-max-ms 2
 http-post-timeout-ms 2
 icon_height 77, 86
 icon_isDefault 77, 86
 icon_path 77, 86
 icon_width 77, 86
 iconCssClass 70
 ignore-http-400-errors 2
 ignore-http-401-errors 2
 ignore-http-402-errors 2
 ignore-http-403-errors 2
 ignore-http-404-errors 2

- | -

ignore-http-422-errors 2
 ignore-http-429-errors 2
 ignore-http-500-errors 2
 ignore-http-502-errors 2
 ignore-http-503-errors 2
 includeArchivedSpaces 70
 invalid-json-on-get-max-tries 2
 invalid-json-on-get-sleep-initial-ms 2
 invalid-json-on-get-sleep-max-ms 2
 invalid-json-on-get-sleep-multiplicator 2
 invalid-json-on-post-max-tries 2
 invalid-json-on-post-sleep-initial-ms 2
 invalid-json-on-post-sleep-max-ms 2
 invalid-json-on-post-sleep-multiplicator 2
 invantive-sql-compress-sparse-arrays 2
 invantive-sql-correct-invalid-date 2
 invantive-sql-forward-filters-to-data-containers 2
 invantive-sql-share-byte-arrays 2
 invantive-sql-share-strings 2
 invantive-sql-shuffle-fetch-results-data-containers
 invantive-use-cache 2

- J -

join-set-points-per-request 2

- K -

key 19, 26, 32, 39, 77, 86, 108, 121, 135, 149

- L -

lastModified 70
 limit-partition-calls-left 2
 log-native-calls-to-disk-max-events 2
 log-native-calls-to-disk-max-seconds 2
 log-native-calls-to-disk-on-error 2
 log-native-calls-to-disk-on-success 2
 log-native-calls-to-trace 2
 Long Tasks 66
 LongTasks 66
 Look-and-feel Settings 66
 lookAndFeel_bordersAndDividers 77, 86
 lookAndFeel_content_body_background 77, 86
 lookAndFeel_content_body_backgroundColor 77, 86
 lookAndFeel_content_body_backgroundImage 77, 86
 lookAndFeel_content_body_backgroundSize 77, 86
 lookAndFeel_content_body_borderRadius 77, 86

lookAndFeel_content_body_padding 77, 86
 lookAndFeel_content_container_background 77, 86
 lookAndFeel_content_container_backgroundColor 77, 86
 lookAndFeel_content_container_backgroundImage 77, 86
 lookAndFeel_content_container_backgroundSize 77, 86
 lookAndFeel_content_container_borderRadius 77, 86
 lookAndFeel_content_container_padding 77, 86
 lookAndFeel_content_header_background 77, 86
 lookAndFeel_content_header_backgroundColor 77, 86
 lookAndFeel_content_header_backgroundImage 77, 86
 lookAndFeel_content_header_backgroundSize 77, 86
 lookAndFeel_content_header_borderRadius 77, 86
 lookAndFeel_content_header_padding 77, 86
 lookAndFeel_content_screen_background 77, 86
 lookAndFeel_content_screen_backgroundColor 77, 86
 lookAndFeel_content_screen_backgroundImage 77, 86
 lookAndFeel_content_screen_backgroundSize 77, 86
 lookAndFeel_content_screen_gutterBottom 77, 86
 lookAndFeel_content_screen_gutterLeft 77, 86
 lookAndFeel_content_screen_gutterRight 77, 86
 lookAndFeel_content_screen_gutterTop 77, 86
 lookAndFeel_header_backgroundColor 77, 86
 lookAndFeel_header_button_backgroundColor 77, 86
 lookAndFeel_header_button_color 77, 86
 lookAndFeel_header_primaryNavigation_color 77, 86
 lookAndFeel_header_primaryNavigation_hoverOrFocus 77, 86
 lookAndFeel_header_search_backgroundColor 77, 86
 lookAndFeel_header_search_color 77, 86
 lookAndFeel_header_secondaryNavigation_color 77, 86
 lookAndFeel_header_secondaryNavigation_hoverOrFocus 77, 86
 lookAndFeel_headings 77, 86
 lookAndFeel_links 77, 86
 lookAndFeel_menus_color 77, 86
 lookAndFeel_menus_hoverOrFocus 77, 86
 LookAndFeelSettings 66

- M -

maximum-length-identifiers 2
max-odata-filters 2
max-url-length-accepted 2
max-url-length-desired 2
Members by Group Name 55
messages_args 66
messages_key 66
metadata-cache-max-age-sec 2

- N -

name 18, 65, 77, 86
name_args 66
name_key 66
Native Platform Scalar Requests 106
NATIVEPLATFORMSCALARREQUESTS 106
npt 106
number 18

- O -

oauth-unauthorized-max-tries 2
oauth-unauthorized-sleep-initial-ms 2
oauth-unauthorized-sleep-max-ms 2
oauth-unauthorized-sleep-multiplicator 2
ORIG_SYSTEM_GROUP 106
ORIG_SYSTEM_REFERENCE 106
Original System Group 106
Original System Reference 106

- P -

partition-slot-based-rate-limit-length-ms 2
partition-slot-based-rate-limit-slots 2
Payload 106
PAYLOAD_TEXT 106
percentageComplete 66
personalSpace_homepage_body_anonymous_export_view_representation 46, 55, 96, 163
personalSpace_homepage_body_anonymous_export_view_value 46, 55, 96, 163
personalSpace_homepage_body_atlas_doc_format_representation 46, 55, 96, 163
personalSpace_homepage_body_atlas_doc_format_lue 46, 55, 96, 163
personalSpace_homepage_body_editor_representation 46, 55, 96, 163

personalSpace_homepage_body_editor_value 46, 55, 96, 163
personalSpace_homepage_body_editor2_representation 46, 55, 96, 163
personalSpace_homepage_body_editor2_value 46, 55, 96, 163
personalSpace_homepage_body_export_view_representation 46, 55, 96, 163
personalSpace_homepage_body_export_view_value 46, 55, 96, 163
personalSpace_homepage_body_storage_representation 46, 55, 96, 163
personalSpace_homepage_body_storage_value 46, 55, 96, 163
personalSpace_homepage_body_styled_view_representation 46, 55, 96, 163
personalSpace_homepage_body_styled_view_value 46, 55, 96, 163
personalSpace_homepage_body_view_representation 46, 55, 96, 163
personalSpace_homepage_body_view_value 46, 55, 96, 163
personalSpace_homepage_history_contributors 46, 55, 96, 163
personalSpace_homepage_history_createdBy_accountId 46, 55, 96, 163
personalSpace_homepage_history_createdBy_accountType 46, 55, 96, 163
personalSpace_homepage_history_createdBy_active 46, 55, 96, 163
personalSpace_homepage_history_createdBy_displayName 46, 55, 96, 163
personalSpace_homepage_history_createdBy_emailAddress 46, 55, 96, 163
personalSpace_homepage_history_createdBy_key 46, 55, 96, 163
personalSpace_homepage_history_createdBy_locale 46, 55, 96, 163
personalSpace_homepage_history_createdBy_name 46, 55, 96, 163
personalSpace_homepage_history_createdBy_timeZone 46, 55, 96, 163
personalSpace_homepage_history_createdDate 46, 55, 96, 163
personalSpace_homepage_history_lastUpdated_by_accountId 46, 55, 96, 163
personalSpace_homepage_history_lastUpdated_by_accountType 46, 55, 96, 163
personalSpace_homepage_history_lastUpdated_by_active 46, 55, 96, 163
personalSpace_homepage_history_lastUpdated_by_displayName 46, 55, 96, 163
personalSpace_homepage_history_lastUpdated_by_emailAddress 46, 55, 96, 163

personalSpace_homepage_history_lastUpdated_by_personalSpace_homepage_history_nextVersion_when
 ey 46, 55, 96, 163 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_by_personalSpace_homepage_history_previousVersion_b
 cale 46, 55, 96, 163 y_accountId 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_by_personalSpace_homepage_history_previousVersion_b
 ame 46, 55, 96, 163 y_accountType 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_by_personalSpace_homepage_history_previousVersion_b
 meZone 46, 55, 96, 163 y_active 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_by_personalSpace_homepage_history_previousVersion_b
 borators 46, 55, 96, 163 y_displayName 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_friend_personalSpace_homepage_history_previousVersion_b
 lyWhen 46, 55, 96, 163 y_emailAddress 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_link_personalSpace_homepage_history_previousVersion_b
 46, 55, 96, 163 y_key 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_message_personalSpace_homepage_history_previousVersion_b
 age 46, 55, 96, 163 y_locale 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_min_personalSpace_homepage_history_previousVersion_b
 Edit 46, 55, 96, 163 y_name 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_number_personalSpace_homepage_history_previousVersion_b
 er 46, 55, 96, 163 y_timeZone 46, 55, 96, 163
 personalSpace_homepage_history_lastUpdated_whole_personalSpace_homepage_history_previousVersion_c
 46, 55, 96, 163 ollaborators 46, 55, 96, 163
 personalSpace_homepage_history_latest 46, 55, personalSpace_homepage_history_previousVersion_friend
 96, 163 endyWhen 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_history_previousVersion_li
 ccountId 46, 55, 96, 163 nks 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_history_previousVersion_ccountType
 46, 55, 96, 163 message 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_history_previousVersion_active
 46, 55, 96, 163 minorEdit 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_history_previousVersion_n
 splayName 46, 55, 96, 163 umber 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_history_previousVersion_w
 mailAddress 46, 55, 96, 163 hen 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_id 46, 55, 96, 163
 ey 46, 55, 96, 163 personalSpace_homepage_key 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_status 46, 55, 96, 163
 cale 46, 55, 96, 163 personalSpace_homepage_title 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_by_personalSpace_homepage_type 46, 55, 96, 163
 ame 46, 55, 96, 163 personalSpace_homepage_version_by_accountId
 personalSpace_homepage_history_nextVersion_by_meZone 46, 55, 96, 163
 personalSpace_homepage_version_by_accountType
 personalSpace_homepage_history_nextVersion_collaborators 46, 55, 96, 163
 personalSpace_homepage_version_by_active 46, 55, 96, 163
 personalSpace_homepage_history_nextVersion_friend 46, 55, 96, 163
 personalSpace_homepage_version_by_displayName
 personalSpace_homepage_history_nextVersion_links 46, 55, 96, 163
 46, 55, 96, 163 personalSpace_homepage_version_by_emailAddress
 personalSpace_homepage_history_nextVersion_message 46, 55, 96, 163
 age 46, 55, 96, 163 personalSpace_homepage_version_by_key 46, 55,
 personalSpace_homepage_history_nextVersion_min 46, 55, 96, 163
 Edit 46, 55, 96, 163 personalSpace_homepage_version_by_locale 46,
 personalSpace_homepage_history_nextVersion_number 46, 55, 96, 163

personalSpace_homepage_version_by_name 46, personalSpace_lookAndFeel_content_header_backgroundImage 46, 55, 96, 163
 personalSpace_homepage_version_by_timeZone 46, 55, 96, 163
 personalSpace_homepage_version_collaborators 46, 55, 96, 163
 personalSpace_homepage_version_friendlyWhen 46, 55, 96, 163
 personalSpace_homepage_version_links 46, 55, 96, 163
 personalSpace_homepage_version_message 46, 55, 96, 163
 personalSpace_homepage_version_minorEdit 46, 55, 96, 163
 personalSpace_homepage_version_number 46, 55, 96, 163
 personalSpace_homepage_version_when 46, 55, 96, 163
 personalSpace_icon_height 46, 55, 96, 163
 personalSpace_icon_isDefault 46, 55, 96, 163
 personalSpace_icon_path 46, 55, 96, 163
 personalSpace_icon_width 46, 55, 96, 163
 personalSpace_id 46, 55, 96, 163
 personalSpace_key 46, 55, 96, 163
 personalSpace_lookAndFeel_bordersAndDividers 46, 55, 96, 163
 personalSpace_lookAndFeel_content_body_backgroundImage 46, 55, 96, 163
 personalSpace_lookAndFeel_content_body_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_content_body_backgroundSize 46, 55, 96, 163
 personalSpace_lookAndFeel_content_body_borderRadius 46, 55, 96, 163
 personalSpace_lookAndFeel_content_body_padding 46, 55, 96, 163
 personalSpace_lookAndFeel_content_container_background 46, 55, 96, 163
 personalSpace_lookAndFeel_content_container_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_content_container_backgroundImage 46, 55, 96, 163
 personalSpace_lookAndFeel_content_container_backgroundSize 46, 55, 96, 163
 personalSpace_lookAndFeel_content_container_borderRadius 46, 55, 96, 163
 personalSpace_lookAndFeel_content_container_padding 46, 55, 96, 163
 personalSpace_lookAndFeel_content_header_background 46, 55, 96, 163
 personalSpace_lookAndFeel_content_header_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_content_header_headerBackgroundImage 46, 55, 96, 163
 personalSpace_lookAndFeel_content_header_headerBackgroundSize 46, 55, 96, 163
 personalSpace_lookAndFeel_content_header_headerBorderRadius 46, 55, 96, 163
 personalSpace_lookAndFeel_content_header_headerPadding 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_background 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_backgroundSize 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_gutterBottom 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_gutterLeft 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_gutterRight 46, 55, 96, 163
 personalSpace_lookAndFeel_content_screen_gutterTop 46, 55, 96, 163
 personalSpace_lookAndFeel_header_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_header_button_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_header_button_color 46, 55, 96, 163
 personalSpace_lookAndFeel_header_primaryNavigation_color 46, 55, 96, 163
 personalSpace_lookAndFeel_header_primaryNavigation_hoverOrFocus 46, 55, 96, 163
 personalSpace_lookAndFeel_header_search_backgroundColor 46, 55, 96, 163
 personalSpace_lookAndFeel_header_search_color 46, 55, 96, 163
 personalSpace_lookAndFeel_header_secondaryNavigation_color 46, 55, 96, 163
 personalSpace_lookAndFeel_header_secondaryNavigation_hoverOrFocus 46, 55, 96, 163
 personalSpace_lookAndFeel_headings 46, 55, 96, 163
 personalSpace_lookAndFeel_links 46, 55, 96, 163
 personalSpace_lookAndFeel_menus_color 46, 55, 96, 163
 personalSpace_lookAndFeel_menus_hoverOrFocus 46, 55, 96, 163
 personalSpace_name 46, 55, 96, 163
 personalSpace_settings_routeOverrideEnabled 46, 55, 96, 163
 personalSpace_status 46, 55, 96, 163
 personalSpace_type 46, 55, 96, 163

pre-request-delay-ms 2
 profilePicture_height 15, 46, 55, 96, 163
 profilePicture_isDefault 15, 46, 55, 96, 163
 profilePicture_path 15, 46, 55, 96, 163
 profilePicture_width 15, 46, 55, 96, 163
 publicName 46, 55, 96, 163

- R -

referencingBlueprint 18
 remoteAddress 16
 requested-page-size 2
 requests-parallel-max 2
 Response Cache Maximum Age (sec) 106
 Result BLOB 106
 Result Text 106
 RESULT_BLOB 106
 RESULT_DATE_TIME_UTC 106
 RESULT_NUMBER 106
 RESULT_TEXT 106
 resultGlobalContainer_displayUrl 70
 resultGlobalContainer_title 70
 resultParentContainer_displayUrl 70
 resultParentContainer_title 70
 Run without Actions 106

- S -

Save HTTP Disk Cache 106
 Save HTTP Memory Cache 106
 sce_homepage_body_anonymous_export_view_representation 108, 121, 135, 149
 sce_homepage_body_anonymous_export_view_value 108, 121, 135, 149
 sce_homepage_body_atlas_doc_format_representation 108, 121, 135, 149
 n 108, 121, 135, 149
 sce_homepage_body_atlas_doc_format_value 108, 108, 121, 135, 149
 121, 135, 149
 sce_homepage_body_editor_representation 108, s 108, 121, 135, 149
 121, 135, 149
 sce_homepage_body_editor_value 108, 121, 135, 121, 135, 149
 149
 sce_homepage_body_editor2_representation 108, 108, 121, 135, 149
 121, 135, 149
 sce_homepage_body_editor2_value 108, 121, 135, 121, 135, 149
 149
 sce_homepage_body_export_view_representation 108, 121, 135, 149
 108, 121, 135, 149
 sce_homepage_body_export_view_value 108, 121, 135, 149
 135, 149
 sce_homepage_body_storage_representation 108, 108, 121, 135, 149
 121, 135, 149

sce_homepage_body_storage_value 108, 121, 135, 149
 sce_homepage_body_styled_view_representation 108, 121, 135, 149
 sce_homepage_body_styled_view_value 108, 121, 135, 149
 sce_homepage_body_view_representation 108, 121, 135, 149
 sce_homepage_body_view_value 108, 121, 135, 149
 sce_homepage_history_contributors 108, 121, 135, 149
 sce_homepage_history_createdBy_accountId 108, 121, 135, 149
 sce_homepage_history_createdBy_accountType 108, 121, 135, 149
 sce_homepage_history_createdBy_active 108, 121, 135, 149
 sce_homepage_history_createdBy_displayName 108, 121, 135, 149
 sce_homepage_history_createdBy_emailAddress 108, 121, 135, 149
 sce_homepage_history_createdBy_key 108, 121, 135, 149
 sce_homepage_history_createdBy_locale 108, 121, 135, 149
 sce_homepage_history_createdBy_name 108, 121, 135, 149
 sce_homepage_history_createdBy_timeZone 108, 121, 135, 149
 sce_homepage_history_createdDate 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_accountId 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_accountType 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_active 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_displayName 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_emailAddress 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_key 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_locale 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_name 108, 121, 135, 149
 sce_homepage_history_lastUpdated_by_timeZone 108, 121, 135, 149
 sce_homepage_history_lastUpdated_collaborators 108, 121, 135, 149
 sce_homepage_history_lastUpdated_friendlyWhen 108, 121, 135, 149

sce_homepage_history_lastUpdated_links 108, sce_homepage_history_previousVersion_by_locale
121, 135, 149 108, 121, 135, 149
sce_homepage_history_lastUpdated_message 108, sce_homepage_history_previousVersion_by_name
121, 135, 149 108, 121, 135, 149
sce_homepage_history_lastUpdated_minorEdit 108, sce_homepage_history_previousVersion_by_timeZone
108, 121, 135, 149 108, 121, 135, 149
sce_homepage_history_lastUpdated_number 108, sce_homepage_history_previousVersion_collaborators
121, 135, 149 108, 121, 135, 149
sce_homepage_history_lastUpdated_when 108, sce_homepage_history_previousVersion_friendlyWhen
121, 135, 149 108, 121, 135, 149
sce_homepage_history_latest 108, 121, 135, 149, sce_homepage_history_previousVersion_links 108,
sce_homepage_history_nextVersion_by_accountId 121, 135, 149
108, 121, 135, 149 sce_homepage_history_previousVersion_message
sce_homepage_history_nextVersion_by_accountType 108, 121, 135, 149
108, 121, 135, 149 sce_homepage_history_previousVersion_minorEdit
sce_homepage_history_nextVersion_by_active 108, 121, 135, 149
121, 135, 149 sce_homepage_history_previousVersion_number
sce_homepage_history_nextVersion_by_displayName 108, 121, 135, 149
108, 121, 135, 149 sce_homepage_history_previousVersion_when 108,
sce_homepage_history_nextVersion_by_emailAddress 121, 135, 149
s 108, 121, 135, 149 sce_homepage_id 108, 121, 135, 149
sce_homepage_history_nextVersion_by_key 108, sce_homepage_key 108, 121, 135, 149
121, 135, 149 sce_homepage_status 108, 121, 135, 149
sce_homepage_history_nextVersion_by_locale 108, sce_homepage_title 108, 121, 135, 149
121, 135, 149 sce_homepage_type 108, 121, 135, 149
sce_homepage_history_nextVersion_by_name 108, sce_homepage_version_by_accountId 108, 121,
121, 135, 149 135, 149
sce_homepage_history_nextVersion_by_timeZone 108, sce_homepage_version_by_accountType 108, 121,
108, 121, 135, 149 135, 149
sce_homepage_history_nextVersion_collaborators 108, sce_homepage_version_by_active 108, 121, 135,
108, 121, 135, 149 149
sce_homepage_history_nextVersion_friendlyWhen 108, sce_homepage_version_by_displayName 108, 121,
108, 121, 135, 149 135, 149
sce_homepage_history_nextVersion_links 108, sce_homepage_version_by_emailAddress 108,
121, 135, 149 121, 135, 149
sce_homepage_history_nextVersion_message 108, sce_homepage_version_by_key 108, 121, 135, 149
121, 135, 149 sce_homepage_version_by_locale 108, 121, 135,
sce_homepage_history_nextVersion_minorEdit 108, sce_homepage_version_by_name 108, 121, 135,
108, 121, 135, 149 149
sce_homepage_history_nextVersion_number 108, sce_homepage_version_by_timeZone 108, 121,
121, 135, 149 135, 149
sce_homepage_history_nextVersion_when 108, sce_homepage_version_collaborators 108, 121,
121, 135, 149 135, 149
sce_homepage_history_previousVersion_by_accountId 108, sce_homepage_version_friendlyWhen 108, 121,
108, 121, 135, 149 135, 149
sce_homepage_history_previousVersion_by_accountType 108, sce_homepage_version_links 108, 121, 135, 149
sce_homepage_history_previousVersion_by_active 108, sce_homepage_version_message 108, 121, 135,
108, 121, 135, 149 149
sce_homepage_history_previousVersion_by_displayName 108, sce_homepage_version_minorEdit 108, 121, 135,
ame 108, 121, 135, 149 149
sce_homepage_history_previousVersion_by_emailAddress 108, sce_homepage_version_number 108, 121, 135, 149
ress 108, 121, 135, 149 sce_homepage_version_when 108, 121, 135, 149
sce_homepage_history_previousVersion_by_key 108, sce_icon_height 108, 121, 135, 149

sce_icon_isDefault 108, 121, 135, 149
 sce_icon_path 108, 121, 135, 149
 sce_icon_width 108, 121, 135, 149
 sce_id 108, 121, 135, 149
 sce_key 108, 121, 135, 149
 sce_lookAndFeel_bordersAndDividers 108, 121, 135, 149
 sce_lookAndFeel_content_body_background 108, 121, 135, 149
 sce_lookAndFeel_content_body_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_content_body_backgroundImage 108, 121, 135, 149
 sce_lookAndFeel_content_body_backgroundSize 108, 121, 135, 149
 sce_lookAndFeel_content_body_borderRadius 108, 121, 135, 149
 sce_lookAndFeel_content_body_padding 108, 121, 135, 149
 sce_lookAndFeel_content_container_background 108, 121, 135, 149
 sce_lookAndFeel_content_container_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_content_container_backgroundImage 108, 121, 135, 149
 sce_lookAndFeel_content_container_backgroundSize 108, 121, 135, 149
 sce_lookAndFeel_content_container_borderRadius 108, 121, 135, 149
 sce_lookAndFeel_content_container_padding 108, 121, 135, 149
 sce_lookAndFeel_content_header_background 108, 121, 135, 149
 sce_lookAndFeel_content_header_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_content_header_borderRadius 108, 121, 135, 149
 sce_lookAndFeel_content_header_padding 108, 121, 135, 149
 sce_lookAndFeel_content_screen_background 108, 121, 135, 149
 sce_lookAndFeel_content_screen_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_content_screen_backgroundImage 108, 121, 135, 149
 sce_lookAndFeel_content_screen_backgroundSize 108, 121, 135, 149
 sce_lookAndFeel_content_screen_gutterBottom 108, 121, 135, 149
 sce_lookAndFeel_content_screen_gutterLeft 108, 121, 135, 149
 sce_lookAndFeel_content_screen_gutterRight 108, 121, 135, 149
 sce_lookAndFeel_content_screen_gutterTop 108, 121, 135, 149
 sce_lookAndFeel_header_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_header_button_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_header_button_color 108, 121, 135, 149
 sce_lookAndFeel_header_primaryNavigation_color 108, 121, 135, 149
 sce_lookAndFeel_header_primaryNavigation_hoverOrFocus 108, 121, 135, 149
 sce_lookAndFeel_header_search_backgroundColor 108, 121, 135, 149
 sce_lookAndFeel_header_search_color 108, 121, 135, 149
 sce_lookAndFeel_header_secondaryNavigation_color 108, 121, 135, 149
 sce_lookAndFeel_header_secondaryNavigation_hoverOrFocus 108, 121, 135, 149
 sce_lookAndFeel_headings 108, 121, 135, 149
 sce_lookAndFeel_links 108, 121, 135, 149
 sce_lookAndFeel_menus_color 108, 121, 135, 149
 sce_lookAndFeel_menus_hoverOrFocus 108, 121, 135, 149
 sce_name 108, 121, 135, 149
 sce_settings_routeOverrideEnabled 108, 121, 135, 149
 sce_status 108, 121, 135, 149
 sce_type 108, 121, 135, 149
 SearchCql 70
 searchString 16
 server 2
 settings_routeOverrideEnabled 77, 86
 simulate-http-400-errors 2
 simulate-http-400-errors-percentage 2
 simulate-http-401-errors 2
 simulate-http-401-errors-percentage 2
 simulate-http-403-errors 2
 simulate-http-403-errors-percentage 2
 simulate-http-408-errors 2
 simulate-http-408-errors-percentage 2
 simulate-http-429-errors 2
 simulate-http-429-errors-percentage 2
 simulate-http-500-errors 2
 simulate-http-500-errors-percentage 2
 simulate-http-502-errors 2
 simulate-http-502-errors-percentage 2
 simulate-http-503-errors 2

simulate-http-503-errors-percentage 2
 simulate-http-protocol-errors 2
 simulate-http-protocol-errors-percentage 2
 simulate-http-timeout-errors 2
 simulate-http-timeout-errors-percentage 2
 slot-based-rate-limit-length-ms 2
 slot-based-rate-limit-slots 2
 source_name 16
 source_objectType 16
 Space by Key 77
 SpaceByKey 77
 spaceKey 19, 26, 32, 39, 77
 Spaces 86
 standardize-identifiers 2
 standardize-identifiers-casing 2
 Start Date 106
 startDate 16
 status 19, 26, 32, 39, 77, 86, 108, 121, 135, 149
 Succesful 106
 SUCCESSFUL 66, 106
 summary 16
 sysAdmin 16
 System Information 95
 SystemInformation 95

- T -

templateId 18
 templateType 18
 Timeout (sec) 106
 TIMEOUT_SEC 106
 title 19, 26, 32, 39, 70, 108, 121, 135, 149
 Transaction ID 106
 TRANSACTION_ID 106
 type 15, 19, 26, 32, 39, 46, 55, 65, 77, 86, 96, 108, 121, 135, 149, 163

- U -

units 18
 URL 70, 106
 Use HTTP Disk Cache 106
 Use HTTP Memory Cache 106
 use-batch-insert 2
 use-http-disk-cache-read 2
 use-http-disk-cache-write 2
 use-http-memory-cache-read 2
 use-http-memory-cache-write 2
 User by Account ID 70, 96
 UserByAccountId 96

- V -

version_by_accountId 19, 26, 32, 39, 108, 121, 135, 149
 version_by_accountType 19, 26, 32, 39, 108, 121, 135, 149
 version_by_active 19, 26, 32, 39, 108, 121, 135, 149
 version_by_displayName 19, 26, 32, 39, 108, 121, 135, 149
 version_by_emailAddress 19, 26, 32, 39, 108, 121, 135, 149
 version_by_key 19, 26, 32, 39, 108, 121, 135, 149
 version_by_locale 19, 26, 32, 39, 108, 121, 135, 149
 version_by_name 19, 26, 32, 39, 108, 121, 135, 149
 version_by_timeZone 19, 26, 32, 39, 108, 121, 135, 149
 version_collaborators 19, 26, 32, 39, 108, 121, 135, 149
 version_friendlyWhen 19, 26, 32, 39, 108, 121, 135, 149
 version_links 19, 26, 32, 39, 108, 121, 135, 149
 version_message 19, 26, 32, 39, 108, 121, 135, 149
 version_minorEdit 19, 26, 32, 39, 108, 121, 135, 149
 version_number 19, 26, 32, 39, 108, 121, 135, 149
 version_when 19, 26, 32, 39, 108, 121, 135, 149

