

# Mail Data Model

*for use with Invantive SQL*



# Copyright

(C) Copyright 2004-2023 Invantive Software B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

## Important Safety and Usage Information

**Intended Use and Limitations:** This software, developed by Invantive, is designed to support a variety of business and information technology data processing functions, such as accounting, financial reporting and sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The software should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.
- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weaponry control, military strategy planning, or any other aspects of national defense.
- Aviation: The software is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.
- Healthcare and Medicine Production: This software should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.
- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.
- Transportation and Traffic Control Systems: The software should not be used for the control, operation, or management of transportation systems, including railway signal controls, subway systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.
- Energy Grid and Utility Control Systems: This software is not designed for the control or operation of energy grid systems, including electrical substations, renewable energy control systems, or water utility control systems. The failure of software in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.
- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

**User Responsibility:** Users must ensure that they understand the intended use of the software and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the software for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment.

**Disclaimer of Liability:** Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this software in prohibited or unintended applications.

---

# Contents

<b>1</b>	<b>SQL Driver for Mail API</b>	<b>1</b>
<b>2</b>	<b>SQL Driver Attributes for Mail API</b>	<b>1</b>
<b>3</b>	<b>SMTP: Mail Outgoing Mail Message Queue</b>	<b>5</b>
	<b>Index</b>	<b>8</b>

## 1 SQL Driver for Mail API

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the [user community](#). Invantive Support or other users will try to help you.

Exchange email through SMTP.

The Mail driver covers 1 tables and 41 columns.

### Mail API Clients

Invantive UniversalSQL is available on many user interfaces ("clients" in traditional server-client paradigm). All Invantive UniversalSQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL.

### Specifications

The SQL driver for Mail does not support partitioning.

An introduction into the concepts of Invantive UniversalSQL such as databases, data containers and partitioning can be found in the [Invantive UniversalSQL grammar](#).

The configuration can be changed using various attributes from the database definition, on log on and during use. A full list of configuration options is listed in the [driver attributes](#)<sup>1</sup>.

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On Mail the comparison of two texts is case sensitive by default.

Changes and bug fixes on the Mail SQL driver can be found in the [release notes](#). Get access to the community through the [Mail section](#) of the Invantive forums.

Driver code for use in settings.xml: Mail

Alias: mail

Recommended alias: ml

Updated 28-07-2024 17:47 using Invantive UniversalSQL version 24.1.6-BETA+4856.

## 2 SQL Driver Attributes for Mail API

The SQL driver for Mail has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the API server of Mail or high volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The Mail driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings\*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for Mail can be found in the settings\*.xml file used for the database. The reference manuals contain instructions how to relocate the settings\*.xml files. Settings\*.xml files are typically located in the %USERPROFILE%\invantive folder in most deployment scenarios. Each data container of a database in the connection string can have a `connectionString` element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: `set NAME VALUE`, or for a distributed database: `set NAME@ALIAS VALUE`. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The Mail driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
analysis-enforce-row-uniqueness	Enforce rows to be unique for software analysis. A fingerprint is calculated from the whole row of data when the primary key column is unknown.	Shared	False	✓	✓	✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting.	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting.	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting.	Shared	10000	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from: Unset, Lower, Upper and Mixed.	Shared		✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-execution-profile-disk-path	{res:itgen_pae_invantive_sql_execution_profile_disk_path}	SQL Engine V1	c:\temp\profiles	✓	✓	✓	
invantive-sql-execution-profile-to-disk	{res:itgen_pae_invantive_sql_execution_profile_to_disk}	SQL Engine V1	True	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of call events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register calls from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files when the call raised an error.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files when the call raised no error.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	
mail-body-html	Whether the mail body is HTML.	Mail		✓	✓	✓	
mail-from-email	The default FROM email address.	Mail		✓	✓	✓	
mail-from-name	The default FROM name.	Mail		✓	✓	✓	
mail-priority	Priority of the mail; negative is bulk, 0 is neutral, positive is urgent.	Mail		✓	✓	✓	
mail-reply-to-email	The default REPLY TO email address.	Mail		✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Driver's File	Set from Log On
mail-reply-to-name	The default REPLY TO name.	Mail		✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
partition-slot-based-rate-limit-length-ms	Total length in milliseconds across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit.	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online.	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
slot-based-rate-limit-length-ms	Total length in milliseconds across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit.	Shared		✓		✓	
smtp-enable-ssl	Set whether SSL is enabled for SMTP connections.	Mail	False	✓	✓	✓	
smtp-host-address	The default SMTP host address to use.	Mail		✓	✓	✓	
smtp-host-port-number	The default SMTP host port number to use.	Mail		✓	✓	✓	
smtp-max-parallel	Maximum number of concurrent SMTP requests.	Mail	32	✓	✓	✓	
smtp-minimum-deliver-duration-ms	Minimum deliver duration in milliseconds for the SMTP send plus inserted sleep when SMTP send finished earlier than the minimum. The value is applied per parallel thread.	Mail		✓	✓	✓	
smtp-password	The default SMTP password to authenticate with.	Mail		✓	✓	✓	
smtp-send-timeout-ms	Timeout in milliseconds after which the SMTP send times out.	Mail		✓	✓	✓	
smtp-user-name	The default SMTP user name to authenticate with.	Mail		✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-	Shared	True	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
	specific casing when changing a data model on a case-dependent platform.						
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	

### 3 SMTP: Mail Outgoing Mail Message Queue

Catalog: Mail

Primary Keys: id

Label: Outgoing Mail Message Queue

Retrieve: true

#### Table Columns

The columns of the table SMTP are shown below. Each column has an SQL data type. A new non-null value must be provided for every required column at all times during insert.

Name	Data Type	Label	Required	Documentation
AddressEncoding	string(30)	Address Encoding	<input type="checkbox"/>	Character set for encoding mail addresses.
attachment1Contents	byte[]	Attachment 1 Contents	<input type="checkbox"/>	Binary contents of the first attachment.
attachment1MimeType	string	Attachment 1 MIME Type	<input type="checkbox"/>	MIME type of the first attachment.
attachment1Name	string	Attachment #1 File Name	<input type="checkbox"/>	File name of the first attachment.
attachment2Contents	byte[]	Attachment 2 Contents	<input type="checkbox"/>	Binary contents of the second attachment.
attachment2MimeType	string	Attachment 2 MIME Type	<input type="checkbox"/>	MIME type of the second attachment.
attachment2Name	string	Attachment #2 File Name	<input type="checkbox"/>	File name of the second attachment.
attachment3Contents	byte[]	Attachment 3 Contents	<input type="checkbox"/>	Binary contents of the third attachment.
attachment3MimeType	string	Attachment 3 MIME Type	<input type="checkbox"/>	MIME type of the third attachment.
attachment3Name	string	Attachment #3 File Name	<input type="checkbox"/>	File name of the third attachment.
bccEmail	string	Blank Carbon Copy Recipient Email Addresses	<input type="checkbox"/>	List of Blank Carbon Copy recipients, separated by ','.
body	string	Body Text	<input type="checkbox"/>	Body text of the mail.



Name	Data Type	Label	Required	Documentation
bodyEncoding	string(30)	Body Encoding	<input type="checkbox"/>	Character set for encoding mail body.
ccEmail	string	Carbon Copy Recipient Email Addresses	<input type="checkbox"/>	List of email addresses of the recipients of a copy, separated by ','.
dateEndUtc	datetime	Date End (UTC)	<input type="checkbox"/>	Date end (UTC).
dateStartUtc	datetime	Date Start (UTC)	<input type="checkbox"/>	Date start (UTC).
DispositionNotificationToEmailAddress	string	Disposition Notification to Email Address	<input type="checkbox"/>	Email address in Disposition-Notification-To header.
enableSsl	boolean	SMTP Enable SSL	<input type="checkbox"/>	Whether to use SSL on SMTP transport.
errorMessageCode	string	Error Message Code	<input type="checkbox"/>	Message code of the error.
errorMessageText	string	Error Message Text	<input type="checkbox"/>	Message text of the error.
failOnError	boolean	On Error	<input type="checkbox"/>	Fail on error.
fromEmail	string	From Email Address	<input type="checkbox"/>	FROM email address.
fromName	string	From Name	<input type="checkbox"/>	FROM name.
headers	string	Mail Headers	<input type="checkbox"/>	List of headers, per header separated by ';'. The header name and value are separated by a ':'.
HeadersEncoding	string(30)	Headers Encoding	<input type="checkbox"/>	Character set for encoding headers.
id	int64	Mail ID	<input checked="" type="checkbox"/>	ID.
isBodyHtml	boolean	Body is HTML Text	<input type="checkbox"/>	True when the contents of the body are formatted as HTML, false when formatted as plain text.
minimumDeliveryDurationMsec	int32	Minimum Delivery Duration (ms)	<input type="checkbox"/>	Minimum deliver duration in milliseconds for the SMTP send plus inserted sleep when SMTP send finished earlier than the minimum.
origSystemReference	string	Original System Reference	<input type="checkbox"/>	Original system reference.
priority	int32	Priority	<input type="checkbox"/>	Priority of the mail; negative is bulk, 0 is neutral, positive is urgent.
replyToEmail	string	Reply to Email Address	<input type="checkbox"/>	REPLY TO email address.
replyToName	string	Reply to Name	<input type="checkbox"/>	REPLY TO name.
ReturnReceiptToEmailAddress	string	Return Receipt To Email Address	<input type="checkbox"/>	Email address in Return-Receipt-To header.
smtpHostAddress	string	SMTP Server Host	<input type="checkbox"/>	Host name or IP-address of the SMTP server to send the mail through.
smtpHostPortNumber	int32	SMTP Server Port	<input type="checkbox"/>	Port number of the SMTP server.
smtpPassw ord	string	SMTP Server Passw ord	<input type="checkbox"/>	Passw ord for authentication of the user on the SMTP server.
smtpUserName	string	SMTP Server Log On Code	<input type="checkbox"/>	User name for authentication on the SMTP server.

Name	Data Type	Label	Required	Documentation
subject	string	Subject	<input type="checkbox"/>	Subject of the mail.
subjectEncoding	string(30)	Subject Encoding	<input type="checkbox"/>	Character set for encoding subject.
successful	boolean	Successful	<input type="checkbox"/>	Result of the sending was successful.
toEmail	string	Recipient Email Addresses	<input checked="" type="checkbox"/>	List of email addresses of the recipients, separated by ';'

# Index

## - A -

Address Encoding 5  
 AddressEncoding 5  
 analysis-enforce-row-uniqueness 1  
 Attachment #1 File Name 5  
 Attachment #2 File Name 5  
 Attachment #3 File Name 5  
 Attachment 1 Contents 5  
 Attachment 1 MIME Type 5  
 Attachment 2 Contents 5  
 Attachment 2 MIME Type 5  
 Attachment 3 Contents 5  
 Attachment 3 MIME Type 5  
 attachment1Contents 5  
 attachment1MimeType 5  
 attachment1Name 5  
 attachment2Contents 5  
 attachment2MimeType 5  
 attachment2Name 5  
 attachment3Contents 5  
 attachment3MimeType 5  
 attachment3Name 5

## - B -

bccEmail 5  
 Blank Carbon Copy Recipient Email Addresses  
 body 5  
 Body Encoding 5  
 Body is HTML Text 5  
 Body Text 5  
 bodyEncoding 5  
 bulk-delete-page-size-rows 1  
 bulk-insert-page-size-bytes 1  
 bulk-insert-page-size-rows 1

## - C -

Carbon Copy Recipient Email Addresses 5  
 ccEmail 5

## - D -

Database Driver 1  
 Date End (UTC) 5

Date Start (UTC) 5  
 dateEndUtc 5  
 dateStartUtc 5  
 Disposition Notification to Email Address 5  
 DispositionNotificationToEmailAddress 5

## - E -

enableSsl 5  
 Error Message Code 5  
 Error Message Text 5  
 errorMessageCode 5  
 errorMessageText 5

## - F -

failOnError 5  
 force-case-sensitive-identifiers 1  
 forced-casing-identifiers 1  
 From Email Address 5  
 From Name 5  
 fromEmail 5  
 fromName 5

## - H -

headers 5  
 Headers Encoding 5  
 HeadersEncoding 5

## - I -

invantive-sql-compress-sparse-arrays 1  
 invantive-sql-correct-invalid-date 1  
 invantive-sql-execution-profile-disk-path 1  
 invantive-sql-execution-profile-to-disk 1  
 invantive-sql-forward-filters-to-data-containers 1  
 invantive-sql-share-byte-arrays 1  
 invantive-sql-share-strings 1  
 invantive-sql-shuffle-fetch-results-data-containers 1  
 invantive-use-cache 1  
 isBodyHtml 5

## - L -

log-native-calls-to-disk-max-events 1  
 log-native-calls-to-disk-max-seconds 1  
 log-native-calls-to-disk-on-error 1  
 log-native-calls-to-disk-on-success 1

log-native-calls-to-trace 1

## - M -

Mail 1, 5

Mail Headers 5

mail-body-html 1

mail-from-email 1

mail-from-name 1

mail-priority 1

mail-reply-to-email 1

mail-reply-to-name 1

maximum-length-identifiers 1

max-url-length-accepted 1

max-url-length-desired 1

Minimum Delivery Duration (ms) 5

minimumDeliveryDurationMsec 5

## - O -

On Error 5

Original System Reference 5

origSystemReference 5

Outgoing Mail Message Queue 5

## - P -

partition-slot-based-rate-limit-length-ms 1

partition-slot-based-rate-limit-slots 1

pre-request-delay-ms 1

Priority 5

## - R -

Recipient Email Addresses 5

Reply to Email Address 5

Reply to Name 5

replyToEmail 5

replyToName 5

requested-page-size 1

requests-parallel-max 1

Return Receipt To Email Address 5

ReturnReceiptToEmailAddress 5

## - S -

slot-based-rate-limit-length-ms 1

slot-based-rate-limit-slots 1

SMTP 5

SMTP Enable SSL 5

SMTP Server Host 5

SMTP Server Log On Code 5

SMTP Server Password 5

SMTP Server Port 5

smtp-enable-ssl 1

smtpHostAddress 5

smtp-host-address 1

smtpHostPortNumber 5

smtp-host-port-number 1

smtp-max-parallel 1

smtp-minimum-deliver-duration-ms 1

smtpPassword 5

smtp-password 1

smtp-send-timeout-ms 1

smtpUserName 5

smtp-user-name 1

standardize-identifiers 1

standardize-identifiers-casing 1

Subject 5

Subject Encoding 5

subjectEncoding 5

Successful 5

successful 5

## - T -

toEmail 5



# *invantive* the **SQL** company

Invantive B.V.  
Biesteweg 11  
3849 RD Hierden  
the Netherlands

Tel: +31 88 00 26 500  
Fax: +31 84 22 58 178  
info@invantive.com  
invantive.com

IBAN NL25 BUNQ 2098 2586 07  
Chamber of Industry and Commerce  
13031406  
VAT NL812602377B01  
RSIN 8122602377  
Managing Director: Guido Leenders  
Registered office: Roermond