

RSS Data Model

for use with Invantive SQL



23.0

Copyright

(C) Copyright 2004-2023 Invantive Softw are B.V., the Netherlands. All rights reserved.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

Despite all the care taken in the compilation of this text, neither the author nor the publisher can accept liability for any damage, which might result from any error, which might appear in this publication.

This manual is a reference guide intended to clarify usage. If data in the sample images match data in your system, the similarity is coincidental.

Important Safety and Usage Information Intended Use and Limitations: This software, developed by Invantive, is designed to support a variety of business and

information technology data processing functions, such as accounting, financial reporting an sales reporting. It is important to note that this software is not designed, tested, or approved for use in environments where malfunction or failure could lead to life-threatening situations or severe physical or environmental damage. This includes, but is not limited to:

- Nuclear facilities: The softw are should not be used for operations or functions related to the control, maintenance, or operation of nuclear facilities.

- Defense and Military Applications: This software is not suitable for use in defense-related applications, including but not limited to weaponry control, military strategy planning, or any other aspects of national defense.

- Aviation: The softw are is not intended for use in the operation, navigation, or communication systems of any aircraft or air traffic control environments.

- Healthcare and Medicine Production: This softw are should not be utilized for medical device operation, patient data analysis for critical health decisions, pharmaceutical production, or medical research where its failure or malfunction could impact patient health.

- Chemical and Hazardous Material Handling: This software is not intended for the management, control, or operational aspects of chemical plants or hazardous material handling facilities. Any malfunction in software used in these settings could result in dangerous chemical spills, explosions, or environmental disasters.

- Transportation and Traffic Control Systems: The softw are should not be used for the control, operation, or management of transportation systems, including railw ay signal controls, subw ay systems, or traffic light management. Malfunctions in such critical systems could lead to severe accidents and endanger public safety.

- Energy Grid and Utility Control Systems: This softw are is not designed for the control or operation of energy grid systems, including electrical substations, renew able energy control systems, or water utility control systems. The failure of softw are in these areas could lead to significant power outages, water supply disruptions, or other public utility failures, potentially endangering communities and causing extensive damage.

- Other High-Risk Environments: Any other critical infrastructure and environments where a failure of the software could result in significant harm to individuals or the environment.

User Responsibility: Users must ensure that they understand the intended use of the softw are and refrain from deploying it in any setting that falls outside of its designed purpose. It is the responsibility of the user to assess the suitability of the softw are for their intended application, especially in any scenarios that might pose a risk to life, health, or the environment. Disclaimer of Liability: Invantive disclaims any responsibility for damage, injury, or legal consequences resulting from the use or misuse of this softw are in prohibited or unintended applications.

Contents

1	SQL Driver for RSS 2.0	1
2	SQL Driver Attributes for RSS 2.0	2
3	Channelltems	5
4	Channels	7
5	ReallySimpleSyndications	9
	Index	10

RSS Data Model

1

1 SQL Driver for RSS 2.0

Invantive SQL is the fastest, easiest and most reliable way to exchange data with RSS 2.0.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the <u>user community</u>. Other users or Invantive Support will try to help you to our best.

RSS version 2.0. RSS is a file format to communicate news messages and other streaming data.

The RSS 2.0 driver covers 3 tables and 70 columns.

RSS 2.0 Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigma). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from RSS 2.0 into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using Invantive Data Replicator. Invantive Data Replicator automatically creates and maintains RSS 2.0 datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an RSS 2.0 ADO.net provider.

Specifications

The SQL driver for RSS 2.0 does not support partitioning. Define one data container in a database for each company in RSS 2.0 to enable parallel access for data from multiple companies.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the <u>Invantive SQL grammar</u>.

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the <u>driver attributes</u> 2.

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On RSS 2.0 the comparison of two texts is case sensitive by default.

Changes and bug fixes on the RSS 2.0 SQL driver can be found in the <u>release notes</u>. Get access to the RSS 2.0 community through the <u>RSS 2.0 section</u> of the Invantive forums.

Driver code for use in settings.xml: Rss20

Alias: rss

Recommended alias: rss

More technical documentation as provided by the supplier of RSS 2.0 on the native connection used can be found at <u>http://www.rssboard.org/rss-specification</u>.

Updated: 15-06-2022 20:41 using Invantive SQL version 22.0.232-PROD+3445.

2 SQL Driver Attributes for RSS 2.0

The SQL driver for RSS 2.0 has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the RSS 2.0 server or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The RSS 2.0 driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for RSS 2.0 can be found in the settings*.xml file used for the database. Settings*.xml files are typically located in the <code>%USERPROFILE%\invantive</code> folder in most deployment scenarios. The reference manuals contain instructions how to relocate the settings*.xml files. Each data container of a database in the connection string can have a <code>connectionString</code> element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: set NAME VALUE, or for a distributed database: set NAME@ALIAS VALUE. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

Code	Description	Origin	Default Value	Set from Conne ction String	Set from Set SQL- Statem ent	Set from Driver s File	Set from Log On
analysis-enforce- row-uniqueness	Use for analysis only! Enforce row s to be unique.	Shared	False	\checkmark	\checkmark	\checkmark	

The RSS 2.0 driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Conne ction String	Set from Set SQL- Statem ent	Set from Driver s File	Set from Log On
bulk-delete-page- size-row s	Number of rows to delete per batch when bulk deleting	Shared	10000	\checkmark	\checkmark	\checkmark	
bulk-insert-page- size-bytes	Approximate maximum size in bytes of batch w hen bulk inserting	Shared	1000000	\checkmark	\checkmark	\checkmark	
bulk-insert-page- size-row s	Number of rows to insert per batch when bulk inserting	Shared	10000	\checkmark	\checkmark	\checkmark	
force-case- sensitive-identifiers	Consider identifiers as case- sensitive independent of the platform capabilities.		False	\checkmark	\checkmark	\checkmark	
forced-casing- identifiers	Forced casing of identifiers. Choose from Unset, Low er, Upper and Mixed.	Shared		\checkmark	\checkmark	\checkmark	
invantive-sql- compress-sparse- arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	\checkmark	~	\checkmark	
invantive-sql- correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01- 1753. When nullable, they are removed. Otherw ise they are replaced by 01-01-1753.	SQL Engine V1	False	\checkmark	~	\checkmark	
invantive-sql- forw ard-filters-to- data-containers	Whether to forw ard filters to data containers.	SQL Engine V1	True	\checkmark	\checkmark	\checkmark	
invantive-sql-share- byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	\checkmark	\checkmark	\checkmark	
invantive-sql-share- strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	\checkmark	~	\checkmark	
invantive-sql- shuffle-fetch- results-data- containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	~	√	\checkmark	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	\checkmark	\checkmark	\checkmark	
log-native-calls-to- disk-max-events	Maximum number of events to register from last activation.	Shared		\checkmark	\checkmark	\checkmark	
log-native-calls-to- disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		\checkmark	\checkmark	\checkmark	
log-native-calls-to- disk-on-error	Registers native calls to data container backend as disk files w hen an error occurred.	Shared	False	\checkmark	\checkmark	\checkmark	
log-native-calls-to- disk-on-success	Registers native calls to data container backend as disk files w hen successful.	Shared	False	~	~	~	
log-native-calls-to- trace	Log native calls to data container backend on the trace.	Shared	False	\checkmark	~	~	
maximum-length- identifiers	Non-default maximum length in characters of identifier names.	Shared		\checkmark	\checkmark	\checkmark	

SQL Driver Attributes for RSS 2.0

Code	Description	Origin	Default Value	Set from Conne ction String	Set from Set SQL- Statem ent	Set from Driver s File	Set from Log On
max-url-length- accepted	The maximum accepted URL length before raising an error.	Shared	8000	\checkmark	\checkmark	\checkmark	
max-url-length- desired	The maximum desired URL length.	Shared	8000	\checkmark	\checkmark	\checkmark	
minimum-length-text	Extend all text columns to this length to allow processing of XML that uses longer text values than the XSD specifies.	XML		√			\checkmark
partition-slot-based- rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	\checkmark		\checkmark	
partition-slot-based- rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		\checkmark		\checkmark	
pre-request-delay- ms	Pre-request delay in milliseconds per request.	Shared	0	\checkmark	\checkmark	\checkmark	
requested-page-size	Preferred number of row s to exchange per round trip; only effective on limited platforms such as AFAS Online	Shared		√	\checkmark	\checkmark	
requests-parallel- max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	\checkmark	\checkmark	\checkmark	
result-set-memory- cache	Action: provide 'empty' to empty.	XML			\checkmark		
slot-based-rate-limit- length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	\checkmark		\checkmark	
slot-based-rate-limit- slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		\checkmark		\checkmark	
standardize- identifiers	Rew rite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	\checkmark	\checkmark	\checkmark	
standardize- identifiers-casing	Rew rite all identifiers to the recommended standard platform- specific casing w hen changing a data model on a case-dependent platform.	Shared	True	√	~	\checkmark	
use-metadata- memory-cache	Whether to use the metadata in memory calculated previously Has only practical use during development on a XML provider.	XML	True	1	√	\checkmark	
use-result-memory- cache	Whether to use result sets cached in memory from previous queries that can answ er the current query.	XML	False	~	~	~	
xml-directories	{res:itgen_provider_attribute_xml_dir ectories_description}			~	~	\checkmark	\checkmark
xml-extension	{res:itgen_provider_attribute_xml_ex tension_description}		*.rss	\checkmark	\checkmark	\checkmark	\checkmark

5	RSS Data	Model

Code	Description	Origin	Default Value	Set from Conne ction String	Set from Set SQL- Statem ent	Set from Driver s File	Set from Log On
xml-namespaces	Comma-separated list of namespace prefixes and their URI			\checkmark	\checkmark	\checkmark	

3 Channelltems

Catalog: RSS

The data in this table is partitioned per value of the column.

Retrieve: true

Topic: rss

Base XPath: /rss/channel

XPath:/item

Table Columns

The columns of the table ChannelItems are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
CATEGORY_DOMAIN_ATTR	string			
CATEGORY	string			
CHANNEL_CATEGORY_DOMAIN_ ATTR	string			
CHANNEL_CATEGORY	string			
CHANNEL_CLOUD	string			Allow s processes to register w ith a cloud to be notified of updates to the channel, implementing a lightw eight publish-subscribe protocol for RSS feeds.
CHANNEL_COPY RIGHT	string	Channel Copyright		Copyright notice for content in the channel.
CHANNEL_DESCRIPTION	string	Channel Description		Phrase or sentence describing the channel.
CHANNEL_DOCS	string			A URL that points to the documentation for the format used in the RSS file. It's probably a pointer to this page. It's for people w ho might stumble across an RSS file on a Web server 25 years from now and w onder w hat it is.
CHANNEL_GENERATOR	string	Channel Generator		A string indicating the program used to generate the channel.

Name	Data Type	Label	Required	Documentation
CHANNEL_IMAGE_DESCRIPTION	string	Image Description		Text that is included in the TITLE attribute of the link formed around the image in the HTML rendering.
CHANNEL_IMAGE_HEIGHT	int64			The height of the image in pixels.
CHANNEL_IMAGE_LINK	string	Image Hyperlink		The URL of the site, w hen the channel is rendered, the image is a link to the site. (Note, in practice the image <title> and k> should have the same value as the channel's <title> and <link/>.</title></title>
CHANNEL_IMAGE_TITLE	string	Image Title		Describes the image, it's used in the ALT attribute of the HTML tag w hen the channel is rendered in HTML.
CHANNEL_IMAGE_URL	string			The URL of the image file.
CHANNEL_IMAGE_WIDTH	int64			The width of the image in pixels.
CHANNEL_LANGUAGE	string(17)	Channel Language		The language the channel is w ritten in. This allow s aggregators to group all Italian language sites, for example, on a single page. A list of allow able values for this element, as provided by Netscape, is here. You may also use values defined by the W3C.
CHANNEL_LASTBUILDDATE	string			A date-time displayed in RFC-822 format.
CHANNEL_LINK	string	Channel Hyperlink		The URL to the HTML w ebsite corresponding to the channel.
CHANNEL_PUBDATE	string			A date-time displayed in RFC-822 format.
CHANNEL_SKIPDAYS	int64			A hint for aggregators telling them w hich days they can skip.
CHANNEL_SKIPHOURS	int64			A hint for aggregators telling them w hich hours they can skip.
CHANNEL_TEXTINPUT_DESCRIPTI ON	string			Explains the text input area.
CHANNEL_TEXTINPUT_LINK	string			The URL of the CGI script that processes text input requests.
CHANNEL_TEXTINPUT_NAME	string			The name of the text object in the text input area.
CHANNEL_TEXTINPUT_TITLE	string			The label of the Submit button in the text input area.
CHANNEL_TITLE	string	Channel Title		The name of the channel. It's how people refer to your service. If you have an HTML w ebsite that contains the same information as your RSS file, the title of your channel should be the same as the title of your w ebsite.

Name	Data Type	Label	Required	Documentation
CHANNEL_TTL	int64			ttl stands for time to live. It's a number of minutes that indicates how long a channel can be cached before refreshing from the source.
COMMENTS	string			URL of a page for comments relating to the item.
DESCRIPTION	string	Description		The item synopsis.
ENCLOSURE_LENGTH_ATTR	int64			Size in bytes
ENCLOSURE_TYPE_ATTR	string			MIME media-type of the enclosure
ENCLOSURE_URL_ATTR	string			URL where the enclosure is located
ENCLOSURE	string			
GUID_ISPERMALINK_ATTR	boolean			
GUID	string			
INTERFACE_URL	string(4000)	Interface URL		
LINK	string	Hyperlink		The URL of the item.
PUBDATE	string			A date-time displayed in RFC-822 format.
SOURCE_URL_ATTR	string			
SOURCE	string			
TITLE	string	Title		The title of the item.

4 Channels

Catalog: RSS

The data in this table is partitioned per value of the column.

Retrieve: true

Topic: rss

Base XPath: /rss

XPath: /channel

Table Columns

The columns of the table Channels are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
CATEGORY_DOMAIN_ATTR	string			
CATEGORY	string			
CLOUD	string			Allow s processes to register with a cloud to be notified of updates to the channel, implementing a lightw eight publish-subscribe protocol for RSS feeds.

Name	Data Type	Label	Required	Documentation
COPYRIGHT	string	Copyright		Copyright notice for content in the channel.
DESCRIPTION	string	Description		Phrase or sentence describing the channel.
DOCS	string			A URL that points to the documentation for the format used in the RSS file. It's probably a pointer to this page. It's for people w ho might stumble across an RSS file on a Web server 25 years from now and w onder w hat it is.
GENERATOR	string	Generator		A string indicating the program used to generate the channel.
IMAGE_DESCRIPTION	string	Image Description		Text that is included in the TITLE attribute of the link formed around the image in the HTML rendering.
IMAGE_HEIGHT	int64			The height of the image in pixels.
IMAGE_LINK	string	Image Hyperlink		The URL of the site, when the channel is rendered, the image is a link to the site. (Note, in practice the image <title> and <link/> should have the same value as the channel's <title> and <link/>.</title></title>
IMAGE_TITLE	string	Image Title		Describes the image, it's used in the ALT attribute of the HTML tag w hen the channel is rendered in HTML.
IMAGE_URL	string			The URL of the image file.
IMAGE_WIDTH	int64			The width of the image in pixels.
INTERFACE_URL	string(4000)	Interface URL		
LANGUAGE	string(17)	Language		The language the channel is w ritten in. This allow s aggregators to group all Italian language sites, for example, on a single page. A list of allow able values for this element, as provided by Netscape, is here. You may also use values defined by the W3C.
LASTBUILDDATE	string			A date-time displayed in RFC-822 format.
LINK	string	Hyperlink		The URL to the HTML website corresponding to the channel.
PUBDATE	string			A date-time displayed in RFC-822 format.
RSS_VERSION_ATTR	decimal	Version		
SKIPDAYS	int64			A hint for aggregators telling them w hich days they can skip.
SKIPHOURS	int64			A hint for aggregators telling them w hich hours they can skip.

Name	Data Type	Label	Required	Documentation
TEXTINPUT_DESCRIPTION	string			Explains the text input area.
TEXTINPUT_LINK	string			The URL of the CGI script that processes text input requests.
TEXTINPUT_NAME	string			The name of the text object in the text input area.
TEXTINPUT_TITLE	string			The label of the Submit button in the text input area.
ΠΠLE	string	Title		The name of the channel. It's how people refer to your service. If you have an HTML w ebsite that contains the same information as your RSS file, the title of your channel should be the same as the title of your w ebsite.
TTL	int64			ttl stands for time to live. It's a number of minutes that indicates how long a channel can be cached before refreshing from the source.

5 ReallySimpleSyndications

Catalog: RSS

The data in this table is partitioned per value of the column.

Retrieve: true

Topic: rss

Base XPath: /rss

Table Columns

The columns of the table ReallySimpleSyndications are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
INTERFACE_URL	string(4000)	Interface URL		
VERSION_ATTR	decimal	Version		

Index

- A -

analysis-enforce-row-uniqueness 2

- B -

bulk-delete-page-size-rows2bulk-insert-page-size-bytes2bulk-insert-page-size-rows2

- C -

CATEGORY 5, 7 CATEGORY_DOMAIN_ATTR 5, 7 **Channel Copyright** 5 Channel Description 5 **Channel Generator** 5 Channel Hyperlink 5 5 **Channel Language Channel Title** 5 CHANNEL_CATEGORY 5 CHANNEL CATEGORY DOMAIN ATTR 5 CHANNEL_CLOUD 5 CHANNEL_COPYRIGHT 5 CHANNEL_DESCRIPTION 5 CHANNEL DOCS 5 CHANNEL GENERATOR 5 CHANNEL_IMAGE_DESCRIPTION 5 CHANNEL_IMAGE_HEIGHT 5 CHANNEL_IMAGE_LINK 5 CHANNEL_IMAGE_TITLE 5 CHANNEL_IMAGE_URL 5 CHANNEL_IMAGE_WIDTH 5 CHANNEL_LANGUAGE 5 CHANNEL_LASTBUILDDATE 5 CHANNEL_LINK 5 CHANNEL PUBDATE 5 CHANNEL SKIPDAYS 5 CHANNEL SKIPHOURS 5 CHANNEL TEXTINPUT DESCRIPTION 5 CHANNEL_TEXTINPUT_LINK 5 CHANNEL_TEXTINPUT_NAME 5 CHANNEL TEXTINPUT TITLE 5 CHANNEL TITLE 5 CHANNEL TTL 5 Channelltems 5

Channels 7 CLOUD 7 COMMENTS 5 COPYRIGHT 7

- D -

DESCRIPTION 5, 7 DOCS 7 Driver 1

- E -

ENCLOSURE 5 ENCLOSURE_LENGTH_ATTR 5 ENCLOSURE_TYPE_ATTR 5 ENCLOSURE_URL_ATTR 5

- F -

force-case-sensitive-identifiers 2 forced-casing-identifiers 2

- G -

GENERATOR 7 GUID 5 GUID_ISPERMALINK_ATTR 5

- H -

Hyperlink 5, 7

- | -

Image Description 5, 7 Image Hyperlink 5, 7 Image Title 5, 7 IMAGE_DESCRIPTION 7 IMAGE_HEIGHT 7 IMAGE LINK 7 **IMAGE TITLE** 7 IMAGE URL 7 IMAGE WIDTH 7 Interface URL 5, 7, 9 INTERFACE URL 5, 7, 9 2 invantive-sql-compress-sparse-arrays invantive-sql-correct-invalid-date 2 invantive-sql-forward-filters-to-data-containers 2

RSS Data Model

invantive-sql-share-byte-arrays 2 invantive-sql-share-strings 2 invantive-sql-shuffle-fetch-results-data-containers invantive-use-cache 2

- L -

LANGUAGE 7 LASTBUILDDATE 7 LINK 5, 7 log-native-calls-to-disk-max-events 2 log-native-calls-to-disk-max-seconds 2 log-native-calls-to-disk-on-error 2 log-native-calls-to-disk-on-success 2 log-native-calls-to-trace 2

- M -

maximum-length-identifiers2max-url-length-accepted2max-url-length-desired2minimum-length-text2

- P -

partition-slot-based-rate-limit-length-ms 2 partition-slot-based-rate-limit-slots 2 pre-request-delay-ms 2 PUBDATE 5, 7

- R -

ReallySimpleSyndications 9 requested-page-size 2 requests-parallel-max 2 result-set-memory-cache 2 rss 1 RSS 2.0 1, 5, 7, 9 RSS_VERSION_ATTR 7 Rss20 1

- S -

SKIPDAYS 7 SKIPHOURS 7 slot-based-rate-limit-length-ms 2 slot-based-rate-limit-slots 2 SOURCE 5 SOURCE_URL_ATTR 5 standardize-identifiers 2 standardize-identifiers-casing 2

² **- T -**

TEXTINPUT_DESCRIPTION 7 TEXTINPUT_LINK 7 TEXTINPUT_NAME 7 TEXTINPUT_TITLE 7 TITLE 5, 7 TTL 7

- U -

use-metadata-memory-cache 2 use-result-memory-cache 2

- V -

Version 7, 9 VERSION_ATTR 9

- X -

xml-directories2xml-extension2xml-namespaces2

invantive the SOL company

Invantive B.V. Biesteweg | | 3849 RD Hierden the Netherlands

Tel: +31 88 00 26 500 Fax: +31 84 22 58 178 info@invantive.com invantive.com

IBAN NL25 BUNQ 2098 2586 07 Chamber of Industry and Commerce 13031406 VAT NL812602377B01 RSIN 8122602377 Managing Director: Guido Leenders Registered office: Regermond

(C) Copyright 2004-2023 Invantive Software B.V., the Netherlands. All rights reserved. 23.0.92 15/01/2025, 20:22 ISBN 978-94-6302-000-8: