



XAF 3.2 Data Model

for use with Invantive SQL

Auteursrecht

(C) Copyright 2004-2023 Invantive Software B.V., Nederland. Alle rechten voorbehouden.

Alle rechten voorbehouden. Niets uit deze uitgave mag worden verveelvoudigd, opgeslagen in een geautomatiseerd gegevensbestand, of openbaar gemaakt, in enige vorm of op enige wijze, hetzij elektronisch, mechanisch, door fotokopieën, opnemen, of enig andere manier, zonder voorafgaande schriftelijke toestemming van de uitgever.

Ondanks alle aan de samenstelling van deze tekst bestede zorg, kan noch de schrijver noch de uitgever aansprakelijkheid aanvaarden voor eventuele schade, die zou kunnen voortvloeien uit enige fout, die in deze uitgave zou kunnen voorkomen.

Deze handleiding is een naslagwerk bedoeld om het gebruik te verduidelijken. Indien gegevens in de voorbeeldafbeeldingen overeenkomen met gegevens in uw systeem, dan is de overeenkomst toevallig.

Belangrijke Informatie over Veiligheid en Gebruik

Beoogd gebruik en beperkingen: Deze software, ontwikkeld door Invantive, is ontworpen om een verscheidenheid aan zakelijke en informatietechnologische gegevensverwerkingsfuncties te ondersteunen, zoals boekhouding, financiële rapportage en verkooprapportage. Het is belangrijk om op te merken dat deze software niet is ontworpen, getest of goedgekeurd voor gebruik in omgevingen waar een storing of defect kan leiden tot levensbedreigende situaties, ernstige fysieke schade of milieuschade. Dit omvat, maar is niet beperkt tot:

- Nucleaire faciliteiten: de software mag niet worden gebruikt voor operaties of functies die verband houden met de controle, het onderhoud of de werking van nucleaire faciliteiten.
- Defensie en militaire toepassingen: deze software is niet geschikt voor gebruik in defensiegerelateerde toepassingen, inclusief maar niet beperkt tot wapenbeheer, militaire strategieplanning of andere aspecten van nationale defensie.
- Luchtvaart: de software is niet bedoeld voor gebruik in de bediening, navigatie of communicatiesystemen van vliegtuigen of luchtverkeersleidingsomgevingen.
- Gezondheidszorg en medicijnproductie: deze software mag niet worden gebruikt voor de werking van medische apparaten, de analyse van patiëntgegevens voor kritieke gezondheidsbeslissingen, farmaceutische productie of medisch onderzoek waarbij een storing of defect de gezondheid van de patiënt kan beïnvloeden.
- Verwerking van chemische en/of gevaarlijke stoffen: deze software is niet bedoeld voor het beheer, de controle of de operationele aspecten van chemische fabrieken of faciliteiten voor de verwerking van chemische en/of gevaarlijke stoffen. Elke storing in de software die in deze omgevingen wordt gebruikt kan leiden tot gevaarlijke chemische lozingen, explosies of milieurampen.
- Transport- en verkeerscontrolesystemen: de software mag niet worden gebruikt voor de besturing, bediening of het beheer van transportsystemen, waaronder de besturing van spoorwegsignalen, metrosystemen of verkeerslichten. Storingen in dergelijke kritieke systemen kunnen tot ernstige ongelukken leiden en de openbare veiligheid in gevaar brengen.
- Energienetwerken- en nutsbesturingssystemen: deze software is niet ontworpen voor de besturing of bediening van energienetwerksystemen, waaronder elektrische onderstations, besturingssystemen voor hernieuwbare energie of besturingssystemen van watermolenbedrijven. Het falen van software op deze gebieden kan leiden tot aanzienlijke stroomonderbrekingen, onderbrekingen in de watervoorziening of andere storingen in openbare voorzieningen, waardoor gemeenschappen in gevaar kunnen komen en grote schade kan worden aangericht.
- Andere omgevingen met een hoog risico: alle andere kritieke infrastructuren en omgevingen waar een storing in de software kan leiden tot aanzienlijke schade aan personen of het milieu.

Gebruikersverantwoordelijkheid: gebruikers moeten ervoor zorgen dat ze het beoogde gebruik van de software begrijpen en de software niet gebruiken in een omgeving die buiten het beoogde doel valt. Het is de verantwoordelijkheid van de gebruiker om de geschiktheid van de software voor de beoogde toepassing te beoordelen, vooral in scenario's die een risico kunnen vormen voor leven, gezondheid en/of milieu.

Afwijzing van aansprakelijkheid: Invantive wijst elke verantwoordelijkheid af voor schade, letsel of wettelijke gevolgen die voortvloeien uit het gebruik of misbruik van deze software in verboden en/of onbedoelde toepassingen.

Inhoud

1	SQL Driver for XAF 3.2	1
2	SQL Driver Attributes for XAF 3.2	2
3	Schema:	5
3.1	Tables	5
3.1.1	Companies	5
3.1.2	CompanyPostalCodes	6
3.1.3	CompanyStreetAddresses	7
3.1.4	CounterParties	8
3.1.5	CounterPartyBankAccounts	9
3.1.6	CounterPartyHistories	11
3.1.7	CounterPartyHistoryBankAccounts	13
3.1.8	CounterPartyHistoryPostalCodes	16
3.1.9	CounterPartyHistoryStreetAddresses	18
3.1.10	CounterPartyPostalCodes	21
3.1.11	CounterPartyStreetAddresses	23
3.1.12	GeneralLedgerAccounts	24
3.1.13	GeneralLedgerBasics	25
3.1.14	GeneralLedgerTaxonomies	26
3.1.15	GeneralLedgerTaxonomyElements	27
3.1.16	Headers	28
3.1.17	OpeningBalanceLines	29
3.1.18	OpeningBalances	30
3.1.19	Periods	31
3.1.20	SubledgerOpeningBalanceLines	32
3.1.21	SubledgerOpeningBalances	34
3.1.22	SubledgerTransactionLines	35
3.1.23	SubledgerTransactionLineVats	37
3.1.24	SubledgerTransactions	38
3.1.25	TransactionAttachments	39
3.1.26	TransactionJournals	40
3.1.27	TransactionLines	41
3.1.28	TransactionLineVats	43
3.1.29	TransactionRegisters	45
3.1.30	Transactions	46
3.1.31	VatCodes	48
4	Schema: CodeValues	49
4.1	Tables	49
4.1.1	AccountTypeCodes: XAF 3.2 Domain AccountTypeCodes	49
4.1.2	BasicTypeCodes: XAF 3.2 Domain BasicTypeCodes	49
4.1.3	CustomerSupplierTypeCodes: XAF 3.2 Domain CustomerSupplierTypeCodes	50
4.1.4	InvoiceDebitCreditTypeCodes: XAF 3.2 Domain InvoiceDebitCreditTypeCodes	51
4.1.5	InvoicePurchaseSalesTypeCodes: XAF 3.2 Domain InvoicePurchaseSalesTypeCodes	51
4.1.6	JournalTypeCodes: XAF 3.2 Domain JournalTypeCodes	52
4.1.7	OpeningBalanceLineDebitCreditTypeCodes: XAF 3.2 Domain OpeningBalanceLineDebitCreditTypeCodes	53
4.1.8	SubledgerLineAmountDebitCreditTypeCodes: XAF 3.2 Domain SubledgerLineAmountDebitCreditTypeCodes	53
4.1.9	SubledgerLineDebitCreditTypeCodes: XAF 3.2 Domain SubledgerLineDebitCreditTypeCodes	54
4.1.10	SubledgerLineInvoiceDebitCreditTypeCodes: XAF 3.2 Domain SubledgerLineInvoiceDebitCreditTypeCodes	54
4.1.11	SubledgerLineInvoicePurchaseSalesTypeCodes: XAF 3.2 Domain SubledgerLineInvoicePurchaseSalesTypeCodes	54

4.1.12	SubledgerLineMutationTypeCodes: XAF 3.2 Domain SubledgerLineMutationTypeCodes	56
4.1.13	SubledgerTypeCodes: XAF 3.2 Domain SubledgerTypeCodes	57
4.1.14	TransactionAmountDebitCreditTypeCodes: XAF 3.2 Domain TransactionAmountDebitCreditTypeCodes ..	57
4.1.15	TransactionLineAmountDebitCreditTypeCodes: XAF 3.2 Domain TransactionLineAmountDebitCreditTypeCodes ..	57
4.1.16	VATAmountDebitCreditTypeCodes: XAF 3.2 Domain VATAmountDebitCreditTypeCodes	59
5	Schema: Views	59
5.1	Views	59
5.1.1	TrialBalancePerPeriod	59
Index		61

1 SQL Driver for XAF 3.2

Invantive SQL is the fastest, easiest and most reliable way to exchange data with XAF 3.2.

Use the "Search" option in the left menu to search for a specific term such as the table or column description. When you already know the term, please use the "Index" option. When you can't find the information needed, please click on the Chat button at the bottom or place your question in the [user community](#). Other users or Invantive Support will try to help you to our best.

XML Auditfile Financieel version 3.2. XAF ("XML Auditfile Financieel") is a file format for Dutch accounting information. It is typically generated by accounting software for communication with other parties and/or the tax office.

The XAF 3.2 driver covers 48 tables and 1110 columns.

XAF 3.2 Clients

Invantive SQL is available on many user interfaces ("clients" in traditional server-client paradigm). All Invantive SQL statements can be exchanged with a close to 100% compatibility across all clients and operating systems (Windows, MacOS, Linux, iOS, Android).

The clients include Microsoft Excel, Microsoft Power BI, Microsoft Power Query, Microsoft Word and Microsoft Outlook. Web-based clients include Invantive Cloud, Invantive Bridge Online as OData proxy, Invantive App Online for interactive apps, Online SQL Editor for query execution and Invantive Data Access Point as extended proxy.

For technical users there are command-line editions of Invantive Data Hub running on iOS, Android, Windows, MacOS and Linux. Invantive Data Hub is also often used for enterprise server applications such as ETL. High-volume replication of data taken from XAF 3.2 into traditional databases such as SQL Server (on-premise and Azure), MySQL, PostgreSQL and Oracle is possible using [Invantive Data Replicator](#). Invantive Data Replicator automatically creates and maintains XAF 3.2 datawarehouses, possibly in combination with data from over 70 other (cloud) platforms. Data Replicator supports data volumes up to over 1 TB and over 5.000 companies. The on-premise edition of Invantive Bridge offers an XAF 3.2 ADO.net provider.

Specifications

The SQL driver for XAF 3.2 supports partitioning: data from multiple companies are all listed together in one table. The value of the column COMPANY_NAME indicates which company the data belongs to.

An introduction into the concepts of Invantive SQL such as databases, data containers and partitioning can be found in the [Invantive SQL grammar](#).

The configuration can be changed using various attributes during log on and use. A full list of configuration options is listed in the [driver attributes](#).

The catalog name is used to compose the full qualified name of an object like a table or view. The schema name is used to compose the full qualified name of an object like a table or view. On XAF 3.2 the comparison of two texts is case sensitive by default.

Changes and bug fixes on the XAF 3.2 SQL driver can be found in the [release notes](#). Get access to the XAF 3.2 community through the [XAF 3.2 section](#) of the Invantive forums.

Driver code for use in settings.xml: xaf32

Alias: xaf

Recommended alias: xf5

Partition Label: Firma

More technical documentation as provided by the supplier of XAF 3.2 on the native connection used can be found at

http://www.ictplaza.nl/uploads/xml_auditfiles/xmlfinancieel/20140402_AuditfileFinancieelVersie_3_2.zip.

General documentation on XAF 3.2 is available at

http://www.softwarepakket.nl/swpakketten/auditfiles/auditfile_financieel.php?bronw=6

Updated: 29-05-2022 00:55 using Invantive SQL version 22.0.196-PROD+3400.

2 SQL Driver Attributes for XAF 3.2

The SQL driver for XAF 3.2 has many attributes that can be finetuned to improve handling in scenarios with unreliable network connections to the XAF 3.2 server or high-volumes of data. Also, many drivers have driver-specific attributes to finetune actual behaviour or handle data not matching specifications.

The XAF 3.2 driver attributes are assigned a default value which seldom requires change. However, changes can be applied when needed on four levels, which are reflected in the table below by separate checkmarks:

- Connection string: the connection string from the settings*.xml file and applied during log on.
- Set SQL statement: a set SQL-statement to be executed once connection has been established.
- Drivers file: the providers.xml file (obsolete starting release 17.32).
- Log on: value to be specified interactively by user during log on in a user interface.

The connection string for XAF 3.2 can be found in the settings*.xml file used for the database. Settings*.xml files are typically located in the %USERPROFILE%\invantive folder in most deployment scenarios. The reference manuals contain instructions how to relocate the settings*.xml files. Each data container of a database in the connection string can have a connectionString element specifying the name and values of attributes. Both name and value must be properly escaped according to XML-semantics. Actual application of the value is solely done during log on. A new connection must be established to change the value of a driver attribute using a connection string.

The set SQL statement can be executed after log on. The syntax is: set NAME VALUE, or for a distributed database: set NAME@ALIAS VALUE. In some scenarios you may need to enclose the driver attribute name in square brackets to escape it from parsing, for instance when a reserved SQL keyword is part of the name. The new value takes effect straight after execution of the set-statement. The set-statement can be executed as often as needed during a session.

Driver attributes that can be interactively set to a value are typically presented in the log on window. Depending on the platform and design decisions of the user interface designer, some or all of the available driver attributes can have been made available.

The XAF 3.2 driver can be configured using the following attributes:

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
analysis-enforce-row-uniqueness	Use for analysis only! Enforce rows to be unique.	Shared	False	✓	✓	✓	
bulk-delete-page-size-rows	Number of rows to delete per batch when bulk deleting	Shared	10000	✓	✓	✓	
bulk-insert-page-size-bytes	Approximate maximum size in bytes of batch when bulk inserting	Shared	10000000	✓	✓	✓	
bulk-insert-page-size-rows	Number of rows to insert per batch when bulk inserting	Shared	10000	✓	✓	✓	
force-case-sensitive-identifiers	Consider identifiers as case-sensitive independent of the platform capabilities.	Shared	False	✓	✓	✓	
forced-casing-identifiers	Forced casing of identifiers. Choose from Unset, Lower, Upper and Mixed.	Shared		✓	✓	✓	
invantive-sql-compress-sparse-arrays	Whether to compress sparse arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-correct-invalid-date	Whether to correct dates considered invalid since they are before 01-01-1753. When nullable, they are removed. Otherwise they are replaced by 01-01-1753.	SQL Engine V1	False	✓	✓	✓	
invantive-sql-forward-filters-to-data-containers	Whether to forward filters to data containers.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-byte-arrays	Whether to share the memory used by identical byte arrays in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-share-strings	Whether to share the memory used by identical strings in result sets during compression.	SQL Engine V1	True	✓	✓	✓	
invantive-sql-shuffle-fetch-results-data-containers	Whether to shuffle results fetched from data containers.	SQL Engine V1	False	✓	✓	✓	
invantive-use-cache	Whether to cache the results of a query.	SQL Engine V1	True	✓	✓	✓	
log-native-calls-to-disk-max-events	Maximum number of events to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-max-seconds	Maximum number of seconds to register from last activation.	Shared		✓	✓	✓	
log-native-calls-to-disk-on-error	Registers native calls to data container backend as disk files when an error occurred.	Shared	False	✓	✓	✓	
log-native-calls-to-disk-on-success	Registers native calls to data container backend as disk files when successful.	Shared	False	✓	✓	✓	
log-native-calls-to-trace	Log native calls to data container backend on the trace.	Shared	False	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
maximum-length-identifiers	Non-default maximum length in characters of identifier names.	Shared		✓	✓	✓	
max-url-length-accepted	The maximum accepted URL length before raising an error.	Shared	8000	✓	✓	✓	
max-url-length-desired	The maximum desired URL length.	Shared	8000	✓	✓	✓	
minimum-length-text	Extend all text columns to this length to allow processing of XML that uses longer text values than the XSD specifies.	XML	240	✓			✓
partition-slot-based-rate-limit-length-ms	Total length in ms across all slots of a partition-based rate limit.	Shared	60000	✓		✓	
partition-slot-based-rate-limit-slots	Number of slots per partition-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
pre-request-delay-ms	Pre-request delay in milliseconds per request.	Shared	0	✓	✓	✓	
requested-page-size	Preferred number of rows to exchange per round trip; only effective on limited platforms such as AFAS Online	Shared		✓	✓	✓	
requests-parallel-max	Maximum number of parallel data requests from individual partitions on the data container.	Shared	32	✓	✓	✓	
result-set-memory-cache	Action: provide 'empty' to empty.	XML			✓		
slot-based-rate-limit-length-ms	Total length in ms across all slots of a slot-based rate limit.	Shared	60000	✓		✓	
slot-based-rate-limit-slots	Number of slots of a slot-based rate limit. Null means no slot-based rate limit	Shared		✓		✓	
standardize-identifiers	Rewrite all identifiers to the preferred standards as configured by standardize-identifiers-casing and maximum-length-identifiers.	Shared	True	✓	✓	✓	
standardize-identifiers-casing	Rewrite all identifiers to the recommended standard platform-specific casing when changing a data model on a case-dependent platform.	Shared	True	✓	✓	✓	
use-exact-online-extensions	Whether to incorporate Exact Online-specific extensions on the XAF 3.2 format. Currently in development for archival purposes.	XML	False	✓		✓	✓
use-metadata-memory-cache	Whether to use the metadata in memory calculated previously Has only practical use during development on a XML provider.	XML	True	✓	✓	✓	

Code	Description	Origin	Default Value	Set from Connection String	Set from Set SQL-Statement	Set from Drivers File	Set from Log On
use-result-memory-cache	Whether to use result sets cached in memory from previous queries that can answer the current query.	XML	False	✓	✓	✓	
xml-directories	{res:itgen_provider_attribute_xml_directories_description}			✓	✓	✓	✓
xml-extension	{res:itgen_provider_attribute_xml_extension_description}		*.xaf	✓	✓	✓	✓
xml-namespaces	Comma-separated list of namespace prefixes and their URI		xaf=http://www.auditfiles.nl/XAF/3.2	✓	✓	✓	

3 Schema:

3.1 Tables

3.1.1 Companies

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile

XPath: /xaf:company

Table Columns

The columns of the table Companies are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COMPANYIDENT	string(240)			
COMPANYNAME	string(999)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
OPENINGBALANCE_LINESCOUNT	int64	Anfangsbestand Lines Count		
OPENINGBALANCE_OPBALDATE	datetime	Anfangsbestand Datum		
OPENINGBALANCE_OPBALDESC	string(999)	Anfangsbestand Beschreibung		
OPENINGBALANCE_TOTALCREDIT	decimal	Anfangsbestand Gesamtguthaben		
OPENINGBALANCE_TOTALDEBIT	decimal	Anfangsbestand Total Debit		
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TAXREGIDENT	string(240)			
TAXREGISTRATIONCOUNTRY	string(240)			
TRANSACTIONS_LINESCOUNT	int64	Transaktionen Lines Count		
TRANSACTIONS_TOTALCREDIT	decimal	Transaktionen Gesamtguthaben		
TRANSACTIONS_TOTALDEBIT	decimal	Transaktionen Total Debit		

3.1.2 CompanyPostalCodes

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company

XPath: /xaf:postalAddress

Table Columns

The columns of the table CompanyPostalCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CITY	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_COMPANYID	string(240)	Firma Firmenkennung		

Name	Data Type	Label	Required	Documentation
COMPANY_COMPANYNAME	string(999)	Firma Firmenname		
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COMPANY_TAXREGIDENT	string(240)	Firma Tax Registration Identification		
COMPANY_TAXREGISTRATIONCOUNTRY	string(240)	Firma Tax Registration Country		
COUNTRY	string(240)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NUMBER	string(240)			
NUMBEREXTENSION	string(999)			
POSTALCODE	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROPERTY	string(240)			
REGION	string(240)			
STREETNAME	string(999)			

3.1.3 CompanyStreetAddresses

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company

XPath: /xaf:streetAddress

Table Columns

The columns of the table CompanyStreetAddresses are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CITY	string(240)			

Name	Data Type	Label	Required	Documentation
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_COMPANYIDENT	string(240)	Firma Firmenkennung		
COMPANY_COMPANYNAME	string(999)	Firma Firmenname		
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COMPANY_TAXREGIDENT	string(240)	Firma Tax Registration Identification		
COMPANY_TAXREGISTRATIONCOUNTRY	string(240)	Firma Tax Registration Country		
COUNTRY	string(240)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NUMBER	string(240)			
NUMBEREXTENSION	string(999)			
POSTALCODE	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROPERTY	string(240)			
REGION	string(240)			
STREETNAME	string(999)			

3.1.4 CounterParties

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers

XPath: /xaf:customerSupplier

Table Columns

The columns of the table CounterParties are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CHANGEINFO_CHANGEDATETIME	datetime	Change Information Datum/Zeit		
CHANGEINFO_CHANGEDICTION	string(999)	Change Information Beschreibung		
CHANGEINFO_USERID	string(240)	Change Information Benutzer-Kennung		
COMMERCENR	string(999)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
CONTACT	string(240)			
CUSTCREDITLIMIT	decimal			
CUSTSUPGRPID	string(240)			
CUSTSUPID	string(240)			
CUSTSUPNAME	string(240)			
CUSTSUPTP	string(240)			
EMAIL	string			
FAX	string(240)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
RELATIONSHIPID	string(240)			
SUPPLIERLIMIT	decimal			
TAXREGIDENT	string(240)			
TAXREGISTRATIONCOUNTRY	string(240)			
TELEPHONE	string(240)			
WEBSITE	string			

3.1.5 CounterPartyBankAccounts

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:bankAccount

Table Columns

The columns of the table CounterPartyBankAccounts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BANKACCNR	string(240)			
BANKIDCD	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit		
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDDESCRIPTION	string(999)	Counter Party Change Information Beschreibung		
CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)	Counter Party Change Information Benutzer-Kennung		
CUSTOMERSUPPLIER_COMMERCE_NR	string(999)	Gegenpartei Commerce Number		
CUSTOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson		
CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal	Gegenpartei Customer Credit Limit		
CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)	Gegenpartei Gruppen-ID		
CUSTOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation		
CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)	Gegenpartei Name		
CUSTOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art		
CUSTOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail		
CUSTOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		

Name	Data Type	Label	Required	Documentation
CUSTOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	

3.1.6 CounterPartyHistories

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:customerSupplierHistory/xaf:customerSupplier

Table Columns

The columns of the table CounterPartyHistories are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CHANGEINFO_CHANGEDATETIME	datetime	Change Information Datum/Zeit		
CHANGEINFO_CHANGEDESCRIPTION	string(999)	Change Information Beschreibung		
CHANGEINFO_USERID	string(240)	Change Information Benutzer-Kennung		
COMMERCENR	string(999)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
CONTACT	string(240)			
CUSTCREDITLIMIT	decimal			
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CHANGEINFO_ CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CHANGEINFO_ CHANGEDDESCRIPTION	string(999)	Counter Party Change Information Beschreibung		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CHANGEINFO_ USERID	string(240)	Counter Party Change Information Benutzer- Kennung		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_COMMERCENR	string(999)	Gegenpartei Commerce Number		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CUSTCREDITLI MIT	decimal	Gegenpartei Customer Credit Limit		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CUSTSUPGRPI D	string(240)	Gegenpartei Gruppen- ID		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CUSTSUPNAM E	string(240)	Gegenpartei Name		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_RELATIONSHIPI D	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_TAXREGISTRA TIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIERHISTORY_CU STOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
CUSTSUPGRPID	string(240)			

Name	Data Type	Label	Required	Documentation
CUSTSUPID	string(240)			
CUSTSUPNAME	string(240)			
CUSTSUPTP	string(240)			
EMAIL	string			
FAX	string(240)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
RELATIONSHIPID	string(240)			
SUPPLIERLIMIT	decimal			
TAXREGIDENT	string(240)			
TAXREGISTRATIONCOUNTRY	string(240)			
TELEPHONE	string(240)			
WEBSITE	string			

3.1.7 CounterPartyHistoryBankAccounts

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:customerSupplierHistory/xaf:customerSupplier/xaf:bankAccount

Table Columns

The columns of the table CounterPartyHistoryBankAccounts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BANKACCNR	string(240)			
BANKIDCD	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime			
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDICTIONARY	string(999)			
CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)			
CUSTOMERSUPPLIER_COMMERCE_NR	string(999)			
CUSTOMERSUPPLIER_CONTACT	string(240)			
CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal			
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDICTIONARY	string(999)	Counter Party Change Information Beschreibung		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)	Counter Party Change Information Benutzer-Kennung		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_COMMERCENR	string(999)	Gegenpartei Commerce Number		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal	Gegenpartei Customer Credit Limit		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)	Gegenpartei Gruppen-ID		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)	Gegenpartei Name		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail		

Name	Data Type	Label	Required	Documentation
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)			
CUSTOMERSUPPLIER_CUSTSUPID	string(240)			
CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)			
CUSTOMERSUPPLIER_CUSTSUPTP	string(240)			
CUSTOMERSUPPLIER_EMAIL	string			
CUSTOMERSUPPLIER_FAX	string(240)			
CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)			
CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal			
CUSTOMERSUPPLIER_TAXREGIDENT	string(240)			
CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)			
CUSTOMERSUPPLIER_TELEPHONE	string(240)			
CUSTOMERSUPPLIER_WEBSITE	string			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	

3.1.8 CounterPartyHistoryPostalAddresses

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:customerSupplierHistory/xaf:customerSupplier/xaf:postalAddress

Table Columns

The columns of the table CounterPartyHistoryPostalAddresses are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CITY	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COUNTRY	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDICTIONARY	string(999)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_COMMERCE_NR	string(999)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CONTACT	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDICTIONARY	string(999)	Counter Party Change Information Beschreibung	<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)	Counter Party Change Information Benutzer-Kennung		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_COMMERCENR	string(999)	Gegenpartei Commerce Number		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal	Gegenpartei Customer Credit Limit		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)	Gegenpartei Gruppen-ID		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)	Gegenpartei Name		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)			
CUSTOMERSUPPLIER_CUSTSUPID	string(240)			

Name	Data Type	Label	Required	Documentation
CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)			
CUSTOMERSUPPLIER_CUSTSUPTP	string(240)			
CUSTOMERSUPPLIER_EMAIL	string			
CUSTOMERSUPPLIER_FAX	string(240)			
CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)			
CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal			
CUSTOMERSUPPLIER_TAXREGIDENT	string(240)			
CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)			
CUSTOMERSUPPLIER_TELEPHONE	string(240)			
CUSTOMERSUPPLIER_WEBSITE	string			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NUMBER	string(240)			
NUMBEREXTENSION	string(999)			
POSTALCODE	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROPERTY	string(240)			
REGION	string(240)			
STREETNAME	string(999)			

3.1.9 CounterPartyHistoryStreetAddresses

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:customerSupplierHistory/xaf:customerSupplier/xaf:streetAddress

Table Columns

The columns of the table CounterPartyHistoryStreetAddresses are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CITY	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COUNTRY	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDDESCRIPTION	string(999)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_COMMERCE_NR	string(999)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CONTACT	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDDESCRIPTION	string(999)	Counter Party Change Information Beschreibung	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)	Counter Party Change Information Benutzer-Kennung	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_COMMERCENR	string(999)	Gegenpartei Commerce Number	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal	Gegenpartei Customer Credit Limit	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)	Gegenpartei Gruppen-ID	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation	<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)	Gegenpartei Name		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIER_CUSTOMER_SUPPLIERHISTORY_CUSTOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)			
CUSTOMERSUPPLIER_CUSTSUPID	string(240)			
CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)			
CUSTOMERSUPPLIER_CUSTSUPTP	string(240)			
CUSTOMERSUPPLIER_EMAIL	string			
CUSTOMERSUPPLIER_FAX	string(240)			
CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)			
CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal			
CUSTOMERSUPPLIER_TAXREGIDENT	string(240)			
CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)			
CUSTOMERSUPPLIER_TELEPHONE	string(240)			
CUSTOMERSUPPLIER_WEBSITE	string			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NUMBER	string(240)			
NUMBEREXTENSION	string(999)			
POSTALCODE	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROPERTY	string(240)			
REGION	string(240)			
STREETNAME	string(999)			

3.1.10 CounterPartyPostalAddresses

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:postalAddress

Table Columns

The columns of the table CounterPartyPostalAddresses are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CITY	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COUNTRY	string(240)			
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit		
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDDESCRIPTION	string(999)	Counter Party Change Information		

Name	Data Type	Label	Required	Documentation
		Beschreibung		
CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)	Counter Party Change Information Benutzer-Kennung		
CUSTOMERSUPPLIER_COMMERCE_NR	string(999)	Gegenpartei Commerce Number		
CUSTOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson		
CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal	Gegenpartei Customer Credit Limit		
CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)	Gegenpartei Gruppen-ID		
CUSTOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation		
CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)	Gegenpartei Name		
CUSTOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art		
CUSTOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail		
CUSTOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIER_RELATIONSHIPID	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		
CUSTOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NUMBER	string(240)			
NUMBEREXTENSION	string(999)			
POSTALCODE	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROPERTY	string(240)			
REGION	string(240)			
STREETNAME	string(999)			

3.1.11 CounterPartyStreetAddresses

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:customersSuppliers/xaf:customerSupplier

XPath: /xaf:streetAddress

Table Columns

The columns of the table CounterPartyStreetAddresses are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CITY	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COUNTRY	string(240)		<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATETIME	datetime	Counter Party Change Information Datum/Zeit	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDDESCRIPTION	string(999)	Counter Party Change Information Beschreibung	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CHANGEINFO_USERID	string(240)	Counter Party Change Information Benutzer-Kennung	<input type="checkbox"/>	
CUSTOMERSUPPLIER_COMMERCE_NR	string(999)	Gegenpartei Commerce Number	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CONTACT	string(240)	Gegenpartei Kontaktperson	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTCREDITLIMIT	decimal	Gegenpartei Customer Credit Limit	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTSUPGRPID	string(240)	Gegenpartei Gruppen-ID	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTSUPID	string(240)	Gegenpartei Identifikation	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTSUPNAME	string(240)	Gegenpartei Name	<input type="checkbox"/>	
CUSTOMERSUPPLIER_CUSTSUPTP	string(240)	Gegenpartei Art	<input type="checkbox"/>	
CUSTOMERSUPPLIER_EMAIL	string	Gegenpartei E-Mail	<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
CUSTOMERSUPPLIER_FAX	string(240)	Gegenpartei Telefax		
CUSTOMERSUPPLIER_RELATIONS_HIPID	string(240)	Gegenpartei ID der Beziehung		
CUSTOMERSUPPLIER_SUPPLIERLIMIT	decimal	Gegenpartei Supplier Credit Limit		
CUSTOMERSUPPLIER_TAXREGIDENT	string(240)	Gegenpartei Tax Registration Identification		
CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNTRY	string(240)	Gegenpartei Tax Registration Country		
CUSTOMERSUPPLIER_TELEPHONE	string(240)	Gegenpartei Telefon		
CUSTOMERSUPPLIER_WEBSITE	string	Gegenpartei Website		
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NUMBER	string(240)			
NUMBEREXTENSION	string(999)			
POSTALCODE	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROPERTY	string(240)			
REGION	string(240)			
STREETNAME	string(999)			

3.1.12 GeneralLedgerAccounts

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:generalLedger

XPath: /xaf:ledgerAccount

Table Columns

The columns of the table GeneralLedgerAccounts are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
ACCDESC	string(999)			

Name	Data Type	Label	Required	Documentation
ACCID	string(240)			
ACCTP	string(240)			
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
CHANGEINFO_CHANGEDATETIME	datetime	Change Information Datum/Zeit		
CHANGEINFO_CHANGEDESCRIPTI ON	string(999)	Change Information Beschreibung		
CHANGEINFO_USERID	string(240)	Change Information Benutzer-Kennung		
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
LEADCODE	string(999)			
LEADCROSSREF	string(999)			
LEADDDESCRIPTION	string(999)			
LEADREFERENCE	string(999)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	

3.1.13 GeneralLedgerBasics

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:generalLedger/xaf:basics

XPath: /xaf:basic

Table Columns

The columns of the table GeneralLedgerBasics are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BASICDESC	string			
BASICID	string(240)			
BASICTYPE	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	

3.1.14 GeneralLedgerTaxonomies

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:generalLedger/xaf:ledgerAccount/xaf:taxonomies

XPath: /xaf:taxonomy

Table Columns

The columns of the table GeneralLedgerTaxonomies are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TAXONOMIES_ACCDESC	string(999)			
TAXONOMIES_ACCID	string(240)			
TAXONOMIES_ACCTP	string(240)			
TAXONOMIES_CHANGEINFO_CHANGEDATETIME	datetime			
TAXONOMIES_CHANGEINFO_CHANGEDDESCRIPTION	string(999)			
TAXONOMIES_CHANGEINFO_USERID	string(240)			
TAXONOMIES_LEADCODE	string(999)			
TAXONOMIES_LEADCROSSREF	string(999)			
TAXONOMIES_LEADDESCRIPTION	string(999)			
TAXONOMIES_LEADREFERENCE	string(999)			
TAXOREF	string			

3.1.15 GeneralLedgerTaxonomyElements

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:generalLedger/xaf:ledgerAccount/xaf:taxonomies/xaf:taxonomy

XPath: /xaf:taxoElement

Table Columns

The columns of the table GeneralLedgerTaxonomyElements are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TAXONOMY_TAXOREF	string			

3.1.16 Headers

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile

XPath: /xaf:header

Table Columns

The columns of the table Headers are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
CURCODE	string(240)			
DATECREATED	datetime			
ENDDATE	datetime			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
FISCALYEAR	string(240)			
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
SOFTWAREDESC	string(240)			
SOFTWAREREVERSION	string(240)			
STARTDATE	datetime			

3.1.17 OpeningBalanceLines

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company

XPath: /xaf:openingBalance/xaf:obLine

Table Columns

The columns of the table OpeningBalanceLines are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
ACCID	string(240)			
AMNT	decimal			
AMNTPP	string(240)			
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BALANCE	decimal		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NR	string(240)			
OPENINGBALANCE_COMPANY_C OMPANYIDENT	string(240)	Firma Firmenkennung		
OPENINGBALANCE_COMPANY_C OMPANYNAME	string(999)	Firma Firmenname		
OPENINGBALANCE_COMPANY_T AXREGIDENT	string(240)	Firma Tax Registration Identification		
OPENINGBALANCE_COMPANY_T AXREGISTRATIONCOUNTRY	string(240)	Firma Tax Registration Country		
OPENINGBALANCE_COMPANY_TR ANSACTONS_LINESCOUNT	int64	Verhandlung Lines Count		
OPENINGBALANCE_COMPANY_TR ANSACTONS_TOTALCREDIT	decimal	Verhandlung Gesamtguthaben		
OPENINGBALANCE_COMPANY_TR ANSACTONS_TOTALDEBIT	decimal	Verhandlung Total Debit		
OPENINGBALANCE_LINESCOUNT	int64	Anfangsbestand Lines Count		
OPENINGBALANCE_OPBALDATE	datetime	Anfangsbestand Datum		
OPENINGBALANCE_OPBALDESC	string(999)	Anfangsbestand Beschreibung		
OPENINGBALANCE_TOTALCREDIT	decimal	Anfangsbestand Gesamtguthaben		
OPENINGBALANCE_TOTALDEBIT	decimal	Anfangsbestand Total Debit		
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	

3.1.18 OpeningBalances

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company

XPath: /xaf:openingBalance

Table Columns

The columns of the table OpeningBalances are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_COMPANYIDENT	string(240)	Firma Firmenkennung		
COMPANY_COMPANYNAME	string(999)	Firma Firmenname		
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COMPANY_TAXREGIDENT	string(240)	Firma Tax Registration Identification		
COMPANY_TAXREGISTRATIONCOUNTR Y	string(240)	Firma Tax Registration Country		
COMPANY_TRANSACTIONS_LINES COUNT	int64	Verhandlung Lines Count		
COMPANY_TRANSACTIONS_TOT ALCREDIT	decimal	Verhandlung Gesamtguthaben		
COMPANY_TRANSACTIONS_TOT ALDEBIT	decimal	Verhandlung Total Debit		
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
LINECOUNT	int64			
OPBALDATE	datetime			
OPBALDESC	string(999)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TOTALCREDIT	decimal			
TOTALDEBIT	decimal			

3.1.19 Periods

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:periods

XPath: /xaf:period

Table Columns

The columns of the table `Periods` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
ENDDATEPERIOD	datetime			
ENDTIMEPERIOD	datetime			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PERIODDESC	string(240)			
PERIODNUMBER	int64			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
STARTDATEPERIOD	datetime			
STARTTIMEPERIOD	datetime			

3.1.20 SubledgerOpeningBalanceLines

Catalog: XAF

The data in this table is partitioned per value of the `COMPANY_NAME` column.

Retrieve: true

Topic: auditfile

Base XPath: `/xaf:auditfile/xaf:company/xaf:openingBalance`

XPath: `/xaf:obSubledgers/xaf:obSubledger/xaf:obSbLine`

Table Columns

The columns of the table `SubledgerOpeningBalanceLines` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AMNT	decimal			
AMNTP	string(240)			
ARTGRPID	string(240)			

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COSTID	string(240)			
CUSTSUPID	string(240)			
DESC	string			
DOCREF	string(999)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
INVDT	datetime			
INVDUEDT	datetime			
INVPURSALTP	string(240)			
INVREF	string(999)			
INVTP	string(240)			
MATCHKEYID	string(240)			
MUTTP	string(240)			
NR	string(240)			
OBLINENR	string(240)			
OBSUBLEDGER_LINESCOUNT	int64	Opening Balance Subledger Lines Count		
OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_LINESCOUNT	int64	Anfangsbestand Lines Count		
OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_OPBALDATE	datetime	Anfangsbestand Datum		
OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_OPBALDESC	string(999)	Anfangsbestand Beschreibung		
OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_TOTALCREDIT	decimal	Anfangsbestand Gesamtguthaben		
OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_TOTALDEBIT	decimal	Anfangsbestand Total Debit		
OBSUBLEDGER_SBDESC	string	Opening Balance Subledger Beschreibung		
OBSUBLEDGER_SBTYPE	string(240)	Opening Balance Subledger Art		

Name	Data Type	Label	Required	Documentation
OBSUBLEDGER_TOTALCREDIT	decimal	Opening Balance Subledger Gesamtguthaben		
OBSUBLEDGER_TOTALDEBIT	decimal	Opening Balance Subledger Total Debit		
PRODID	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROJID	string(240)			
QNTITY	int64			
QNTITYID	string(240)			
RECREF	string(999)			

3.1.21 SubledgerOpeningBalances

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:openingBalance

XPath: /xaf:obSubledgers/xaf:obSubledger

Table Columns

The columns of the table SubledgerOpeningBalances are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
LINESCOUNT	int64			

Name	Data Type	Label	Required	Documentation
OBSUBLEDGERS_OPENINGBALANCE_LINESCOUNT	int64	Anfangsbestand Lines Count		
OBSUBLEDGERS_OPENINGBALANCE_OPBALDATE	datetime	Anfangsbestand Datum		
OBSUBLEDGERS_OPENINGBALANCE_OPBALDESC	string(999)	Anfangsbestand Beschreibung		
OBSUBLEDGERS_OPENINGBALANCE_TOTALCREDIT	decimal	Anfangsbestand Gesamtguthaben		
OBSUBLEDGERS_OPENINGBALANCE_TOTALDEBIT	decimal	Anfangsbestand Total Debit		
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
SBDESC	string			
SBTYPE	string(240)			
TOTALCREDIT	decimal			
TOTALDEBIT	decimal			

3.1.22 SubledgerTransactionLines

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:transactions/xaf:subledgers/xaf:subledger

XPath: /xaf:sbLine

Table Columns

The columns of the table SubledgerTransactionLines are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AMNT	decimal			
AMNTPP	string(240)			
ARTGRPID	string(240)			
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COSTID	string(240)			
CURRENCY_CURAMNT	decimal	Währung Betrag		
CURRENCY_CURCODE	string(240)	Währung Währungscode		
CUSTSUPID	string(240)			
DESC	string			
DOCREF	string(999)			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
INVDT	datetime			
INVDEUDT	datetime			
INVPURSALTP	string(240)			
INVREF	string(999)			
INVTP	string(240)			
JRNID	string(240)			
MATCHKEYID	string(240)			
MUTTP	string(240)			
NR	string(240)			
PRODID	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROJID	string(240)			
QNTITY	int64			
QNTITYID	string(240)			
RECREF	string(999)			
SUBLEDGER_LINESCOUNT	int64	Subledger Lines Count		
SUBLEDGER_SBDESC	string	Subledger Beschreibung		
SUBLEDGER_SBTYPE	string(240)	Subledger Art		
SUBLEDGER_TOTALCREDIT	decimal	Subledger Gesamtguthaben		
SUBLEDGER_TOTALDEBIT	decimal	Subledger Total Debit		
TRLINENR	string(240)			
TRNR	string(240)			

3.1.23 SubledgerTransactionLineVats

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:transactions/xaf:subledgers/xaf:subledger/xaf:sbLine

XPath: /xaf:vat

Table Columns

The columns of the table SubledgerTransactionLineVats are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
SBLINE_AMNT	decimal	Subledger Line Betrag		
SBLINE_AMNTP	string(240)	Subledger Line Summe Typ		
SBLINE_ARTGRPID	string(240)	Subledger Line Article Group ID		
SBLINE_COSTID	string(240)	Subledger Line Cost ID		
SBLINE_CURRENCY_CURAMNT	decimal			
SBLINE_CURRENCY_CURCODE	string(240)			
SBLINE_CUSTSUPID	string(240)	Subledger Line Identifikation		
SBLINE_DESC	string	Subledger Line Beschreibung		
SBLINE_DOCREF	string(999)	Subledger Line Document Reference		

Name	Data Type	Label	Required	Documentation
SBLINE_INVDT	datetime	Subledger Line Rechnungsdatum		
SBLINE_INVDUEDT	datetime	Subledger Line Invoice Due Date		
SBLINE_INVPURSALTP	string(240)	Subledger Line Purchase/Sales Type		
SBLINE_INVREF	string(999)	Subledger Line Invoice Reference		
SBLINE_INVTP	string(240)			
SBLINE_JRNID	string(240)	Subledger Line Journal ID		
SBLINE_MATCHKEYID	string(240)	Subledger Line Match Key ID		
SBLINE_MUTTP	string(240)	Subledger Line Mutation Type		
SBLINE_NR	string(240)	Subledger Line Number		
SBLINE_PRODID	string(240)	Subledger Line Produkt ID		
SBLINE_PROJID	string(240)	Subledger Line Projekt ID		
SBLINE_QNTITY	int64	Subledger Line Menge		
SBLINE_QNTITYID	string(240)	Subledger Line Quantity ID		
SBLINE_RECREF	string(999)	Subledger Line Record Reference		
SBLINE_TRLINENR	string(240)			
SBLINE_TRNR	string(240)			
VATAMNT	decimal			
VATAMNTP	string(240)			
VATID	string(240)			
VATPERC	decimal			

3.1.24 SubledgerTransactions

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:transactions/xaf:subledgers

XPath: /xaf:subledger

Table Columns

The columns of the table SubledgerTransactions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
LINECOUNT	int64			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
SBDESC	string			
SBTYPE	string(240)			
TOTALCREDIT	decimal			
TOTALDEBIT	decimal			

3.1.25 TransactionAttachments

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base

XPath: /xaf:auditfile/xaf:company/xaf:transactions/xaf:journal/xaf:transaction/xaf:attachments

XPath: /xaf:attachment

Table Columns

The columns of the table TransactionAttachments are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BINARYDATA	byte[]			

Name	Data Type	Label	Required	Documentation
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
NAME	string(999)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	

3.1.26 TransactionJournals

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:transactions

XPath: /xaf:journal

Table Columns

The columns of the table TransactionJournals are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BANKACCNR	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
DESCRIPTION	string			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
JRNID	string(240)			
JRNTP	string(240)			
OFFSETACCID	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TRANSACTIONS_LINESCOUNT	int64	Verhandlung Lines Count		
TRANSACTIONS_TOTALCREDIT	decimal	Verhandlung Gesamtguthaben		
TRANSACTIONS_TOTALDEBIT	decimal	Verhandlung Total Debit		

3.1.27 TransactionLines

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:transactions

XPath: /xaf:journal/xaf:transaction/xaf:trLine

Table Columns

The columns of the table TransactionLines are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
ACCID	string(240)			
AMNT	decimal			
AMNTP	string(240)			
ARTGRPID	string(240)			
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
BALANCE	decimal		<input type="checkbox"/>	
BANKACNR	string(240)			
BANKIDCD	string(240)			
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COSTID	string(240)			
CURRENCY_CURAMNT	decimal	Währung Betrag		
CURRENCY_CURCODE	string(240)	Währung Währungscode		
CUSTSUPID	string(240)			
DESCRIPTION	string			
DOCREF	string(999)			
EFFDATE	datetime			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
INV REF	string(999)			
MATCHKEYID	string(240)			
NR	string(240)			
ORDERREF	string(999)			
PRODID	string(240)			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
PROJID	string(240)			
QNTITY	int64			
QNTITYID	string(240)			
RECEIVINGDOCREF	string(999)			
RECREF	string(999)			
SHIPDOCREF	string(999)			
TRANSACTION_AMNT	decimal	Verhandlung Betrag		
TRANSACTION_AMNTP	string(240)	Verhandlung Summe Typ		
TRANSACTION_DESC	string	Verhandlung Beschreibung		
TRANSACTION_JOURNAL_BANKACCNR	string(240)	Journal Bankkontonummer		
TRANSACTION_JOURNAL_DESCRIPTION	string	Journal Beschreibung		
TRANSACTION_JOURNAL_JRNID	string(240)	Journal Journal ID		
TRANSACTION_JOURNAL_JRNTP	string(240)	Journal Journal Typ		
TRANSACTION_JOURNAL_OFFSETTACCID	string(240)	Journal Offset Account ID		

Name	Data Type	Label	Required	Documentation
TRANSACTION_JOURNAL_TRANS ACTIONS_LINESCOUNT	int64	Verhandlung Lines Count		
TRANSACTION_JOURNAL_TRANS ACTIONS_TOTALCREDIT	decimal	Verhandlung Gesamtguthaben		
TRANSACTION_JOURNAL_TRANS ACTIONS_TOTALDEBIT	decimal	Verhandlung Total Debit		
TRANSACTION_NR	string(240)	Verhandlung Number		
TRANSACTION_PERIODNUMBER	int64	Verhandlung Period Number		
TRANSACTION_SOURCEID	string(240)	Verhandlung Quellen-Kennzahl		
TRANSACTION_TRDT	datetime	Verhandlung Datum		
TRANSACTION_USERID	string(240)	Verhandlung Benutzer-Kennung		
WORKCOSTARRREF	string(999)			

3.1.28 TransactionLineVats

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:transactions

XPath: /xaf:journal/xaf:transaction/xaf:trLine/xaf:vat

Table Columns

The columns of the table TransactionLineVats are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	

Name	Data Type	Label	Required	Documentation
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TRLINE_ACCID	string(240)	Transaction Line Konto ID		
TRLINE_AMNT	decimal	Transaction Line Betrag		
TRLINE_AMNTP	string(240)	Transaction Line Summe Typ		
TRLINE_ARTGRPID	string(240)	Transaction Line Article Group ID		
TRLINE_BANKACCNR	string(240)	Transaction Line Bankkontonummer		
TRLINE_BANKIDCD	string(240)	Transaction Line Bank ID Code		
TRLINE_COSTID	string(240)	Transaction Line Cost ID		
TRLINE_CURRENCY_CURAMNT	decimal			
TRLINE_CURRENCY_CURCODE	string(240)			
TRLINE_CUSTSUPID	string(240)	Transaction Line Identifikation		
TRLINE_DESCRIPTION	string	Transaction Line Beschreibung		
TRLINE_DOCREF	string(999)	Transaction Line Document Reference		
TRLINE_EFFDATE	datetime	Transaction Line Gültigkeitsdatum		
TRLINE_INVREF	string(999)	Transaction Line Invoice Reference		
TRLINE_MATCHKEYID	string(240)	Transaction Line Match Key ID		
TRLINE_NR	string(240)	Transaction Line Number		
TRLINE_ORDERREF	string(999)	Transaction Line Auftragsreferenz		
TRLINE_PRODID	string(240)	Transaction Line Produkt ID		
TRLINE_PROJID	string(240)	Transaction Line Projekt ID		
TRLINE_QNTITY	int64	Transaction Line Menge		
TRLINE_QNTITYID	string(240)	Transaction Line Quantity ID		
TRLINE_RECEIVINGDOCREF	string(999)	Transaction Line Receiving Document Reference		
TRLINE_RECREF	string(999)	Transaction Line Record Reference		
TRLINE_SHIPDOCREF	string(999)	Transaction Line Shipping Document		

Name	Data Type	Label	Required	Documentation
		Reference		
TRLINE_TRANSACTION_AMNT	decimal	Verhandlung Betrag		
TRLINE_TRANSACTION_AMNTP	string(240)	Verhandlung Summe Typ		
TRLINE_TRANSACTION_DESC	string	Verhandlung Beschreibung		
TRLINE_TRANSACTION_JOURNAL_BANKACCNR	string(240)	Journal Bankkontonummer		
TRLINE_TRANSACTION_JOURNAL_DESCRIPTION	string	Journal Beschreibung		
TRLINE_TRANSACTION_JOURNAL_JRNID	string(240)	Journal Journal ID		
TRLINE_TRANSACTION_JOURNAL_JRNTP	string(240)	Journal Journal Typ		
TRLINE_TRANSACTION_JOURNAL_OFFSETACCID	string(240)	Journal Offset Account ID		
TRLINE_TRANSACTION_JOURNAL_TRANSACTIONS_LINESCOUNT	int64	Verhandlung Lines Count		
TRLINE_TRANSACTION_JOURNAL_TRANSACTIONS_TOTALCREDIT	decimal	Verhandlung Gesamtguthaben		
TRLINE_TRANSACTION_JOURNAL_TRANSACTIONS_TOTALDEBIT	decimal	Verhandlung Total Debit		
TRLINE_TRANSACTION_NR	string(240)	Verhandlung Number		
TRLINE_TRANSACTION_PERIODNUMBER	int64	Verhandlung Period Number		
TRLINE_TRANSACTION_SOURCEID	string(240)	Verhandlung Quellen-Kennzahl		
TRLINE_TRANSACTION_TRDT	datetime	Verhandlung Datum		
TRLINE_TRANSACTION_USERID	string(240)	Verhandlung Benutzer-Kennung		
TRLINE_WORKCOSTARRREF	string(999)	Transaction Line Work Cost Arrangement Reference		
VATAMNT	decimal			
VATAMNTP	string(240)			
VATID	string(240)			
VATPERC	decimal			

3.1.29 TransactionRegisters

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company

XPath: /xaf:transactions

Table Columns

The columns of the table TransactionRegisters are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_COMPANYIDENT	string(240)	Firma Firmenkennung		
COMPANY_COMPANYNAME	string(999)	Firma Firmenname		
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
COMPANY_TAXREGIDENT	string(240)	Firma Tax Registration Identification		
COMPANY_TAXREGISTRATIONCOUNTRY	string(240)	Firma Tax Registration Country		
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
LINECOUNT	int64			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
TOTALCREDIT	decimal			
TOTALDEBIT	decimal			

3.1.30 Transactions

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company/xaf:transactions

XPath: /xaf:journal/xaf:transaction

Table Columns

The columns of the table Transactions are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AMNT	decimal			
AMNTP	string(240)			
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
DESC	string			
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
JOURNAL_BANKACCNR	string(240)	Journal Bankkontonummer		
JOURNAL_DESCRIPTION	string	Journal Beschreibung		
JOURNAL_JRNID	string(240)	Journal Journal ID		
JOURNAL_JRNTYP	string(240)	Journal Journal Typ		
JOURNAL_OFFSETACCID	string(240)	Journal Offset Account ID		
JOURNAL_TRANSACTIONS_LINES COUNT	int64	Verhandlung Lines Count		
JOURNAL_TRANSACTIONS_TOTA LCREDIT	decimal	Verhandlung Gesamtguthaben		
JOURNAL_TRANSACTIONS_TOTA LDEBIT	decimal	Verhandlung Total Debit		
NR	string(240)			
PERIODNUMBER	int64			
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
SOURCEID	string(240)			
TRDT	datetime			
USERID	string(240)			

3.1.31 VatCodes

Catalog: XAF

The data in this table is partitioned per value of the COMPANY_NAME column.

Retrieve: true

Topic: auditfile

Base XPath: /xaf:auditfile/xaf:company

XPath: /xaf:vatCodes/xaf:vatCode

Table Columns

The columns of the table VatCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
AUDIT_FILE_VERSION	string(240)		<input type="checkbox"/>	
COMPANY_ADDRESS	string(240)		<input type="checkbox"/>	
COMPANY_CITY	string(240)		<input type="checkbox"/>	
COMPANY_ID	string(240)		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
COMPANY_POSTAL_CODE	string(240)		<input type="checkbox"/>	
COMPANY_TAX_REG_IDENT	string(240)		<input type="checkbox"/>	
FILE_CURRENCY_CODE	string(240)		<input type="checkbox"/>	
FILE_DATE_CREATED	string(240)		<input type="checkbox"/>	
FISCAL_YEAR_END_DATE	datetime		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input checked="" type="checkbox"/>	
FISCAL_YEAR_START_DATE	datetime		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input checked="" type="checkbox"/>	
PRODUCT_ID	string(240)		<input type="checkbox"/>	
PRODUCT_VERSION	string(240)		<input type="checkbox"/>	
VATCODES_COMPANY_COMPANYID	string(240)	Firma Firmenkennung		
VATCODES_COMPANY_COMPANYNAME	string(999)	Firma Firmenname		
VATCODES_COMPANY_TAXREGIDENT	string(240)	Firma Tax Registration Identification		
VATCODES_COMPANY_TAXREGISTRATIONCOUNTRY	string(240)	Firma Tax Registration Country		
VATDESC	string(999)			
VATID	string(240)			
VATTOCLAIMACCID	string(240)			
VATTOPAYACCID	string(240)			

4 Schema: CodeValues

4.1 Tables

4.1.1 AccountTypeCodes: XAF 3.2 Domain AccountTypeCodes

Lookup-table that translates code values of the domain 'AccountTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain AccountTypeCodes

Example: The code value 'B' means 'Balance'.

Retrieve: true

View Columns

The columns of the view AccountTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
B	Balance
M	Mixed
P	Profit and Loss

4.1.2 BasicTypeCodes: XAF 3.2 Domain BasicTypeCodes

Lookup-table that translates code values of the domain 'BasicTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain BasicTypeCodes

Example: The code value '02' means 'Cost codes / Cost ID'.

Retrieve: true

View Columns

The columns of the view BasicTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
02	Cost codes / Cost ID
03	Product codes / Product ID
04	Project codes / Project ID
05	Article Group codes / Article Group ID
12	Journal codes / Journal ID
14	Quantity codes / Quantity ID
23	Relationship codes / Relationship ID
29	Source codes / Source ID
30	User codes / User ID

4.1.3 CustomerSupplierTypeCodes: XAF 3.2 Domain CustomerSupplierTypeCodes

Lookup-table that translates code values of the domain 'CustomerSupplierTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain CustomerSupplierTypeCodes

Example: The code value 'B' means 'Both Customer and Supplier'.

Retrieve: true

View Columns

The columns of the view CustomerSupplierTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
B	Both Customer and Supplier
C	Customer
O	Other, no Customer or Supplier
S	Supplier

4.1.4 InvoiceDebitCreditTypeCodes: XAF 3.2 Domain InvoiceDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'InvoiceDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain InvoiceDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view InvoiceDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.5 InvoicePurchaseSalesTypeCodes: XAF 3.2 Domain InvoicePurchaseSalesTypeCodes

Lookup-table that translates code values of the domain 'InvoicePurchaseSalesTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain InvoicePurchaseSalesTypeCodes

Example: The code value 'P' means 'Purchase'.

Retrieve: true

View Columns

The columns of the view `InvoicePurchaseSalesTypeCodes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
P	Purchase
S	Sales

4.1.6 JournalTypeCodes: XAF 3.2 Domain JournalTypeCodes

Lookup-table that translates code values of the domain 'JournalTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain JournalTypeCodes

Example: The code value 'B' means 'Bank'.

Retrieve: true

View Columns

The columns of the view `JournalTypeCodes` are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
B	Bank
C	Cash

Code	Description
G	Goods (received/sent)
M	Memo / Daybook
O	Opening Balance
P	Purchases
S	Sales
T	Production
Y	Payroll
Z	Other

4.1.7 OpeningBalanceLineDebitCreditTypeCodes: XAF 3.2 Domain OpeningBalanceLineDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'OpeningBalanceLineDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain OpeningBalanceLineDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view OpeningBalanceLineDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.8 SubledgerLineAmmountDebitCreditTypeCodes: XAF 3.2 Domain SubledgerLineAmmountDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'SubledgerLineAmmountDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain SubledgerLineAmmountDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view SubledgerLineAmmountDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.9 SubledgerLineDebitCreditTypeCodes: XAF 3.2 Domain SubledgerLineDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'SubledgerLineDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain SubledgerLineDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view SubledgerLineDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.

Name	Data Type	Label	Required	Documentation
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.10 SubledgerLineInvoiceDebitCreditTypeCodes: XAF 3.2 Domain SubledgerLineInvoiceDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'SubledgerLineInvoiceDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain SubledgerLineInvoiceDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view SubledgerLineInvoiceDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.11 SubledgerLineInvoicePurchaseSalesTypeCodes: XAF 3.2 Domain SubledgerLineInvoicePurchaseSalesTypeCodes

Lookup-table that translates code values of the domain 'SubledgerLineInvoicePurchaseSalesTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain SubledgerLineInvoicePurchaseSalesTypeCodes

Example: The code value 'P' means 'Purchase'.

Retrieve: true

View Columns

The columns of the view SubledgerLineInvoicePurchaseSalesTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
P	Purchase
S	Sales

4.1.12 SubledgerLineMutationTypeCodes: XAF 3.2 Domain SubledgerLineMutationTypeCodes

Lookup-table that translates code values of the domain 'SubledgerLineMutationTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain SubledgerLineMutationTypeCodes

Example: The code value 'I' means 'Invoice'.

Retrieve: true

View Columns

The columns of the view SubledgerLineMutationTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
I	Invoice
P	Payment
Z	Other

4.1.13 SubledgerTypeCodes: XAF 3.2 Domain SubledgerTypeCodes

Lookup-table that translates code values of the domain 'SubledgerTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain SubledgerTypeCodes

Example: The code value 'CS' means 'Customers / Suppliers'.

Retrieve: true

View Columns

The columns of the view SubledgerTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
CS	Customers / Suppliers
CU	Customers
SU	Suppliers
ZZ	Other

4.1.14 TransactionAmountDebitCreditTypeCodes: XAF 3.2 Domain TransactionAmountDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'TransactionAmountDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain TransactionAmountDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view TransactionAmountDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.15 TransactionLineAmountDebitCreditTypeCodes: XAF 3.2 Domain TransactionLineAmountDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'TransactionLineAmountDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain TransactionLineAmountDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view TransactionLineAmountDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

4.1.16 VATAmountDebitCreditTypeCodes: XAF 3.2 Domain VATAmountDebitCreditTypeCodes

Lookup-table that translates code values of the domain 'VATAmountDebitCreditTypeCodes' into descriptions.

Catalog: XAF

Schema: CodeValues

Label: Domain VATAmountDebitCreditTypeCodes

Example: The code value 'C' means 'Credit'.

Retrieve: true

View Columns

The columns of the view VATAmountDebitCreditTypeCodes are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
code	string(240)		<input checked="" type="checkbox"/>	Unique code within the domain.
description	string(240)		<input type="checkbox"/>	Meaning of the unique code within the domain.
domain	string(240)		<input checked="" type="checkbox"/>	Each domain defines a map of codes to values.

Values

Code	Description
C	Credit
D	Debit

5 Schema: Views

5.1 Views

5.1.1 TrialBalancePerPeriod

Catalog: XAF

Schema: Views

This is a read-only view. The XAF 3.2 API may not support changing the data or the Invantive SQL driver for XAF 3.2 does not cover it. In the latter case, please use the table NativePlatformScalarRequests to upload data to the XAF 3.2 API.

View Columns

The columns of the view TrialBalancePerPeriod are shown below. Each column has an SQL data type.

Name	Data Type	Label	Required	Documentation
ACCDESC	string(999)		<input type="checkbox"/>	
ACCID	string(240)		<input type="checkbox"/>	
BALANCE	decimal		<input type="checkbox"/>	
COMPANY_NAME	string(1000)		<input type="checkbox"/>	
FISCAL_YEAR_NUMBER	string(240)		<input type="checkbox"/>	
INTERFACE_URL	string(4000)		<input type="checkbox"/>	
OPENING_BALANCE	decimal		<input type="checkbox"/>	
total_balance	decimal		<input checked="" type="checkbox"/>	
TRANSACTION_PERIODNUMBER	int64		<input type="checkbox"/>	

Index

- A -

ACCDESC 24, 59
 ACCID 24, 29, 41, 59
 AccountTypeCodes 49
 ACCTP 24
 AMNT 29, 32, 35, 41, 46
 AMNTTP 29, 32, 35, 41, 46
 analysis-enforce-row-uniqueness 2
 Anfangsbestand Beschreibung 5, 29, 32, 34
 Anfangsbestand Datum 5, 29, 32, 34
 Anfangsbestand Gesamtguthaben 5, 29, 32, 34
 Anfangsbestand Lines Count 5, 29, 32, 34
 Anfangsbestand Total Debit 5, 29, 32, 34
 ARTGRPID 32, 35, 41
 AUDIT_FILE_VERSION 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_ADDRESS 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_CITY 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_COMPANYIDENT 6, 7, 30, 45
 COMPANY_COMPANYNAME 6, 7, 30, 45
 COMPANY_ID 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_NAME 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_POSTAL_CODE 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_REG_IDENT 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_TAX_REG_IDENT 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 COMPANY_TAXREGIDENT 6, 7, 30, 45
 COMPANY_TAXREGISTRATIONCOUNTRY 6, 7, 30, 45
 COMPANY_TRANSACTIONS_LINESCOUNT 30
 COMPANY_TRANSACTIONS_TOTALCREDIT 30
 COMPANY_TRANSACTIONS_TOTALDEBIT 30
 COMPANYIDENT 5
 COMPANYNAME 5
 CompanyPostalCodes 6
 CompanyStreetAddresses 7
 CONTACT 8, 11
 COSTID 32, 35, 41
 Counter Party Change Information Benutzer-Kennung 9, 11, 13, 16, 18, 21, 23
 Counter Party Change Information Beschreibung 9, 11, 13, 16, 18, 21, 23
 Counter Party Change Information Datum/Zeit 9, 11, 13, 16, 18, 21, 23
 CounterParties 8
 CounterPartyBankAccounts 9
 CounterPartyHistories 11
 CounterPartyHistoryBankAccounts 13
 CounterPartyHistoryPostalCodes 16
 CounterPartyHistoryStreetAddresses 18
 CounterPartyPostalCodes 21
 CounterPartyStreetAddresses 23
 COUNTRY 6, 7, 16, 18, 21, 23
 CURCODE 28
 CURRENCY_CURAMNT 35, 41
 CURRENCY_CURCODE 35, 41
 CUSTCREDITLIMIT 8, 11
 CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATE 9, 13, 16, 18, 21, 23

- B -

BALANCE 29, 41, 59
 BANKACCNR 9, 13, 40, 41
 BANKIDCD 9, 13, 41
 BASICDESC 25
 BASICID 25
 BASICTYPE 25
 BasicTypeCodes 49
 BINARYDATA 39
 bulk-delete-page-size-rows 2
 bulk-insert-page-size-bytes 2
 bulk-insert-page-size-rows 2
 COMPANYIDENT 5
 COMPANYNAME 5
 CompanyPostalCodes 6
 CompanyStreetAddresses 7
 CONTACT 8, 11
 COSTID 32, 35, 41
 Counter Party Change Information Benutzer-Kennung 9, 11, 13, 16, 18, 21, 23
 Counter Party Change Information Beschreibung 9, 11, 13, 16, 18, 21, 23
 Counter Party Change Information Datum/Zeit 9, 11, 13, 16, 18, 21, 23
 CounterParties 8
 CounterPartyBankAccounts 9
 CounterPartyHistories 11
 CounterPartyHistoryBankAccounts 13
 CounterPartyHistoryPostalCodes 16
 CounterPartyHistoryStreetAddresses 18
 CounterPartyPostalCodes 21
 CounterPartyStreetAddresses 23
 COUNTRY 6, 7, 16, 18, 21, 23
 CURCODE 28
 CURRENCY_CURAMNT 35, 41
 CURRENCY_CURCODE 35, 41
 CUSTCREDITLIMIT 8, 11
 CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATE 9, 13, 16, 18, 21, 23

- C -

Change Information Benutzer-Kennung 8, 11, 24
 Change Information Beschreibung 8, 11, 24
 Change Information Datum/Zeit 8, 11, 24
 CHANGEINFO_CHANGEDATE 8, 11, 24
 CHANGEINFO_CHANGEDESCRIPTION 8, 11, 24
 CHANGEINFO_USERID 8, 11, 24
 CITY 6, 7, 16, 18, 21, 23
 COMMERCENR 8, 11
 Companies 5
 COMPANYIDENT 5
 COMPANYNAME 5
 CompanyPostalCodes 6
 CompanyStreetAddresses 7
 CONTACT 8, 11
 COSTID 32, 35, 41
 Counter Party Change Information Benutzer-Kennung 9, 11, 13, 16, 18, 21, 23
 Counter Party Change Information Beschreibung 9, 11, 13, 16, 18, 21, 23
 Counter Party Change Information Datum/Zeit 9, 11, 13, 16, 18, 21, 23
 CounterParties 8
 CounterPartyBankAccounts 9
 CounterPartyHistories 11
 CounterPartyHistoryBankAccounts 13
 CounterPartyHistoryPostalCodes 16
 CounterPartyHistoryStreetAddresses 18
 CounterPartyPostalCodes 21
 CounterPartyStreetAddresses 23
 COUNTRY 6, 7, 16, 18, 21, 23
 CURCODE 28
 CURRENCY_CURAMNT 35, 41
 CURRENCY_CURCODE 35, 41
 CUSTCREDITLIMIT 8, 11
 CUSTOMERSUPPLIER_CHANGEINFO_CHANGEDATE 9, 13, 16, 18, 21, 23

CUSTOMERSUPPLIER_CHANGEINFO_CHANGED
SCRIPTION 9, 13, 16, 18, 21, 23 ORY_CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIST
CUSTOMERSUPPLIER_CHANGEINFO_USERID COUNTRY 13, 16, 18
13, 16, 18, 21, 23 CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIST
CUSTOMERSUPPLIER_COMMERCENR 9, 13, 16, 18 ORY_CUSTOMERSUPPLIER_TELEPHONE 13,
18, 21, 23 16, 18
CUSTOMERSUPPLIER_CONTACT 9, 13, 16, 18 CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIST
21, 23 ORY_CUSTOMERSUPPLIER_WEBSITE 13, 16,
CUSTOMERSUPPLIER_CUSTCREDITLIMIT 9, 13, 16, 18 CUSTOMERSUPPLIER_CUSTSUPGRPID 9, 13,
16, 18, 21, 23 16, 18, 21, 23
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIER_CUSTSUPID 9, 13, 16, 18,
ORY_CUSTOMERSUPPLIER_CHANGEINFO_CHAN 21, 23
GEDATETIME 13, 16, 18 CUSTOMERSUPPLIER_CUSTSUPNAME 9, 13,
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS 16, 18, 21, 23
ORY_CUSTOMERSUPPLIER_CHANGEINFO_CHA CUSTOMERSUPPLIER_CUSTSUPT 9, 13, 16,
GEDESCRIPTION 13, 16, 18 18, 21, 23
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIER_EMAIL 9, 13, 16, 18, 21,
ORY_CUSTOMERSUPPLIER_CHANGEINFO_USERB
D 13, 16, 18 CUSTOMERSUPPLIER_FAX 9, 13, 16, 18, 21, 23
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIER_RELATIONSHIPID 9, 13,
ORY_CUSTOMERSUPPLIER_COMMERCENR 13, 16, 18, 21, 23
16, 18 CUSTOMERSUPPLIER_SUPPLIERLIMIT 9, 13, 16,
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS 18, 21, 23
ORY_CUSTOMERSUPPLIER_CONTACT 13, 16, 18 CUSTOMERSUPPLIER_TAXREGIDENT 9, 13, 16,
18 18, 21, 23
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIER_TAXREGISTRATIONCOUNT
ORY_CUSTOMERSUPPLIER_CUSTCREDITLIMIT Y 9, 13, 16, 18, 21, 23
13, 16, 18 CUSTOMERSUPPLIER_TELEPHONE 9, 13, 16,
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS 18, 21, 23
ORY_CUSTOMERSUPPLIER_CUSTSUPGRPID CUSTOMERSUPPLIER_WEBSITE 9, 13, 16, 18,
13, 16, 18 21, 23
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
ORY_CUSTOMERSUPPLIER_CUSTSUPID 13, 16 LIER_CHANGEINFO_CHANGEDATEETIME 11
18 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS LIER_CHANGEINFO_CHANGEDESCRIPTION 11
ORY_CUSTOMERSUPPLIER_CUSTSUPNAME 13 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
16, 18 LIER_CHANGEINFO_USERID 11
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
ORY_CUSTOMERSUPPLIER_CUSTSUPT 13, 16 LIER_COMMERCENR 11
18 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS LIER_CONTACT 11
ORY_CUSTOMERSUPPLIER_EMAIL 13, 16, 18 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS LIER_CUSTCREDITLIMIT 11
ORY_CUSTOMERSUPPLIER_FAX 13, 16, 18 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS LIER_CUSTSUPGRPID 11
ORY_CUSTOMERSUPPLIER_RELATIONSHIPID CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
13, 16, 18 LIER_CUSTSUPID 11
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
ORY_CUSTOMERSUPPLIER_SUPPLIERLIMIT 13 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
16, 18 LIER_CUSTSUPNAME 11
CUSTOMERSUPPLIER_CUSTOMERSUPPLIERHIS CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
ORY_CUSTOMERSUPPLIER_TAXREGIDENT 13 LIER_CUSTSUPT 11
16, 18 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
LIER_EMAIL 11
CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPP
LIER_FAX 11

CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPPLIERNDDATE 28
 LIER_RELATIONSHIPID 11 ENDDATEPERIOD 31
 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPPLIERTIMEPERIOD 31
 LIER_SUPPLIERLIMIT 11
 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPPLIERTAXREGIDENT 11
- F -
 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPPLIERTAXREGISTRATIONCOUNTRY 11 FAX 8, 11
 CUSTOMERSUPPLIERHISTORY_CUSTOMERSUPPLFILE_CURRENCY_CODE 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 LIER_WEBSITE 11 FILE_DATE_CREATED 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 CustomerSupplierTypeCodes 50 Firma Firmenkennung 6, 7, 29, 30, 45, 48
 CUSTSUPGRPID 8, 11 Firma Firmenname 6, 7, 29, 30, 45, 48
 CUSTSUPID 8, 11, 32, 35, 41 Firma Tax Registration Country 6, 7, 29, 30, 45, 48
 CUSTSUPNAME 8, 11 Firma Tax Registration Identification 6, 7, 29, 30, 45, 48
 CUSTSUPTP 8, 11
- D -
 DATECREATED 28 FISCAL_YEAR_END_DATE 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 DESC 32, 35, 46 FISCAL_YEAR_NUMBER 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48, 59
 DESCRIPTION 40, 41 FISCAL_YEAR_START_DATE 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
 DOCREF 32, 35, 41 FISCALYEAR 28 force-case-sensitive-identifiers 2
 Domain AccountTypeCodes 49 forced-casing-identifiers 2
 Domain BasicTypeCodes 49
 Domain CustomerSupplierTypeCodes 50
 Domain InvoiceDebitCreditTypeCodes 51
 Domain InvoicePurchaseSalesTypeCodes 51
 Domain JournalTypeCodes 52
 Domain OpeningBalanceLineDebitCreditTypeCodes 53
 Domain SubledgerLineAmountDebitCreditTypeCodes 53
- G -
 Domain SubledgerLineDebitCreditTypeCodes 54 Gegenpartei Art 9, 11, 13, 16, 18, 21, 23
 Domain SubledgerLineInvoiceDebitCreditTypeCodes 21, 23 Gegenpartei Commerce Number 9, 11, 13, 16, 18, 21, 23
 55 Gegenpartei Customer Credit Limit 9, 11, 13, 16, 18, 21, 23
 Domain SubledgerLineInvoicePurchaseSalesTypeCodes 56 Gegenpartei E-Mail 9, 11, 13, 16, 18, 21, 23
 Domain SubledgerLineMutationTypeCodes 56 Gegenpartei Gruppen-ID 9, 11, 13, 16, 18, 21, 23
 Domain SubledgerTypeCodes 57 Gegenpartei ID der Beziehung 9, 11, 13, 16, 18, 21, 23
 Domain TransactionAmountDebitCreditTypeCodes 57 Gegenpartei Identifikation 9, 11, 13, 16, 18, 21, 23
 58 Gegenpartei Kontaktperson 9, 11, 13, 16, 18, 21, 23
 Domain VATAmountDebitCreditTypeCodes 59 Gegenpartei Name 9, 11, 13, 16, 18, 21, 23
 Driver 1 Gegenpartei Supplier Credit Limit 9, 11, 13, 16, 18, 21, 23
- E -
 EFFDATE 41 Gegenpartei Tax Registration Country 9, 11, 13, 16, 18, 21, 23
 EMAIL 8, 11 Gegenpartei Tax Registration Identification 9, 11, 13, 16, 18, 21, 23
 Gegenpartei Telefax 9, 11, 13, 16, 18, 21, 23

Gegenpartei Telefon 9, 11, 13, 16, 18, 21, 23
 Gegenpartei Website 9, 11, 13, 16, 18, 21, 23
 GeneralLedgerAccounts 24
 GeneralLedgerBasics 25
 GeneralLedgerTaxonomies 26
 GeneralLedgerTaxonomyElements 27

- H -

Headers 28

- I -

INTERFACE_URL 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48, 59
 invantive-sql-compress-sparse-arrays 2
 invantive-sql-correct-invalid-date 2
 invantive-sql-forward-filters-to-data-containers 2
 invantive-sql-share-byte-arrays 2
 invantive-sql-share-strings 2
 invantive-sqlshuffle-fetch-results-data-containers
 invantive-use-cache 2
 INVDT 32, 35
 INVUEDT 32, 35
 InvoiceDebitCreditTypeCodes 51
 InvoicePurchaseSalesTypeCodes 51
 INVPURSALTP 32, 35
 INVREF 32, 35, 41
 INVTP 32, 35

- J -

Journal Bankkontonummer 41, 43, 46
 Journal Beschreibung 41, 43, 46
 Journal Journal ID 41, 43, 46
 Journal Journal Typ 41, 43, 46
 Journal Offset Account ID 41, 43, 46
 JOURNAL_BANKACCR 46
 JOURNAL_DESCRIPTION 46
 JOURNAL_JRNID 46
 JOURNAL_JRNTP 46
 JOURNAL_OFFSETACCID 46
 JOURNAL_TRANSACTIONS_LINESCOUNT 46
 JOURNAL_TRANSACTIONS_TOTALCREDIT 46
 JOURNAL_TRANSACTIONS_TOTALDEBIT 46
 JournalTypeCodes 52
 JRNID 35, 40
 JRNTP 40

- L -

LEADCODE 24
 LEADCROSSREF 24
 LEADDDESCRIPTION 24
 LEADREFERENCE 24
 LINESCOUNT 30, 34, 38, 45
 log-native-calls-to-disk-max-events 2
 log-native-calls-to-disk-max-seconds 2
 log-native-calls-to-disk-on-error 2
 log-native-calls-to-disk-on-success 2
 log-native-calls-to-trace 2

- M -

MATCHKEYID 32, 35, 41
 maximum-length-identifiers 2
 max-url-length-accepted 2
 max-url-length-desired 2
 minimum-length-text 2
 MUTTP 32, 35

- N -

NAME 39
 NR 29, 32, 35, 41, 46
 NUMBER 6, 7, 16, 18, 21, 23
 NUMBEREXTENSION 6, 7, 16, 18, 21, 23

- O -

OBLINENR 32
 OBSUBLEDGER_LINESCOUNT 32
 OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_LINESCOUNT 32
 OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_OPBALDATE 32
 OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_OPBALDESC 32
 OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_TOTALCREDIT 32
 OBSUBLEDGER_OBSUBLEDGERS_OPENINGBALANCE_TOTALDEBIT 32
 OBSUBLEDGER_SBDESC 32
 OBSUBLEDGER_SBTTYPE 32
 OBSUBLEDGER_TOTALCREDIT 32
 OBSUBLEDGER_TOTALDEBIT 32
 OBSUBLEDGERS_OPENINGBALANCE_LINESCOUNT 34

OBSUBLEDGERS_OPENINGBALANCE_OPBALDATEPRODUCT_ID 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
OBSUBLEDGERS_OPENINGBALANCE_OPBALDESC 34
C 34
OBSUBLEDGERS_OPENINGBALANCE_TOTALCREDIT 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48
DIT 34
OBSUBLEDGERS_OPENINGBALANCE_TOTALDEBIT 32, 35, 41
T 34
OFFSETACCID 40
OPBALDATE 30
OPBALDESC 30
Opening Balance Subledger Art 32
Opening Balance Subledger Beschreibung 32
Opening Balance Subledger Gesamtguthaben 32
Opening Balance Subledger Lines Count 32
Opening Balance Subledger Total Debit 32
OPENING_BALANCE 59
OPENINGBALANCE_COMPANY_COMPANYIDENT RECEIVINGDOCREF 41
29 RECREF 32, 35, 41
OPENINGBALANCE_COMPANY_COMPANYNAME REGION 6, 7, 16, 18, 21, 23
29 RELATIONSHIPID 8, 11
OPENINGBALANCE_COMPANY_TAXREGIDENT requested-page-size 2
29 requests-parallel-max 2
OPENINGBALANCE_COMPANY_TAXREGISTRATIO result-set-memory-cache 2
NCOUNTRY 29
OPENINGBALANCE_COMPANY_TRANSACTIONS_L
INESCOUNT 29
OPENINGBALANCE_COMPANY_TRANSACTIONS_T
OTALCREDIT 29 SBDESC 34, 38
OPENINGBALANCE_COMPANY_TRANSACTIONS_SBLINE_AMNT 37
OTALDEBIT 29 SBLINE_AMNTP 37
OPENINGBALANCE_LINESCOUNT 5, 29 SBLINE_ARTGRPID 37
OPENINGBALANCE_OPBALDATE 5, 29 SBLINE_COSTID 37
OPENINGBALANCE_OPBALDESC 5, 29 SBLINE_CURRENCY_CURAMNT 37
OPENINGBALANCE_TOTALCREDIT 5, 29 SBLINE_CURRENCY_CURCODE 37
OPENINGBALANCE_TOTALDEBIT 5, 29 SBLINE_CUSTSUPID 37
OpeningBalanceLineDebitCreditTypeCodes 53 SBLINE_DESC 37
OpeningBalanceLines 29 SBLINE_DOCREF 37
OpeningBalances 30 SBLINE_INVDT 37
ORDERREF 41 SBLINE_INVDUEDT 37
SBLINE_INVPURSALTP 37
SBLINE_INVREF 37
SBLINE_INVTP 37
SBLINE_JRNID 37
SBLINE_MATCHKEYID 37
SBLINE_MUTTP 37
SBLINE_NR 37
SBLINE_PRODID 37
SBLINE_PROJID 37
SBLINE_QNTITY 37
SBLINE_QNTITYID 37
SBLINE_RECREF 37
SBLINE_TRLINENR 37

- Q -**- R -****- S -****- P -**

partition-slot-based-rate-limit-length-ms 2
partition-slot-based-rate-limit-slots 2
PERIODDESC 31
PERIODNUMBER 31, 46
Periods 31
POSTALCODE 6, 7, 16, 18, 21, 23
pre-request-delay-ms 2
PRODID 32, 35, 41

SBLINE_TRNR 37
 SBTYPE 34, 38
 SHIPDOCREF 41
 slot-based-rate-limit-length-ms 2
 slot-based-rate-limit-slots 2
 SOFTWAREDESC 28
 SOFTWAREVERSION 28
 SOURCEID 46
 standardize-identifiers 2
 standardize-identifiers-casing 2
 STARTDATE 28
 STARTDATEPERIOD 31
 STARTTIMEPERIOD 31
 STREETNAME 6, 7, 16, 18, 21, 23
 Subledger Art 35
 Subledger Beschreibung 35
 Subledger Gesamtguthaben 35
 Subledger Line Article Group ID 37
 Subledger Line Beschreibung 37
 Subledger Line Betrag 37
 Subledger Line Cost ID 37
 Subledger Line Document Reference 37
 Subledger Line Identifikation 37
 Subledger Line Invoice Due Date 37
 Subledger Line Invoice Reference 37
 Subledger Line Journal ID 37
 Subledger Line Match Key ID 37
 Subledger Line Menge 37
 Subledger Line Mutation Type 37
 Subledger Line Number 37
 Subledger Line Produkt ID 37
 Subledger Line Projekt ID 37
 Subledger Line Purchase/Sales Type 37
 Subledger Line Quantity ID 37
 Subledger Line Rechnungsdatum 37
 Subledger Line Record Reference 37
 Subledger Line Summe Typ 37
 Subledger Lines Count 35
 Subledger Total Debit 35
 SUBLEDGER_LINESCOUNT 35
 SUBLEDGER_SBDESC 35
 SUBLEDGER_SBTYP 35
 SUBLEDGER_TOTALCREDIT 35
 SUBLEDGER_TOTALDEBIT 35
 SubledgerLineAmmountDebitCreditTypeCodes
 SubledgerLineDebitCreditTypeCodes 54
 SubledgerLineInvoiceDebitCreditTypeCodes 55
 SubledgerLineInvoicePurchaseSalesTypeCodes
 SubledgerLineMutationTypeCodes 56
 SubledgerOpeningBalanceLines 32
 SubledgerOpeningBalances 34

SubledgerTransactionLines 35
 SubledgerTransactionLineVats 37
 SubledgerTransactions 38
 SubledgerTypeCodes 57
 SUPPLIERLIMIT 8, 11

- T -
 TAXONOMIES_ACCDESC 26
 TAXONOMIES_ACCID 26
 TAXONOMIES_ACCTP 26
 TAXONOMIES_CHANGEINFO_CHANGEDATETIME 26
 TAXONOMIES_CHANGEINFO_CHANGEDESCRIPTI
ON 26
 TAXONOMIES_CHANGEINFO_USERID 26
 TAXONOMIES_LEADCODE 26
 TAXONOMIES_LEADCROSSREF 26
 TAXONOMIES_LEADDESCRIPTION 26
 TAXONOMIES_LEADREFERENCE 26
 TAXONOMY_TAXOREF 27
 TAXOREF 26
 TAXREGIDENT 5, 8, 11
 TAXREGISTRATIONCOUNTRY 5, 8, 11
 TELEPHONE 8, 11
 total_balance 59
 TOTALCREDIT 30, 34, 38, 45
 TOTALDEBIT 30, 34, 38, 45
 Transaction Line Article Group ID 43
 Transaction Line Auftragsreferenz 43
 Transaction Line Bank ID Code 43
 Transaction Line Bankkontonummer 43
 Transaction Line Beschreibung 43
 Transaction Line Betrag 43
 Transaction Line Cost ID 43
 Transaction Line Document Reference 43
 Transaction Line Gültigkeitsdatum 43
 Transaction Line Identifikation 43
 Transaction Line Invoice Reference 43
 Transaction Line Konto ID 43
 Transaction Line Match Key ID 43
 Transaction Line Menge 43
 Transaction Line Number 43
 Transaction Line Produkt ID 43
 Transaction Line Projekt ID 43
 Transaction Line Quantity ID 43
 Transaction Line Receiving Document Reference 43
 Transaction Line Record Reference 43
 Transaction Line Shipping Document Reference 43
 Transaction Line Summe Typ 43

Transaction Line Work Cost Arrangement Reference
 TRANSACTION_AMNT 41
 TRANSACTION_AMNTP 41
 TRANSACTION_DESC 41
 TRANSACTION_JOURNAL_BANKACCNR 41
 TRANSACTION_JOURNAL_DESCRIPTION 41
 TRANSACTION_JOURNAL_JRNID 41
 TRANSACTION_JOURNAL_JRNP 41
 TRANSACTION_JOURNAL_OFFSETACCID 41
 TRANSACTION_JOURNAL_TRANSACTIONS_LINESCOUNT 41
 TRANSACTION_JOURNAL_TRANSACTIONS_TOTALCREDIT 41
 TRANSACTION_JOURNAL_TRANSACTIONS_TOTALDEBIT 41
 TRANSACTION_NR 41
 TRANSACTION_PERIODNUMBER 41, 59
 TRANSACTION_SOURCEID 41
 TRANSACTION_TRDT 41
 TRANSACTION_USERID 41
 TransactionAmountDebitCreditTypeCodes 57
 TransactionAttachments 39
 TransactionJournals 40
 TransactionLineAmountDebitCreditTypeCodes 58
 TransactionLines 41
 TransactionLineVats 43
 TransactionRegisters 45
 Transactions 46
 TRANSACTIONS_LINESCOUNT 5, 40
 TRANSACTIONS_TOTALCREDIT 5, 40
 TRANSACTIONS_TOTALDEBIT 5, 40
 Transaktionen Gesamtguthaben 5
 Transaktionen Lines Count 5
 Transaktionen Total Debit 5
 TRDT 46
 TrialBalancePerPeriod 59
 TRLINE_ACCID 43
 TRLINE_AMNT 43
 TRLINE_AMNTP 43
 TRLINE_ARTGRPID 43
 TRLINE_BANKACCNR 43
 TRLINE_BANKIDCD 43
 TRLINE_COSTID 43
 TRLINE_CURRENCY_CURAMNT 43
 TRLINE_CURRENCY_CURCODE 43
 TRLINE_CUSTSUPID 43
 TRLINE_DESCRIPTION 43
 TRLINE_DOCREF 43
 TRLINE_EFFDATE 43
 TRLINE_INVREF 43
 TRLINE_MATCHKEYID 43
 TRLINE_ORDERREF 43
 TRLINE_PRODID 43
 TRLINE_PROJID 43
 TRLINE_QNTITY 43
 TRLINE_QNTITYID 43
 TRLINE_RECEIVINGDOCREF 43
 TRLINE_RECREF 43
 TRLINE_SHIPDOCREF 43
 TRLINE_TRANSACTION_AMNT 43
 TRLINE_TRANSACTION_AMNTP 43
 TRLINE_TRANSACTION_DESC 43
 TRLINE_TRANSACTION_JOURNAL_BANKACCNR 43
 TRLINE_TRANSACTION_JOURNAL_DESCRIPTION 43
 TRLINE_TRANSACTION_JOURNAL_JRNID 43
 TRLINE_TRANSACTION_JOURNAL_JRNP 43
 TRLINE_TRANSACTION_JOURNAL_OFFSETACCID 43
 TRLINE_TRANSACTION_JOURNAL_TRANSACTIONS_LINESCOUNT 43
 TRLINE_TRANSACTION_JOURNAL_TRANSACTIONS_TOTALCREDIT 43
 TRLINE_TRANSACTION_JOURNAL_TRANSACTIONS_TOTALDEBIT 43
 TRLINE_TRANSACTION_NR 43
 TRLINE_TRANSACTION_PERIODNUMBER 43
 TRLINE_TRANSACTION_SOURCEID 43
 TRLINE_TRANSACTION_TRDT 43
 TRLINE_TRANSACTION_USERID 43
 TRLINE_WORKCOSTARRREF 43
 TRLINENR 35
 TRNR 35

- U -

use-exact-online-extensions 2
 use-metadata-memory-cache 2
 use-result-memory-cache 2
 USERID 46

- V -

VATAMNT 37, 43
 VATAMNTP 37, 43
 VATAmountDebitCreditTypeCodes 59
 VatCodes 48
 VATCODES_COMPANY_COMPANYIDENT 48
 VATCODES_COMPANY_COMPANYNAME 48
 VATCODES_COMPANY_TAXREGIDENT 48

VATCODES_COMPANY_TAXREGISTRATIONCOUNT
RY 48
VATDESC 48
VATID 37, 43, 48
VATPERC 37, 43
VATTOCLAIMACCID 48
VATTOPAYACCID 48
Verhandlung Benutzer-Kennung 41, 43
Verhandlung Beschreibung 41, 43
Verhandlung Betrag 41, 43
Verhandlung Datum 41, 43
Verhandlung Gesamtguthaben 29, 30, 40, 41, 43, 46
Verhandlung Lines Count 29, 30, 40, 41, 43, 46
Verhandlung Number 41, 43
Verhandlung Period Number 41, 43
Verhandlung Quellen-Kennzahl 41, 43
Verhandlung Summe Typ 41, 43
Verhandlung Total Debit 29, 30, 40, 41, 43, 46

- W -

Währung Betrag 35, 41
Währung Währungscode 35, 41
WEBSITE 8, 11
WORKCOSTARRREF 41

- X -

xaf 1
XAF 3.2 1, 5, 6, 7, 8, 9, 11, 13, 16, 18, 21, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 34, 35, 37, 38, 39, 40, 41, 43, 45, 46, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59
Xaf32 1
xml-directories 2
xml-extension 2
xml-namespaces 2

